

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P641688

Luminaire Tested: ML5612LSVWFL97FS1E - 593WB - 600LM - 3500K

Issue Date: 2/17/2023

Test Information

Test Method: LM-79-2019
Report Number: P641688
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-97)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/17/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML5612LSVWFL97FS1E - 593WB - 600LM - 3500K
Description: ML56 RR, MILKY OPTIC, 5" WHITE BAFFLE TRIM
Light Source: (1) HCL SELECTABLE LUMEN LED 90CRI / 3500K CCT
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 870.5 lumens
Efficiency: N/A
Efficacy: 84.5 lumens/watt
Spacing Criteria (0/90/45): 1.16 / 1.16 / 1.14
Luminous Opening: Circular (Dia: 0.42' x H: 0')
CIE Type: Direct

Input Watts (W): 10.3
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P641688
CATALOG NUMBER: ML5612LSVWFL97FS1E - 593WB - 600LM - 3500K

Luminous Intensity Polar Plot





TEST NUMBER: P641688

CATALOG NUMBER: ML5612LSVWFL97FS1E - 593WB - 600LM - 3500K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	111	107	104	101	109	105	102	99	101	99	96	97	95	93	94	92	91	89																			
2	103	97	91	87	101	95	90	86	92	87	84	88	85	82	86	83	80	78																			
3	96	88	81	76	94	86	80	75	83	78	74	81	76	73	78	75	71	69																			
4	90	80	72	67	87	78	72	66	76	70	66	74	69	65	72	67	64	62																			
5	84	73	65	60	82	72	65	59	70	63	59	68	62	58	66	61	58	56																			
6	78	67	59	54	76	66	59	53	64	58	53	63	57	53	61	56	52	50																			
7	73	61	54	49	72	61	54	48	59	53	48	58	52	48	57	51	48	46																			
8	69	57	49	44	67	56	49	44	55	49	44	54	48	44	53	47	43	42																			
9	65	53	45	41	63	52	45	41	51	45	40	50	44	40	49	44	40	38																			
10	61	49	42	37	60	49	42	37	48	41	37	47	41	37	46	41	37	35																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	40568
5°	40437
10°	39967
15°	39351
20°	38643
25°	37793
30°	36361
35°	32900
40°	26103
45°	18554
50°	13239
55°	10267
60°	8794
65°	8219
70°	7871
75°	7686
80°	7365
85°	6521

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 18554 cd/sqm



TEST NUMBER: P641688

CATALOG NUMBER: ML5612LSVWFL97FS1E - 593WB - 600LM - 3500K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	48.3	5.6
10°-20°	135.6	15.6
20°-30°	199.3	22.9
30°-40°	208.9	24.0
40°-50°	131.3	15.1
50°-60°	69.1	7.9
60°-70°	43.8	5.0
70°-80°	26.3	3.0
80°-90°	7.8	0.9
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	383.3	44.0
0°-40°	592.2	68.0
0°-60°	792.6	91.1
0°-90°	870.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	870.5	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	514	
5°	510	48
15°	482	136
25°	434	199
35°	341	209
45°	166	131
55°	75	69
65°	44	44
75°	25	26
85°	7	8
90°	0	



TEST NUMBER: P641688

CATALOG NUMBER: ML5612LSVWFL97FS1E - 593WB - 600LM - 3500K

CANDELA DISTRIBUTION (FULL):

0°	
0°	513.9
2.5°	513.0
5°	510.3
7.5°	505.8
10°	498.6
12.5°	490.5
15°	481.5
17.5°	470.7
20°	460.0
22.5°	447.4
25°	433.9
27.5°	418.6
30°	398.9
32.5°	373.7
35°	341.4
37.5°	300.1
40°	253.3
42.5°	206.6
45°	166.2
47.5°	133.0
50°	107.8
52.5°	88.9
55°	74.6
57.5°	64.7
60°	55.7
62.5°	49.4
65°	44.0
67.5°	38.6
70°	34.1
72.5°	29.6
75°	25.2
77.5°	19.8
80°	16.2
82.5°	10.8
85°	7.2
87.5°	2.7
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)