

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P641705

Luminaire Tested: ML5612LSVWFL97FS1E - 594SNB - 600LM - 5000K

Issue Date: 2/17/2023

Test Information

Test Method: LM-79-2019
Report Number: P641705
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-102)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/17/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML5612LSVWFL97FS1E - 594SNB - 600LM - 5000K
Description: ML56 RR, MILKY OPTIC, 5" SATIN NICKLE GIMBAL TRIM
Light Source: (1) HCL SELECTABLE LUMEN LED 90CRI / 5000K CCT
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1043.6 lumens
Efficiency: N/A
Efficacy: 101.3 lumens/watt
Spacing Criteria (0/90/45): 1.19 / 1.19 / 1.26
Luminous Opening: Circular (Dia: 0.42' x H: 0')
CIE Type: Direct

Input Watts (W): 10.3
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P641705
CATALOG NUMBER: ML5612LSVWFL97FS1E - 594SNB - 600LM - 5000K

Luminous Intensity Polar Plot





TEST NUMBER: P641705
 CATALOG NUMBER: ML5612LSVWFL97FS1E - 594SNB - 600LM - 5000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	110	106	102	99	108	104	100	97	100	97	94	96	93	91	92	90	89	87																			
2	101	94	88	83	99	92	87	82	89	84	80	85	82	78	83	79	76	74																			
3	93	84	76	70	91	82	75	70	79	73	69	77	72	67	74	70	66	64																			
4	86	75	67	61	84	74	66	60	71	65	60	69	63	59	67	62	58	56																			
5	80	68	59	53	78	67	59	53	65	58	52	63	57	52	61	56	51	49																			
6	74	61	53	47	72	60	53	47	59	52	46	57	51	46	56	50	46	44																			
7	69	56	48	42	67	55	47	42	54	47	42	52	46	41	51	45	41	39																			
8	64	51	43	38	63	51	43	38	49	42	37	48	42	37	47	41	37	35																			
9	60	47	39	34	59	47	39	34	46	39	34	45	38	34	44	38	34	32																			
10	56	44	36	31	55	43	36	31	42	36	31	41	35	31	41	35	31	29																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	37063
5°	37054
10°	36865
15°	36482
20°	36039
25°	35259
30°	34173
35°	32775
40°	30760
45°	28256
50°	25397
55°	22200
60°	18756
65°	15709
70°	13156
75°	11194
80°	9683
85°	9601

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 28256 cd/sqm



TEST NUMBER: P641705

CATALOG NUMBER: ML5612LSVWFL97FS1E - 594SNB - 600LM - 5000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	44.4	4.3
10°-20°	125.9	12.1
20°-30°	186.2	17.8
30°-40°	211.9	20.3
40°-50°	195.0	18.7
50°-60°	144.3	13.8
60°-70°	84.5	8.1
70°-80°	39.6	3.8
80°-90°	11.9	1.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	356.5	34.2
0°-40°	568.3	54.5
0°-60°	907.6	87.0
0°-90°	1043.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1043.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	470	
5°	468	44
15°	446	126
25°	405	186
35°	340	212
45°	253	195
55°	161	144
65°	84	85
75°	37	40
85°	11	12
90°	0	



TEST NUMBER: P641705

CATALOG NUMBER: ML5612LSVWFL97FS1E - 594SNB - 600LM - 5000K

CANDELA DISTRIBUTION (FULL):

0°	
0°	469.5
2.5°	468.6
5°	467.6
7.5°	464.7
10°	459.9
12.5°	454.1
15°	446.4
17.5°	437.7
20°	429.0
22.5°	417.4
25°	404.8
27.5°	391.3
30°	374.9
32.5°	358.4
35°	340.1
37.5°	319.8
40°	298.5
42.5°	276.3
45°	253.1
47.5°	229.9
50°	206.8
52.5°	183.6
55°	161.3
57.5°	139.1
60°	118.8
62.5°	100.5
65°	84.1
67.5°	69.6
70°	57.0
72.5°	46.4
75°	36.7
77.5°	28.0
80°	21.3
82.5°	15.5
85°	10.6
87.5°	6.8
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)