

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P641779

Luminaire Tested: ML5612LSVWFL97FS1E - 692H - 600LM - 4000K

Issue Date: 2/17/2023

Test Information

Test Method: LM-79-2019
Report Number: P641779
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-107)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/17/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML5612LSVWFL97FS1E - 692H - 600LM - 4000K
Description: ML56 RR, MILKY OPTIC, 6" HAZE TRIM
Light Source: (1) HCL SELECTABLE LUMEN LED 90CRI / 4000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 942.6 lumens
Efficiency: N/A
Efficacy: 91.5 lumens/watt
Spacing Criteria (0/90/45): 1.01 / 1.01 / 1.1
Luminous Opening: Circular (Dia: 0.5' x H: 0')
CIE Type: Direct


Input Watts (W): 10.3
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P641779

CATALOG NUMBER: ML5612LSVWFL97FS1E - 692H - 600LM - 4000K

Luminous Intensity Polar Plot





TEST NUMBER: P641779

CATALOG NUMBER: ML5612LSVWFL97FS1E - 692H - 600LM - 4000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20	
RC	80					70					50					30					10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100	
1	112	109	106	104	110	107	105	102	103	101	99	99	98	96	96	94	93	91			91	
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	84	83			83	
3	99	91	86	81	97	90	85	80	87	83	79	85	81	78	82	79	76	75			75	
4	93	84	77	72	91	83	77	72	80	75	71	78	74	70	76	72	69	67			67	
5	87	77	70	65	85	76	70	65	74	68	64	72	67	64	71	66	63	61			61	
6	81	71	64	59	80	70	64	59	69	63	58	67	62	58	66	61	57	56			56	
7	77	66	59	54	75	65	58	54	64	58	53	62	57	53	61	56	53	51			51	
8	72	61	54	49	71	60	54	49	59	53	49	58	53	49	57	52	48	47			47	
9	68	57	50	45	67	56	50	45	55	49	45	54	49	45	53	48	45	43			43	
10	64	53	46	42	63	52	46	42	52	46	42	51	45	41	50	45	41	40			40	

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	37831
5°	37448
10°	36372
15°	34614
20°	32594
25°	30522
30°	28454
35°	26261
40°	22549
45°	16188
50°	9808
55°	5543
60°	2971
65°	1375
70°	769
75°	614
80°	316
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 16188 cd/sqm



TEST NUMBER: P641779

CATALOG NUMBER: ML5612LSVWFL97FS1E - 692H - 600LM - 4000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	64.1	6.8
10°-20°	171.1	18.2
20°-30°	232.0	24.6
30°-40°	242.7	25.7
40°-50°	161.5	17.1
50°-60°	55.5	5.9
60°-70°	12.5	1.3
70°-80°	2.8	0.3
80°-90°	0.4	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	467.2	49.6
0°-40°	709.9	75.3
0°-60°	926.9	98.3
0°-90°	942.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	942.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	690	
5°	680	64
15°	610	171
25°	505	232
35°	392	243
45°	209	162
55°	58	56
65°	11	12
75°	3	3
85°	0	0
90°	0	



TEST NUMBER: P641779

CATALOG NUMBER: ML5612LSVWFL97FS1E - 692H - 600LM - 4000K

CANDELA DISTRIBUTION (FULL):

	0°
0°	690.1
2.5°	688.2
5°	680.5
7.5°	668.9
10°	653.4
12.5°	633.1
15°	609.9
17.5°	584.8
20°	558.7
22.5°	531.6
25°	504.6
27.5°	477.5
30°	449.5
32.5°	422.4
35°	392.4
37.5°	358.6
40°	315.1
42.5°	263.9
45°	208.8
47.5°	157.6
50°	115.0
52.5°	82.2
55°	58.0
57.5°	39.6
60°	27.1
62.5°	17.4
65°	10.6
67.5°	6.8
70°	4.8
72.5°	2.9
75°	2.9
77.5°	1.9
80°	1.0
82.5°	1.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)