

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P641886

Luminaire Tested: ML5612LSVWFL97FS1E - 694TBZB - 900LM - 2700K

Issue Date: 2/17/2023

Test Information

Test Method: LM-79-2019
Report Number: P641886
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-114)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/17/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML5612LSVWFL97FS1E - 694TBZB - 900LM - 2700K
Description: ML56 RR, MILKY OPTIC, 6" TUSCON BRONZE GIMBAL TRIM
Light Source: (1) HCL SELECTABLE LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1154.3 lumens
Efficiency: N/A
Efficacy: 86.8 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 1.2 / 1.27
Luminous Opening: Circular (Dia: 0.5' x H: 0')
CIE Type: Direct

Input Watts (W): 13.3
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P641886
CATALOG NUMBER: ML5612LSVWFL97FS1E - 694TBZB - 900LM - 2700K

Luminous Intensity Polar Plot





TEST NUMBER: P641886

CATALOG NUMBER: ML5612LSVWFL97FS1E - 694TBZB - 900LM - 2700K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				20	
RC	80				70				50				30				10				0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100				100
1	110	106	102	99	107	104	100	97	100	97	94	96	93	91	92	90	89	87				87
2	101	94	88	83	99	92	87	82	89	84	80	85	82	78	82	79	76	74				74
3	93	84	76	70	91	82	75	70	79	73	69	77	72	67	74	70	66	64				64
4	86	75	67	61	84	74	66	60	71	65	60	69	63	59	67	62	58	56				56
5	80	68	59	53	78	67	59	53	64	58	52	63	57	52	61	56	51	49				49
6	74	61	53	47	72	60	53	47	59	52	46	57	51	46	56	50	46	44				44
7	69	56	48	42	67	55	47	42	54	47	41	52	46	41	51	45	41	39				39
8	64	51	43	38	63	51	43	38	49	42	37	48	42	37	47	41	37	35				35
9	60	47	39	34	59	47	39	34	46	39	34	45	38	34	44	38	34	32				32
10	56	44	36	31	55	43	36	31	42	36	31	41	35	31	40	35	31	29				29

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	28298
5°	28225
10°	28128
15°	27934
20°	27629
25°	27068
30°	26321
35°	25197
40°	23666
45°	21746
50°	19547
55°	17003
60°	14363
65°	12038
70°	10146
75°	8790
80°	7577
85°	7548

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 21746 cd/sqm



TEST NUMBER: P641886

CATALOG NUMBER: ML5612LSVWFL97FS1E - 694TBZB - 900LM - 2700K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	48.7	4.2
10°-20°	138.8	12.0
20°-30°	206.0	17.8
30°-40°	234.8	20.3
40°-50°	215.8	18.7
50°-60°	159.5	13.8
60°-70°	93.0	8.1
70°-80°	44.3	3.8
80°-90°	13.4	1.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	393.5	34.1
0°-40°	628.3	54.4
0°-60°	1003.7	86.9
0°-90°	1154.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1154.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	516	
5°	513	49
15°	492	139
25°	448	206
35°	376	235
45°	280	216
55°	178	160
65°	93	93
75°	42	44
85°	12	13
90°	0	



TEST NUMBER: P641886

CATALOG NUMBER: ML5612LSVWFL97FS1E - 694TBZB - 900LM - 2700K

CANDELA DISTRIBUTION (FULL):

	0°
0°	516.2
2.5°	515.1
5°	512.9
7.5°	509.7
10°	505.3
12.5°	499.8
15°	492.2
17.5°	483.5
20°	473.6
22.5°	461.6
25°	447.5
27.5°	433.3
30°	415.8
32.5°	397.3
35°	376.5
37.5°	354.7
40°	330.7
42.5°	305.6
45°	280.5
47.5°	254.3
50°	229.2
52.5°	203.0
55°	177.9
57.5°	153.9
60°	131.0
62.5°	110.2
65°	92.8
67.5°	76.4
70°	63.3
72.5°	51.3
75°	41.5
77.5°	31.6
80°	24.0
82.5°	17.5
85°	12.0
87.5°	7.6
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)