

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P642004

Luminaire Tested: ML5612LSWFL5597FS1E - 593SNB - 600LM - 4000K

Issue Date: 2/17/2023

Test Information

Test Method: LM-79-2019
Report Number: P642004
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-53)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/17/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML5612LSWFL5597FS1E - 593SNB - 600LM - 4000K
Description: ML56 RR, 55D TIR OPTIC, 5" SATIN NICKLE BAFFLE TRIM
Light Source: (1) HCL SELECTABLE LUMEN LED 90CRI / 4000K CCT
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1069.3 lumens
Efficiency: N/A
Efficacy: 103.8 lumens/watt
Spacing Criteria (0/90/45): 0.86 / 0.86 / 0.89
Luminous Opening: Circular (Dia: 0.42' x H: 0')
CIE Type: Direct

Input Watts (W): 10.3
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P642004
CATALOG NUMBER: ML5612LSWFL5597FS1E - 593SNB - 600LM - 4000K

Luminous Intensity Polar Plot





TEST NUMBER: P642004

CATALOG NUMBER: ML5612LSWFL5597FS1E - 593SNB - 600LM - 4000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				20
RC	80				70				50				30				10				0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100
1	113	110	108	106	111	108	106	104	104	102	101	100	99	98	97	96	95	93			93
2	107	102	98	94	105	101	97	93	97	94	91	94	92	89	91	89	88	86			86
3	102	95	90	85	100	93	89	85	91	87	83	88	85	82	86	83	81	79			79
4	96	88	82	78	94	87	82	77	85	80	76	83	79	76	81	77	75	73			73
5	91	82	76	71	89	81	75	71	79	74	70	78	73	70	76	72	69	68			68
6	86	77	70	66	84	76	70	66	74	69	65	73	68	65	71	67	64	63			63
7	81	72	65	61	80	71	65	61	70	64	60	68	64	60	67	63	60	58			58
8	77	67	61	57	76	67	61	56	65	60	56	64	60	56	63	59	56	54			54
9	73	63	57	53	72	63	57	53	62	56	53	61	56	52	60	55	52	51			51
10	70	59	53	49	69	59	53	49	58	53	49	57	52	49	57	52	49	48			48

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	90758
5°	86889
10°	82395
15°	77680
20°	70348
25°	59969
30°	49004
35°	38297
40°	27803
45°	17271
50°	5932
55°	2794
60°	1074
65°	355
70°	231
75°	305
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 17271 cd/sqm



TEST NUMBER: P642004

CATALOG NUMBER: ML5612LSWFL5597FS1E - 593SNB - 600LM - 4000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	102.6	9.6
10°-20°	264.7	24.8
20°-30°	314.4	29.4
30°-40°	248.0	23.2
40°-50°	116.1	10.9
50°-60°	20.1	1.9
60°-70°	2.6	0.2
70°-80°	0.7	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	681.7	63.8
0°-40°	929.7	86.9
0°-60°	1066.0	99.7
0°-90°	1069.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1069.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1150	
5°	1096	103
15°	950	265
25°	688	314
35°	397	248
45°	155	116
55°	20	20
65°	2	3
75°	1	1
85°	0	0
90°	0	



TEST NUMBER: P642004

CATALOG NUMBER: ML5612LSWFL5597FS1E - 593SNB - 600LM - 4000K

CANDELA DISTRIBUTION (FULL):

	0°
0°	1149.7
2.5°	1135.2
5°	1096.5
7.5°	1060.7
10°	1027.9
12.5°	993.1
15°	950.5
17.5°	898.3
20°	837.4
22.5°	766.8
25°	688.5
27.5°	610.1
30°	537.6
32.5°	467.0
35°	397.4
37.5°	331.7
40°	269.8
42.5°	211.8
45°	154.7
47.5°	87.0
50°	48.3
52.5°	30.9
55°	20.3
57.5°	12.6
60°	6.8
62.5°	3.9
65°	1.9
67.5°	1.0
70°	1.0
72.5°	1.0
75°	1.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)