

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P642107

Luminaire Tested: ML5612LSWFL5597FS1E - 691WB - 600LM - 3000K

Issue Date: 2/17/2023

Test Information

Test Method: LM-79-2019
Report Number: P642107
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-59)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/17/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML5612LSWFL5597FS1E - 691WB - 600LM - 3000K
Description: ML56 RR, 55D TIR OPTIC, 6" DEADFRONT TRIM
Light Source: (1) HCL SELECTABLE LUMEN LED 90CRI / 3000K CCT
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 989.3 lumens
Efficiency: N/A
Efficacy: 96.0 lumens/watt
Spacing Criteria (0/90/45): 0.86 / 0.86 / 0.89
Luminous Opening: Circular (Dia: 0.5' x H: 0')
CIE Type: Direct

Input Watts (W): 10.3
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P642107
CATALOG NUMBER: ML5612LSWFL5597FS1E - 691WB - 600LM - 3000K

Luminous Intensity Polar Plot





TEST NUMBER: P642107

CATALOG NUMBER: ML5612LSWFL5597FS1E - 691WB - 600LM - 3000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	113	110	107	105	111	108	106	103	104	102	100	100	99	97	97	96	94	93																			
2	107	102	97	94	105	100	96	93	97	93	91	94	91	89	91	89	87	85																			
3	101	94	89	84	99	93	88	84	90	86	82	88	84	81	85	82	80	78																			
4	95	87	81	77	93	86	81	76	84	79	75	82	78	74	80	76	74	72																			
5	90	81	75	70	88	80	74	70	78	73	69	77	72	69	75	71	68	66																			
6	85	76	69	65	84	75	69	64	73	68	64	72	67	63	70	66	63	61																			
7	81	71	64	60	79	70	64	59	69	63	59	67	62	59	66	62	58	57																			
8	76	66	60	55	75	66	59	55	64	59	55	63	58	55	62	58	54	53																			
9	72	62	56	52	71	62	56	51	61	55	51	60	55	51	59	54	51	49																			
10	69	58	52	48	68	58	52	48	57	52	48	56	51	48	56	51	48	46																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	56684
5°	54298
10°	51569
15°	48604
20°	43940
25°	37200
30°	30289
35°	23711
40°	17655
45°	11869
50°	5748
55°	2839
60°	1436
65°	908
70°	417
75°	360
80°	284
85°	566

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 11869 cd/sqm



TEST NUMBER: P642107

CATALOG NUMBER: ML5612LSWFL5597FS1E - 691WB - 600LM - 3000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	92.3	9.3
10°-20°	238.4	24.1
20°-30°	281.0	28.4
30°-40°	221.7	22.4
40°-50°	116.4	11.8
50°-60°	29.7	3.0
60°-70°	7.1	0.7
70°-80°	1.8	0.2
80°-90°	0.9	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	611.7	61.8
0°-40°	833.4	84.2
0°-60°	979.5	99.0
0°-90°	989.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	989.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1034	
5°	987	92
15°	856	238
25°	615	281
35°	354	222
45°	153	116
55°	30	30
65°	7	7
75°	2	2
85°	1	1
90°	0	



TEST NUMBER: P642107

CATALOG NUMBER: ML5612LSWFL5597FS1E - 691WB - 600LM - 3000K

CANDELA DISTRIBUTION (FULL):

	0°
0°	1034.0
2.5°	1020.8
5°	986.7
7.5°	954.4
10°	926.4
12.5°	894.0
15°	856.4
17.5°	809.1
20°	753.2
22.5°	686.7
25°	615.0
27.5°	543.2
30°	478.5
32.5°	414.6
35°	354.3
37.5°	298.3
40°	246.7
42.5°	198.6
45°	153.1
47.5°	102.3
50°	67.4
52.5°	45.5
55°	29.7
57.5°	19.2
60°	13.1
62.5°	9.6
65°	7.0
67.5°	4.4
70°	2.6
72.5°	1.7
75°	1.7
77.5°	1.7
80°	0.9
82.5°	0.9
85°	0.9
87.5°	0.9
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)