

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P642125

Luminaire Tested: ML5612LSWFL5597FS1E - 692H - 600LM - 5000K

Issue Date: 2/17/2023

Test Information

Test Method: LM-79-2019
Report Number: P642125
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-61)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/17/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML5612LSWFL5597FS1E - 692H - 600LM - 5000K
Description: ML56 RR, 55D TIR OPTIC, 6" HAZE TRIM
Light Source: (1) HCL SELECTABLE LUMEN LED 90CRI / 5000K CCT
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1090.0 lumens
Efficiency: N/A
Efficacy: 105.8 lumens/watt
Spacing Criteria (0/90/45): 0.86 / 0.86 / 0.89
Luminous Opening: Circular (Dia: 0.5' x H: 0')
CIE Type: Direct

Input Watts (W): 10.3
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P642125
CATALOG NUMBER: ML5612LSWFL5597FS1E - 692H - 600LM - 5000K

Luminous Intensity Polar Plot





TEST NUMBER: P642125

CATALOG NUMBER: ML5612LSWFL5597FS1E - 692H - 600LM - 5000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20	
RC	80					70					50					30					10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100				
1	113	110	108	105	111	108	106	104	104	102	101	100	99	98	97	96	95	93				
2	107	102	98	94	105	100	97	93	97	94	91	94	92	89	91	89	87	86				
3	101	95	89	85	99	93	88	85	91	87	83	88	85	82	86	83	81	79				
4	96	88	82	78	94	87	81	77	85	80	76	83	79	75	81	77	74	73				
5	91	82	76	71	89	81	75	71	79	74	70	77	73	70	76	72	69	67				
6	86	76	70	66	84	76	70	65	74	69	65	73	68	64	71	67	64	62				
7	81	71	65	61	80	71	65	60	69	64	60	68	63	60	67	63	59	58				
8	77	67	61	56	76	66	60	56	65	60	56	64	59	56	63	59	55	54				
9	73	63	57	52	72	62	56	52	61	56	52	60	56	52	60	55	52	50				
10	69	59	53	49	68	59	53	49	58	53	49	57	52	49	56	52	49	47				

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	64079
5°	61446
10°	58009
15°	54586
20°	49337
25°	41906
30°	34176
35°	26676
40°	19737
45°	12831
50°	5279
55°	2036
60°	954
65°	246
70°	160
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 12831 cd/sqm



TEST NUMBER: P642125

CATALOG NUMBER: ML5612LSWFL5597FS1E - 692H - 600LM - 5000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	104.2	9.6
10°-20°	267.7	24.6
20°-30°	316.7	29.1
30°-40°	249.4	22.9
40°-50°	125.6	11.5
50°-60°	23.1	2.1
60°-70°	2.8	0.3
70°-80°	0.4	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	688.7	63.2
0°-40°	938.0	86.1
0°-60°	1086.7	99.7
0°-90°	1090.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1090.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1169	
5°	1117	104
15°	962	268
25°	693	317
35°	399	249
45°	166	126
55°	21	23
65°	2	3
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P642125

CATALOG NUMBER: ML5612LSWFL5597FS1E - 692H - 600LM - 5000K

CANDELA DISTRIBUTION (FULL):

	0°
0°	1168.9
2.5°	1155.3
5°	1116.6
7.5°	1076.9
10°	1042.1
12.5°	1004.4
15°	961.8
17.5°	907.6
20°	845.7
22.5°	773.1
25°	692.8
27.5°	614.4
30°	539.9
32.5°	468.3
35°	398.6
37.5°	333.8
40°	275.8
42.5°	218.7
45°	165.5
47.5°	107.4
50°	61.9
52.5°	33.9
55°	21.3
57.5°	14.5
60°	8.7
62.5°	3.9
65°	1.9
67.5°	1.0
70°	1.0
72.5°	1.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)