

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269



Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P642185

Luminaire Tested: ML5612LSWFL5597FS1E - 693SNB - 600LM - 5000K

Issue Date: 2/17/2023

**Test Information**

Test Method: LM-79-2019  
Report Number: P642185  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-65)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 2/17/2023  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: HALO  
Catalog Number: ML5612LSWFL5597FS1E - 693SNB - 600LM - 5000K  
Description: ML56 RR, 55D TIR OPTIC, 6" SATIN NICKLE BAFFLE TRIM  
Light Source: (1) HCL SELECTABLE LUMEN LED 90CRI / 5000K CCT  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 1083.2 lumens  
Efficiency: N/A  
Efficacy: 105.2 lumens/watt  
Spacing Criteria (0/90/45): 0.86 / 0.86 / 0.89  
Luminous Opening: Circular (Dia: 0.5' x H: 0')  
CIE Type: Direct

Input Watts (W): 10.3  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT



TEST NUMBER: P642185  
CATALOG NUMBER: ML5612LSWFL5597FS1E - 693SNB - 600LM - 5000K

### Luminous Intensity Polar Plot





TEST NUMBER: P642185

CATALOG NUMBER: ML5612LSWFL5597FS1E - 693SNB - 600LM - 5000K

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	113	110	108	105	111	108	106	104	104	102	101	100	99	98	97	96	95	93																			
2	107	102	98	94	105	100	97	93	97	94	91	94	92	89	91	89	87	86																			
3	101	95	89	85	99	93	88	85	91	87	83	88	85	82	86	83	81	79																			
4	96	88	82	78	94	87	81	77	85	80	76	83	79	75	81	77	74	73																			
5	91	82	76	71	89	81	75	71	79	74	70	77	73	69	76	72	69	67																			
6	86	76	70	65	84	75	70	65	74	69	65	72	68	64	71	67	64	62																			
7	81	71	65	60	80	71	65	60	69	64	60	68	63	60	67	63	59	58																			
8	77	67	61	56	76	66	60	56	65	60	56	64	59	56	63	59	55	54																			
9	73	63	57	52	72	62	56	52	61	56	52	60	55	52	60	55	52	50																			
10	69	59	53	49	68	59	53	49	58	52	49	57	52	49	56	52	48	47																			

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	63027
5°	60389
10°	57263
15°	53990
20°	48835
25°	41621
30°	33999
35°	26615
40°	19737
45°	12831
50°	5526
55°	2036
60°	954
65°	246
70°	0
75°	0
80°	0
85°	0

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 45°  
 Luminance: 12831 cd/sqm



TEST NUMBER: P642185

CATALOG NUMBER: ML5612LSWFL5597FS1E - 693SNB - 600LM - 5000K

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	102.7	9.5
10°-20°	264.7	24.4
20°-30°	314.4	29.0
30°-40°	248.8	23.0
40°-50°	126.3	11.7
50°-60°	23.6	2.2
60°-70°	2.7	0.3
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	681.8	62.9
0°-40°	930.5	85.9
0°-60°	1080.4	99.7
0°-90°	1083.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1083.2	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	1150	
5°	1097	103
15°	951	265
25°	688	314
35°	398	249
45°	166	126
55°	21	24
65°	2	3
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P642185

CATALOG NUMBER: ML5612LSWFL5597FS1E - 693SNB - 600LM - 5000K

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	1149.7
2.5°	1136.1
5°	1097.4
7.5°	1061.6
10°	1028.7
12.5°	991.9
15°	951.3
17.5°	898.1
20°	837.1
22.5°	765.5
25°	688.1
27.5°	611.6
30°	537.1
32.5°	466.5
35°	397.7
37.5°	333.9
40°	275.8
42.5°	219.7
45°	165.5
47.5°	108.4
50°	64.8
52.5°	34.8
55°	21.3
57.5°	14.5
60°	8.7
62.5°	3.9
65°	1.9
67.5°	1.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report





Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)