

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P642373

Luminaire Tested: ML5615LSFL409FS1E - 592H - 1200LM - 3500K

Issue Date: 2/17/2023

Test Information

Test Method: LM-79-2019
Report Number: P642373
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-26)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/17/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML5615LSFL409FS1E - 592H - 1200LM - 3500K
Description: ML56 RR, 40D TIR OPTIC, 5" HAZE TRIM
Light Source: (1) STANDARD SELECTABLE LUMEN LED 90CRI / 3500K CCT
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1518.0 lumens
Efficiency: N/A
Efficacy: 113.3 lumens/watt
Spacing Criteria (0/90/45): 0.64 / 0.64 / 0.69
Luminous Opening: Circular (Dia: 0.42' x H: 0')
CIE Type: Direct

Input Watts (W): 13.4
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P642373
CATALOG NUMBER: ML5615LSFL409FS1E - 592H - 1200LM - 3500K

Luminous Intensity Polar Plot





TEST NUMBER: P642373

CATALOG NUMBER: ML5615LSFL409FS1E - 592H - 1200LM - 3500K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10		0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	114	111	109	107	111	109	107	105	105	103	102	101	100	99	98	97	96	94		
2	108	104	100	97	106	102	99	96	99	96	94	96	94	92	93	91	90	88		
3	103	97	92	89	101	96	91	88	93	90	87	91	88	85	89	86	84	82		
4	98	91	86	82	97	90	85	81	88	84	80	86	82	80	84	81	79	77		
5	94	86	80	76	92	85	80	76	83	79	75	82	78	75	80	77	74	72		
6	89	81	75	71	88	80	75	71	79	74	70	77	73	70	76	72	70	68		
7	85	77	71	67	84	76	70	67	75	70	66	73	69	66	72	69	66	64		
8	82	72	67	63	80	72	67	63	71	66	63	70	65	62	69	65	62	61		
9	78	69	63	59	77	68	63	59	67	63	59	67	62	59	66	62	59	57		
10	75	65	60	56	74	65	60	56	64	59	56	63	59	56	63	59	56	55		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	202854
5°	196323
10°	170850
15°	140119
20°	108890
25°	82294
30°	59195
35°	40311
40°	25062
45°	13720
50°	5084
55°	2945
60°	1689
65°	504
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 13720 cd/sqm



TEST NUMBER: P642373

CATALOG NUMBER: ML5615LSFL409FS1E - 592H - 1200LM - 3500K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	225.1	14.8
10°-20°	473.7	31.2
20°-30°	433.1	28.5
30°-40°	264.3	17.4
40°-50°	97.7	6.4
50°-60°	20.6	1.4
60°-70°	3.6	0.2
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1131.9	74.6
0°-40°	1396.2	92.0
0°-60°	1514.4	99.8
0°-90°	1518.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1518.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2570	
5°	2478	225
15°	1714	474
25°	945	433
35°	418	264
45°	123	98
55°	21	21
65°	3	4
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P642373

CATALOG NUMBER: ML5615LSFL409FS1E - 592H - 1200LM - 3500K

CANDELA DISTRIBUTION (FULL):

	0°
0°	2569.7
2.5°	2551.0
5°	2477.5
7.5°	2327.9
10°	2131.4
12.5°	1925.6
15°	1714.5
17.5°	1502.0
20°	1296.2
22.5°	1110.5
25°	944.8
27.5°	789.8
30°	649.4
32.5°	525.2
35°	418.3
37.5°	324.7
40°	243.2
42.5°	184.4
45°	122.9
47.5°	66.8
50°	41.4
52.5°	30.7
55°	21.4
57.5°	14.7
60°	10.7
62.5°	6.7
65°	2.7
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)