

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P642384

Luminaire Tested: ML5615LSFL409FS1E - 592H - 900LM - 4000K

Issue Date: 2/17/2023

Test Information

Test Method: LM-79-2019
Report Number: P642384
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-26)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/17/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML5615LSFL409FS1E - 592H - 900LM - 4000K
Description: ML56 RR, 40D TIR OPTIC, 5" HAZE TRIM
Light Source: (1) STANDARD SELECTABLE LUMEN LED 90CRI / 4000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1291.4 lumens
Efficiency: N/A
Efficacy: 123.0 lumens/watt
Spacing Criteria (0/90/45): 0.64 / 0.64 / 0.69
Luminous Opening: Circular (Dia: 0.42' x H: 0')
CIE Type: Direct


Input Watts (W): 10.5
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P642384

CATALOG NUMBER: ML5615LSFL409FS1E - 592H - 900LM - 4000K

Luminous Intensity Polar Plot





TEST NUMBER: P642384

CATALOG NUMBER: ML5615LSFL409FS1E - 592H - 900LM - 4000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10		0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	114	111	109	107	111	109	107	105	105	103	102	101	100	99	98	97	96	94		
2	108	104	100	97	106	102	99	96	99	96	94	96	94	92	93	91	90	88		
3	103	97	92	89	101	96	91	88	93	90	87	91	88	85	89	86	84	82		
4	98	91	86	82	97	90	85	81	88	84	80	86	82	80	84	81	79	77		
5	94	86	80	76	92	85	80	76	83	79	75	82	78	75	80	77	74	72		
6	89	81	75	71	88	80	75	71	79	74	70	77	73	70	76	72	70	68		
7	85	77	71	67	84	76	70	67	75	70	66	73	69	66	72	69	66	64		
8	82	72	67	63	80	72	67	63	71	66	63	70	65	62	69	65	62	61		
9	78	69	63	59	77	68	63	59	67	63	59	67	62	59	66	62	59	57		
10	75	65	60	56	74	65	60	56	64	59	56	63	59	56	63	59	56	55		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	172573
5°	167019
10°	145352
15°	119205
20°	92635
25°	70004
30°	50362
35°	34288
40°	21321
45°	11677
50°	4323
55°	2505
60°	1437
65°	430
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 11677 cd/sqm



TEST NUMBER: P642384

CATALOG NUMBER: ML5615LSFL409FS1E - 592H - 900LM - 4000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	191.5	14.8
10°-20°	403.0	31.2
20°-30°	368.4	28.5
30°-40°	224.9	17.4
40°-50°	83.1	6.4
50°-60°	17.5	1.4
60°-70°	3.1	0.2
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	962.9	74.6
0°-40°	1187.8	92.0
0°-60°	1288.4	99.8
0°-90°	1291.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1291.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2186	
5°	2108	191
15°	1459	403
25°	804	368
35°	356	225
45°	105	83
55°	18	17
65°	2	3
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P642384

CATALOG NUMBER: ML5615LSFL409FS1E - 592H - 900LM - 4000K

CANDELA DISTRIBUTION (FULL):

	0°
0°	2186.1
2.5°	2170.2
5°	2107.7
7.5°	1980.4
10°	1813.3
12.5°	1638.2
15°	1458.6
17.5°	1277.8
20°	1102.7
22.5°	944.7
25°	803.7
27.5°	671.9
30°	552.5
32.5°	446.8
35°	355.8
37.5°	276.3
40°	206.9
42.5°	156.9
45°	104.6
47.5°	56.8
50°	35.2
52.5°	26.1
55°	18.2
57.5°	12.5
60°	9.1
62.5°	5.7
65°	2.3
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)