

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P642433

Luminaire Tested: ML5615LSFL409FS1E - 593SNB - 1200LM - 3500K

Issue Date: 2/17/2023

Test Information

Test Method: LM-79-2019
Report Number: P642433
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-30)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/17/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML5615LSFL409FS1E - 593SNB - 1200LM - 3500K
Description: ML56 RR, 40D TIR OPTIC, 5" SATIN NICKLE BAFFLE TRIM
Light Source: (1) STANDARD SELECTABLE LUMEN LED 90CRI / 3500K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1501.9 lumens
Efficiency: N/A
Efficacy: 112.1 lumens/watt
Spacing Criteria (0/90/45): 0.64 / 0.64 / 0.69
Luminous Opening: Circular (Dia: 0.42' x H: 0')
CIE Type: Direct


Input Watts (W): 13.4
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P642433

CATALOG NUMBER: ML5615LSFL409FS1E - 593SNB - 1200LM - 3500K

Luminous Intensity Polar Plot





TEST NUMBER: P642433

CATALOG NUMBER: ML5615LSFL409FS1E - 593SNB - 1200LM - 3500K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	114	111	109	106	111	109	107	105	105	103	102	101	100	99	98	97	96	94																			
2	108	104	100	96	106	102	98	95	99	96	93	96	93	91	93	91	89	88																			
3	103	97	92	88	101	96	91	88	93	89	86	91	87	85	88	86	84	82																			
4	98	91	86	82	96	90	85	81	88	83	80	86	82	79	84	81	78	77																			
5	93	85	80	76	92	85	79	75	83	78	75	81	77	74	80	76	73	72																			
6	89	81	75	71	88	80	74	70	78	74	70	77	73	69	76	72	69	68																			
7	85	76	70	66	84	75	70	66	74	69	66	73	69	65	72	68	65	64																			
8	81	72	66	62	80	71	66	62	70	65	62	69	65	62	68	64	61	60																			
9	78	68	63	59	76	68	62	59	67	62	59	66	62	58	65	61	58	57																			
10	74	65	59	56	73	65	59	56	64	59	56	63	59	55	62	58	55	54																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	196594
5°	190570
10°	166001
15°	136596
20°	106403
25°	80996
30°	58821
35°	40167
40°	25196
45°	14915
50°	5576
55°	3303
60°	1895
65°	747
70°	300
75°	397
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 14915 cd/sqm



TEST NUMBER: P642433

CATALOG NUMBER: ML5615LSFL409FS1E - 593SNB - 1200LM - 3500K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	218.4	14.5
10°-20°	461.2	30.7
20°-30°	426.5	28.4
30°-40°	263.9	17.6
40°-50°	103.0	6.9
50°-60°	22.9	1.5
60°-70°	5.2	0.3
70°-80°	0.9	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1106.1	73.6
0°-40°	1370.0	91.2
0°-60°	1495.9	99.6
0°-90°	1501.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1501.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2490	
5°	2405	218
15°	1671	461
25°	930	426
35°	417	264
45°	134	103
55°	24	23
65°	4	5
75°	1	1
85°	0	0
90°	0	



TEST NUMBER: P642433

CATALOG NUMBER: ML5615LSFL409FS1E - 593SNB - 1200LM - 3500K

CANDELA DISTRIBUTION (FULL):

	0°
0°	2490.4
2.5°	2475.7
5°	2404.9
7.5°	2256.6
10°	2070.9
12.5°	1871.8
15°	1671.4
17.5°	1461.6
20°	1266.6
22.5°	1088.9
25°	929.9
27.5°	782.9
30°	645.3
32.5°	523.7
35°	416.8
37.5°	326.0
40°	244.5
42.5°	185.7
45°	133.6
47.5°	78.8
50°	45.4
52.5°	33.4
55°	24.0
57.5°	17.4
60°	12.0
62.5°	9.4
65°	4.0
67.5°	1.3
70°	1.3
72.5°	1.3
75°	1.3
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)