

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P642436

Luminaire Tested: ML5615LSFL409FS1E - 593SNB - 1500LM - 2700K

Issue Date: 2/17/2023

Test Information

Test Method: LM-79-2019
Report Number: P642436
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-30)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/17/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML5615LSFL409FS1E - 593SNB - 1500LM - 2700K
Description: ML56 RR, 40D TIR OPTIC, 5" SATIN NICKLE BAFFLE TRIM
Light Source: (1) STANDARD SELECTABLE LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1747.8 lumens
Efficiency: N/A
Efficacy: 102.2 lumens/watt
Spacing Criteria (0/90/45): 0.64 / 0.64 / 0.69
Luminous Opening: Circular (Dia: 0.42' x H: 0')
CIE Type: Direct


Input Watts (W): 17.1
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P642436

CATALOG NUMBER: ML5615LSFL409FS1E - 593SNB - 1500LM - 2700K

Luminous Intensity Polar Plot





TEST NUMBER: P642436

CATALOG NUMBER: ML5615LSFL409FS1E - 593SNB - 1500LM - 2700K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	114	111	109	106	111	109	107	105	105	103	102	101	100	99	98	97	96	94			
2	108	104	100	96	106	102	98	95	99	96	93	96	93	91	93	91	89	88			
3	103	97	92	88	101	96	91	88	93	89	86	91	87	85	88	86	84	82			
4	98	91	86	82	96	90	85	81	88	83	80	86	82	79	84	81	78	77			
5	93	85	80	76	92	85	79	75	83	78	75	81	77	74	80	76	73	72			
6	89	81	75	71	88	80	74	70	78	74	70	77	73	69	76	72	69	68			
7	85	76	70	66	84	75	70	66	74	69	66	73	69	65	72	68	65	64			
8	81	72	66	62	80	71	66	62	70	65	62	69	65	62	68	64	61	60			
9	78	68	63	59	76	68	62	59	67	62	59	66	62	58	65	61	58	57			
10	74	65	59	56	73	65	59	56	64	59	55	63	59	55	62	58	55	54			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	228755
5°	221744
10°	193158
15°	158940
20°	123810
25°	94244
30°	68447
35°	46739
40°	29318
45°	17360
50°	6497
55°	3854
60°	2210
65°	878
70°	369
75°	488
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 17360 cd/sqm



TEST NUMBER: P642436

CATALOG NUMBER: ML5615LSFL409FS1E - 593SNB - 1500LM - 2700K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	254.1	14.5
10°-20°	536.7	30.7
20°-30°	496.2	28.4
30°-40°	307.1	17.6
40°-50°	119.8	6.9
50°-60°	26.7	1.5
60°-70°	6.1	0.3
70°-80°	1.0	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1287.0	73.6
0°-40°	1594.1	91.2
0°-60°	1740.6	99.6
0°-90°	1747.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1747.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2898	
5°	2798	254
15°	1945	537
25°	1082	496
35°	485	307
45°	156	120
55°	28	27
65°	5	6
75°	2	1
85°	0	0
90°	0	



TEST NUMBER: P642436

CATALOG NUMBER: ML5615LSFL409FS1E - 593SNB - 1500LM - 2700K

CANDELA DISTRIBUTION (FULL):

	0°
0°	2897.8
2.5°	2880.7
5°	2798.3
7.5°	2625.8
10°	2409.7
12.5°	2178.0
15°	1944.8
17.5°	1700.8
20°	1473.8
22.5°	1267.0
25°	1082.0
27.5°	911.0
30°	750.9
32.5°	609.4
35°	485.0
37.5°	379.3
40°	284.5
42.5°	216.1
45°	155.5
47.5°	91.7
50°	52.9
52.5°	38.9
55°	28.0
57.5°	20.2
60°	14.0
62.5°	10.9
65°	4.7
67.5°	1.6
70°	1.6
72.5°	1.6
75°	1.6
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)