

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P642622

Luminaire Tested: ML5615LSFL409FS1E - 693SNB - 900LM - 3000K

Issue Date: 2/17/2023

Test Information

Test Method: LM-79-2019
Report Number: P642622
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-42)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/17/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML5615LSFL409FS1E - 693SNB - 900LM - 3000K
Description: ML56 RR, 40D TIR OPTIC, 6" SATIN NICKLE BAFFLE TRIM
Light Source: (1) STANDARD SELECTABLE LUMEN LED 90CRI / 3000K CCT
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1170.5 lumens
Efficiency: N/A
Efficacy: 111.5 lumens/watt
Spacing Criteria (0/90/45): 0.64 / 0.64 / 0.7
Luminous Opening: Circular (Dia: 0.5' x H: 0')
CIE Type: Direct

Input Watts (W): 10.5
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P642622
CATALOG NUMBER: ML5615LSFL409FS1E - 693SNB - 900LM - 3000K

Luminous Intensity Polar Plot





TEST NUMBER: P642622

CATALOG NUMBER: ML5615LSFL409FS1E - 693SNB - 900LM - 3000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	114	111	109	106	111	109	107	105	105	103	101	101	100	98	98	97	96	94			
2	108	104	100	96	106	102	98	95	99	96	93	96	93	91	93	91	89	88			
3	103	97	92	88	101	95	91	87	93	89	86	90	87	85	88	86	83	82			
4	98	91	85	81	96	90	85	81	87	83	80	85	82	79	84	80	78	76			
5	93	85	80	75	92	84	79	75	82	78	74	81	77	74	79	76	73	72			
6	89	80	74	70	87	79	74	70	78	73	70	77	72	69	75	72	69	67			
7	85	76	70	66	83	75	70	66	74	69	65	73	68	65	72	68	65	63			
8	81	72	66	62	80	71	66	62	70	65	62	69	65	61	68	64	61	60			
9	77	68	62	58	76	67	62	58	67	62	58	66	61	58	65	61	58	56			
10	74	65	59	55	73	64	59	55	63	58	55	63	58	55	62	58	55	53			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	105123
5°	101843
10°	88698
15°	72963
20°	56927
25°	43333
30°	31536
35°	21630
40°	13998
45°	8621
50°	4657
55°	1768
60°	1129
65°	402
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 8621 cd/sqm



TEST NUMBER: P642622

CATALOG NUMBER: ML5615LSFL409FS1E - 693SNB - 900LM - 3000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	168.2	14.4
10°-20°	355.2	30.3
20°-30°	328.5	28.1
30°-40°	204.8	17.5
40°-50°	89.5	7.6
50°-60°	20.6	1.8
60°-70°	3.8	0.3
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	851.9	72.8
0°-40°	1056.7	90.3
0°-60°	1166.7	99.7
0°-90°	1170.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1170.5	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1918	
5°	1851	168
15°	1286	355
25°	716	329
35°	323	205
45°	111	89
55°	18	21
65°	3	4
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P642622

CATALOG NUMBER: ML5615LSFL409FS1E - 693SNB - 900LM - 3000K

CANDELA DISTRIBUTION (FULL):

	0°
0°	1917.6
2.5°	1904.2
5°	1850.7
7.5°	1739.5
10°	1593.4
12.5°	1440.0
15°	1285.6
17.5°	1128.1
20°	975.8
22.5°	837.9
25°	716.4
27.5°	603.2
30°	498.2
32.5°	404.5
35°	323.2
37.5°	253.2
40°	195.6
42.5°	151.3
45°	111.2
47.5°	82.3
50°	54.6
52.5°	27.8
55°	18.5
57.5°	14.4
60°	10.3
62.5°	6.2
65°	3.1
67.5°	1.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)