

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P642679

Luminaire Tested: ML5615LSFL409FS1E - 694WB - 1500LM - 4000K

Issue Date: 2/17/2023

Test Information

Test Method: LM-79-2019
Report Number: P642679
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-44)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/17/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML5615LSFL409FS1E - 694WB - 1500LM - 4000K
Description: ML56 RR, 40D TIR OPTIC, 6" WHITE GIMBAL TRIM
Light Source: (1) STANDARD SELECTABLE LUMEN LED 90CRI / 4000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2034.6 lumens
Efficiency: N/A
Efficacy: 119.0 lumens/watt
Spacing Criteria (0/90/45): 0.64 / 0.64 / 0.69
Luminous Opening: Circular (Dia: 0.5' x H: 0')
CIE Type: Direct


Input Watts (W): 17.1
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P642679

CATALOG NUMBER: ML5615LSFL409FS1E - 694WB - 1500LM - 4000K

Luminous Intensity Polar Plot





TEST NUMBER: P642679

CATALOG NUMBER: ML5615LSFL409FS1E - 694WB - 1500LM - 4000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	114	111	108	106	111	109	106	104	105	103	101	101	99	98	97	96	95	93																			
2	108	103	99	96	106	101	98	95	98	95	92	95	93	91	92	90	89	87																			
3	103	96	91	87	101	95	90	87	92	88	85	90	87	84	87	85	83	81																			
4	97	90	85	80	96	89	84	80	87	82	79	85	81	78	83	80	77	76																			
5	93	84	79	74	91	84	78	74	82	77	73	80	76	73	79	75	72	71																			
6	88	79	74	69	87	79	73	69	77	72	69	76	71	68	74	71	68	66																			
7	84	75	69	65	83	74	69	65	73	68	64	72	67	64	71	67	64	62																			
8	80	71	65	61	79	70	65	61	69	64	61	68	64	60	67	63	60	59																			
9	77	67	61	58	76	67	61	57	66	61	57	65	60	57	64	60	57	56																			
10	73	64	58	55	72	63	58	54	63	58	54	62	57	54	61	57	54	53																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	180863
5°	175033
10°	152352
15°	125126
20°	97676
25°	74109
30°	53274
35°	36205
40°	23279
45°	15079
50°	8742
55°	4903
60°	3300
65°	2296
70°	1699
75°	1504
80°	568
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 15079 cd/sqm



TEST NUMBER: P642679

CATALOG NUMBER: ML5615LSFL409FS1E - 694WB - 1500LM - 4000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	289.0	14.2
10°-20°	609.7	30.0
20°-30°	561.3	27.6
30°-40°	343.6	16.9
40°-50°	153.7	7.6
50°-60°	50.8	2.5
60°-70°	19.0	0.9
70°-80°	6.7	0.3
80°-90°	0.7	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1460.1	71.8
0°-40°	1803.7	88.7
0°-60°	2008.1	98.7
0°-90°	2034.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2034.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3299	
5°	3181	289
15°	2205	610
25°	1225	561
35°	541	344
45°	194	154
55°	51	51
65°	18	19
75°	7	7
85°	0	1
90°	0	



TEST NUMBER: P642679

CATALOG NUMBER: ML5615LSFL409FS1E - 694WB - 1500LM - 4000K

CANDELA DISTRIBUTION (FULL):

	0°
0°	3299.2
2.5°	3277.9
5°	3180.7
7.5°	2989.8
10°	2736.9
12.5°	2475.3
15°	2204.7
17.5°	1936.0
20°	1674.3
22.5°	1437.4
25°	1225.2
27.5°	1027.2
30°	841.6
32.5°	678.9
35°	541.0
37.5°	424.3
40°	325.3
42.5°	254.6
45°	194.5
47.5°	143.2
50°	102.5
52.5°	72.5
55°	51.3
57.5°	38.9
60°	30.1
62.5°	24.8
65°	17.7
67.5°	14.1
70°	10.6
72.5°	8.8
75°	7.1
77.5°	3.5
80°	1.8
82.5°	1.8
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)