

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269



Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P642978

Luminaire Tested: ML5615LSNFL259FS1E - 693TBZB - 1500LM - 3500K

Issue Date: 2/17/2023

**Test Information**

Test Method: LM-79-2019  
Report Number: P642978  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-20)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 2/17/2023  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: HALO  
Catalog Number: ML5615LSNFL259FS1E - 693TBZB - 1500LM - 3500K  
Description: ML56 RR, 25D TIR OPTIC, 6" TUSCON BRONZE BAFFLE TRIM  
Light Source: (1) STANDARD SELECTABLE LUMEN LED 90CRI / 3500K CCT  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 1660.9 lumens  
Efficiency: N/A  
Efficacy: 97.1 lumens/watt  
Spacing Criteria (0/90/45): 0.43 / 0.43 / 0.44  
Luminous Opening: Circular (Dia: 0.5' x H: 0')  
CIE Type: Direct


Input Watts (W): 17.1  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT



TEST NUMBER: P642978

CATALOG NUMBER: ML5615LSNFL259FS1E - 693TBZB - 1500LM - 3500K

### Luminous Intensity Polar Plot





TEST NUMBER: P642978

CATALOG NUMBER: ML5615LSNFL259FS1E - 693TBZB - 1500LM - 3500K

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	114	111	109	107	111	109	107	105	105	103	102	101	100	99	98	97	96	94																			
2	108	104	100	97	106	102	99	96	99	96	93	96	94	91	93	91	90	88																			
3	103	97	92	89	101	96	91	88	93	89	86	91	88	85	89	86	84	82																			
4	98	91	86	82	97	90	85	81	88	84	80	86	82	79	84	81	79	77																			
5	94	86	80	76	92	85	80	76	83	79	75	82	78	75	80	77	74	72																			
6	90	81	75	71	88	80	75	71	79	74	71	77	73	70	76	73	70	68																			
7	86	77	71	67	84	76	71	67	75	70	67	74	69	66	73	69	66	65																			
8	82	73	67	63	81	72	67	63	71	66	63	70	66	63	69	65	63	61																			
9	78	69	64	60	77	69	64	60	68	63	60	67	63	60	66	62	59	58																			
10	75	66	61	57	74	66	61	57	65	60	57	64	60	57	64	60	57	56																			

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	242064
5°	220834
10°	161186
15°	92242
20°	56273
25°	45626
30°	37550
35°	30463
40°	24109
45°	18475
50°	9390
55°	2361
60°	1436
65°	636
70°	256
75°	0
80°	0
85°	0

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 45°  
 Luminance: 18475 cd/sqm



TEST NUMBER: P642978

CATALOG NUMBER: ML5615LSNFL259FS1E - 693TBZB - 1500LM - 3500K

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	346.7	20.9
10°-20°	466.2	28.1
20°-30°	347.4	20.9
30°-40°	285.4	17.2
40°-50°	175.8	10.6
50°-60°	33.4	2.0
60°-70°	5.4	0.3
70°-80°	0.6	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1160.4	69.9
0°-40°	1445.8	87.0
0°-60°	1654.9	99.6
0°-90°	1660.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1660.9	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	4416	
5°	4013	347
15°	1625	466
25°	754	347
35°	455	285
45°	238	176
55°	25	33
65°	5	5
75°	0	1
85°	0	0
90°	0	



TEST NUMBER: P642978

CATALOG NUMBER: ML5615LSNFL259FS1E - 693TBZB - 1500LM - 3500K

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	4415.6
2.5°	4326.9
5°	4013.0
7.5°	3510.2
10°	2895.6
12.5°	2226.7
15°	1625.3
17.5°	1199.6
20°	964.6
22.5°	843.0
25°	754.3
27.5°	668.8
30°	593.2
32.5°	522.6
35°	455.2
37.5°	394.4
40°	336.9
42.5°	287.6
45°	238.3
47.5°	170.9
50°	110.1
52.5°	49.3
55°	24.7
57.5°	16.4
60°	13.1
62.5°	8.2
65°	4.9
67.5°	1.6
70°	1.6
72.5°	1.6
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report





Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)