

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P643086

Luminaire Tested: ML5615LSVWFL759FS1E - 592SC - 900LM - 2700K

Issue Date: 2/17/2023

Test Information

Test Method: LM-79-2019
Report Number: P643086
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-71)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/17/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML5615LSVWFL759FS1E - 592SC - 900LM - 2700K
Description: ML56 RR, 75D TIR OPTIC, 5" SPECULAR CLEAR TRIM
Light Source: (1) STANDARD SELECTABLE LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1086.0 lumens
Efficiency: N/A
Efficacy: 103.4 lumens/watt
Spacing Criteria (0/90/45): 1.15 / 1.15 / 1.07
Luminous Opening: Circular (Dia: 0.42' x H: 0')
CIE Type: Direct


Input Watts (W): 10.5
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P643086

CATALOG NUMBER: ML5615LSVWFL759FS1E - 592SC - 900LM - 2700K

Luminous Intensity Polar Plot





TEST NUMBER: P643086

CATALOG NUMBER: ML5615LSVWFL759FS1E - 592SC - 900LM - 2700K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100																
1	113	110	107	105	111	108	106	103	104	102	100	100	99	97	97	95	94	93			93																
2	107	102	97	93	105	100	96	92	96	93	90	93	91	88	91	89	87	85			85																
3	101	94	88	84	99	92	87	83	90	85	82	87	84	81	85	82	79	78			78																
4	95	87	81	76	93	85	80	75	83	78	75	81	77	74	79	76	73	71			71																
5	89	80	74	69	88	79	73	69	77	72	68	76	71	68	74	70	67	65			65																
6	84	75	68	63	83	74	68	63	72	67	63	71	66	62	69	65	62	60			60																
7	80	69	63	58	78	69	62	58	67	62	58	66	61	57	65	60	57	55			55																
8	75	65	58	54	74	64	58	54	63	57	53	62	57	53	61	56	53	51			51																
9	71	60	54	50	70	60	54	50	59	53	49	58	53	49	57	52	49	48			48																
10	67	57	50	46	66	56	50	46	55	50	46	55	49	46	54	49	46	44			44																

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	64258
5°	64266
10°	65570
15°	67424
20°	66702
25°	63149
30°	57062
35°	45775
40°	30503
45°	15406
50°	8597
55°	5092
60°	1895
65°	374
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 15406 cd/sqm



TEST NUMBER: P643086

CATALOG NUMBER: ML5615LSVWFL759FS1E - 592SC - 900LM - 2700K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	77.7	7.2
10°-20°	231.4	21.3
20°-30°	330.8	30.5
30°-40°	290.7	26.8
40°-50°	117.8	10.8
50°-60°	34.0	3.1
60°-70°	3.7	0.3
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	639.9	58.9
0°-40°	930.5	85.7
0°-60°	1082.4	99.7
0°-90°	1086.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1086.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	814	
5°	811	78
15°	825	231
25°	725	331
35°	475	291
45°	138	118
55°	37	34
65°	2	4
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P643086
CATALOG NUMBER: ML5615LSVWFL759FS1E - 592SC - 900LM - 2700K

CANDELA DISTRIBUTION (FULL):

	0°
0°	814
2.5°	814
5°	811
7.5°	813
10°	818
12.5°	824
15°	825
17.5°	815
20°	794
22.5°	763
25°	725
27.5°	680
30°	626
32.5°	557
35°	475
37.5°	384
40°	296
42.5°	209
45°	138
47.5°	91
50°	70
52.5°	52
55°	37
57.5°	24
60°	12
62.5°	6
65°	2
67.5°	1
70°	0
72.5°	0
75°	0
77.5°	0
80°	0
82.5°	0
85°	0
87.5°	0
90°	0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)