

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P643119

Luminaire Tested: ML5615LSVWFL759FS1E - 593BB - 900LM - 4000K

Issue Date: 2/17/2023

Test Information

Test Method: LM-79-2019
Report Number: P643119
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-75)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/17/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML5615LSVWFL759FS1E - 593BB - 900LM - 4000K
Description: ML56 RR, 75D TIR OPTIC, 5" BLACK BAFFLE TRIM
Light Source: (1) STANDARD SELECTABLE LUMEN LED 90CRI / 4000K CCT
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1167.5 lumens
Efficiency: N/A
Efficacy: 111.2 lumens/watt
Spacing Criteria (0/90/45): 1.19 / 1.19 / 1.09
Luminous Opening: Circular (Dia: 0.42' x H: 0')
CIE Type: Direct

Input Watts (W): 10.5
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P643119
CATALOG NUMBER: ML5615LSVWFL759FS1E - 593BB - 900LM - 4000K

Luminous Intensity Polar Plot





TEST NUMBER: P643119

CATALOG NUMBER: ML5615LSVWFL759FS1E - 593BB - 900LM - 4000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100				100															
1	113	110	107	105	111	108	105	103	104	102	100	100	99	97	97	95	94	92				92															
2	107	101	97	93	104	100	96	92	96	93	90	93	91	88	91	88	86	85				85															
3	101	94	88	84	99	92	87	83	90	85	82	87	83	81	85	82	79	78				78															
4	95	87	80	76	93	85	80	75	83	78	74	81	77	74	79	76	73	71				71															
5	89	80	74	69	88	79	73	69	77	72	68	76	71	67	74	70	67	65				65															
6	84	74	68	63	83	74	67	63	72	66	62	71	66	62	69	65	61	60				60															
7	79	69	63	58	78	68	62	58	67	62	57	66	61	57	65	60	57	55				55															
8	75	64	58	53	74	64	58	53	63	57	53	62	57	53	61	56	53	51				51															
9	71	60	54	49	70	60	54	49	59	53	49	58	53	49	57	52	49	47				47															
10	67	56	50	46	66	56	50	46	55	50	46	54	49	46	54	49	45	44				44															

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	65458
5°	66429
10°	68480
15°	71208
20°	72145
25°	68662
30°	61592
35°	49659
40°	33285
45°	16634
50°	9358
55°	5629
60°	1974
65°	205
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 16634 cd/sqm



TEST NUMBER: P643119

CATALOG NUMBER: ML5615LSVWFL759FS1E - 593BB - 900LM - 4000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	80.5	6.9
10°-20°	245.5	21.0
20°-30°	358.9	30.7
30°-40°	314.3	26.9
40°-50°	127.6	10.9
50°-60°	37.2	3.2
60°-70°	3.4	0.3
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	684.9	58.7
0°-40°	999.3	85.6
0°-60°	1164.1	99.7
0°-90°	1167.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1167.5	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	829	
5°	838	81
15°	871	246
25°	788	359
35°	515	314
45°	149	128
55°	41	37
65°	1	3
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P643119

CATALOG NUMBER: ML5615LSVWFL759FS1E - 593BB - 900LM - 4000K

CANDELA DISTRIBUTION (FULL):

	0°
0°	829.2
2.5°	831.5
5°	838.3
7.5°	846.3
10°	854.3
12.5°	863.4
15°	871.3
17.5°	871.3
20°	858.8
22.5°	830.4
25°	788.3
27.5°	737.1
30°	675.7
32.5°	599.5
35°	515.3
37.5°	415.2
40°	323.0
42.5°	225.2
45°	149.0
47.5°	99.0
50°	76.2
52.5°	56.9
55°	40.9
57.5°	26.2
60°	12.5
62.5°	6.8
65°	1.1
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)