

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P643148

Luminaire Tested: ML5615LSVWFL759FS1E - 593TBZB - 900LM - 3500K

Issue Date: 2/17/2023

Test Information

Test Method: LM-79-2019
Report Number: P643148
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-77)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/17/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML5615LSVWFL759FS1E - 593TBZB - 900LM - 3500K
Description: ML56 RR, 75D TIR OPTIC, 5" TUSCON BRONZE BAFFLE TRIM
Light Source: (1) STANDARD SELECTABLE LUMEN LED 90CRI / 3500K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1090.4 lumens
Efficiency: N/A
Efficacy: 103.8 lumens/watt
Spacing Criteria (0/90/45): 1.19 / 1.19 / 1.09
Luminous Opening: Circular (Dia: 0.42' x H: 0')
CIE Type: Direct


Input Watts (W): 10.5
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P643148

CATALOG NUMBER: ML5615LSVWFL759FS1E - 593TBZB - 900LM - 3500K

Luminous Intensity Polar Plot





TEST NUMBER: P643148

CATALOG NUMBER: ML5615LSVWFL759FS1E - 593TBZB - 900LM - 3500K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20					
RC	80					70					50					30					10					0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																										
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100					100			
1	113	110	107	105	111	108	105	103	104	102	100	100	99	97	97	95	94	92					92			
2	107	101	97	93	104	100	96	92	96	93	90	93	91	88	91	88	86	85					85			
3	101	94	88	84	99	92	87	83	89	85	82	87	83	80	85	82	79	78					78			
4	95	86	80	76	93	85	80	75	83	78	74	81	77	73	79	76	73	71					71			
5	89	80	74	69	88	79	73	69	77	72	68	76	71	67	74	70	67	65					65			
6	84	74	68	63	83	73	67	63	72	66	62	70	66	62	69	65	61	60					60			
7	79	69	62	58	78	68	62	58	67	61	57	66	61	57	65	60	57	55					55			
8	75	64	58	53	74	64	58	53	63	57	53	62	56	53	61	56	52	51					51			
9	71	60	54	49	70	60	53	49	59	53	49	58	53	49	57	52	49	47					47			
10	67	56	50	46	66	56	50	46	55	49	46	54	49	45	53	49	45	44					44			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	61053
5°	61960
10°	63862
15°	66320
20°	67281
25°	64055
30°	57499
35°	46122
40°	31028
45°	15339
50°	8953
55°	5381
60°	1831
65°	392
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 15339 cd/sqm



TEST NUMBER: P643148

CATALOG NUMBER: ML5615LSVWFL759FS1E - 593TBZB - 900LM - 3500K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	75.1	6.9
10°-20°	228.8	21.0
20°-30°	334.7	30.7
30°-40°	293.4	26.9
40°-50°	119.1	10.9
50°-60°	35.5	3.3
60°-70°	3.7	0.3
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	638.6	58.6
0°-40°	932.1	85.5
0°-60°	1086.7	99.7
0°-90°	1090.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1090.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	773	
5°	782	75
15°	812	229
25°	735	335
35°	479	293
45°	137	119
55°	39	36
65°	2	4
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P643148

CATALOG NUMBER: ML5615LSVWFL759FS1E - 593TBZB - 900LM - 3500K

CANDELA DISTRIBUTION (FULL):

0°	
0°	773.4
2.5°	775.6
5°	781.9
7.5°	789.3
10°	796.7
12.5°	804.1
15°	811.5
17.5°	812.5
20°	800.9
22.5°	773.4
25°	735.4
27.5°	687.9
30°	630.8
32.5°	561.1
35°	478.6
37.5°	388.8
40°	301.1
42.5°	210.3
45°	137.4
47.5°	93.0
50°	72.9
52.5°	53.9
55°	39.1
57.5°	25.4
60°	11.6
62.5°	6.3
65°	2.1
67.5°	1.1
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)