

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P643173

Luminaire Tested: ML5615LSVWFL759FS1E - 594SNB - 1500LM - 3500K

Issue Date: 2/17/2023

Test Information

Test Method: LM-79-2019
Report Number: P643173
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-79)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/17/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML5615LSVWFL759FS1E - 594SNB - 1500LM - 3500K
Description: ML56 RR, 75D TIR OPTIC, 5" SATIN NICKLE GIMBAL TRIM
Light Source: (1) STANDARD SELECTABLE LUMEN LED 90CRI / 3500K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1802.2 lumens
Efficiency: N/A
Efficacy: 105.4 lumens/watt
Spacing Criteria (0/90/45): 1.19 / 1.19 / 1.09
Luminous Opening: Circular (Dia: 0.42' x H: 0')
CIE Type: Direct


Input Watts (W): 17.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P643173

CATALOG NUMBER: ML5615LSVWFL759FS1E - 594SNB - 1500LM - 3500K

Luminous Intensity Polar Plot





TEST NUMBER: P643173

CATALOG NUMBER: ML5615LSVWFL759FS1E - 594SNB - 1500LM - 3500K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	112	109	106	104	110	107	104	102	103	101	99	99	98	96	96	94	93	91			
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	84	83			
3	99	92	86	81	97	90	85	80	87	83	79	85	81	78	83	79	77	75			
4	93	84	78	73	91	83	77	72	81	76	72	79	74	71	77	73	70	68			
5	87	78	71	66	86	77	70	66	75	69	65	73	68	64	71	67	64	62			
6	82	72	65	60	81	71	64	60	69	64	59	68	63	59	67	62	58	57			
7	77	67	60	55	76	66	59	55	65	59	54	63	58	54	62	57	54	52			
8	73	62	55	50	72	61	55	50	60	54	50	59	54	50	58	53	50	48			
9	69	58	51	47	68	57	51	47	56	50	46	55	50	46	54	50	46	44			
10	65	54	48	43	64	54	47	43	53	47	43	52	47	43	51	46	43	41			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	93600
5°	95131
10°	98066
15°	102002
20°	103472
25°	98556
30°	88464
35°	71371
40°	49248
45°	29339
50°	18557
55°	12662
60°	9852
65°	7976
70°	6440
75°	5002
80°	3000
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 29339 cd/sqm



TEST NUMBER: P643173

CATALOG NUMBER: ML5615LSVWFL759FS1E - 594SNB - 1500LM - 3500K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	115.3	6.4
10°-20°	351.9	19.5
20°-30°	515.1	28.6
30°-40°	454.7	25.2
40°-50°	215.8	12.0
50°-60°	86.9	4.8
60°-70°	43.2	2.4
70°-80°	17.5	1.0
80°-90°	1.8	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	982.3	54.5
0°-40°	1437.1	79.7
0°-60°	1739.7	96.5
0°-90°	1802.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1802.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1186	
5°	1200	115
15°	1248	352
25°	1132	515
35°	741	455
45°	263	216
55°	92	87
65°	43	43
75°	16	17
85°	0	2
90°	0	



TEST NUMBER: P643173

CATALOG NUMBER: ML5615LSVWFL759FS1E - 594SNB - 1500LM - 3500K

CANDELA DISTRIBUTION (FULL):

0°	
0°	1185.7
2.5°	1190.6
5°	1200.5
7.5°	1212.0
10°	1223.4
12.5°	1236.6
15°	1248.1
17.5°	1249.7
20°	1231.7
22.5°	1190.6
25°	1131.5
27.5°	1059.2
30°	970.5
32.5°	863.8
35°	740.6
37.5°	606.0
40°	477.9
42.5°	359.6
45°	262.8
47.5°	195.4
50°	151.1
52.5°	116.6
55°	92.0
57.5°	75.5
60°	62.4
62.5°	50.9
65°	42.7
67.5°	36.1
70°	27.9
72.5°	21.3
75°	16.4
77.5°	11.5
80°	6.6
82.5°	3.3
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)