

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P643196

Luminaire Tested: ML5615LSVWFL759FS1E - 594WB - 1200LM - 2700K

Issue Date: 2/17/2023

Test Information

Test Method: LM-79-2019
Report Number: P643196
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-78)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/17/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML5615LSVWFL759FS1E - 594WB - 1200LM - 2700K
Description: ML56 RR, 75D TIR OPTIC, 5" WHITE GIMBAL TRIM
Light Source: (1) STANDARD SELECTABLE LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1391.3 lumens
Efficiency: N/A
Efficacy: 103.8 lumens/watt
Spacing Criteria (0/90/45): 1.19 / 1.19 / 1.09
Luminous Opening: Circular (Dia: 0.42' x H: 0')
CIE Type: Direct


Input Watts (W): 13.4
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P643196

CATALOG NUMBER: ML5615LSVWFL759FS1E - 594WB - 1200LM - 2700K

Luminous Intensity Polar Plot





TEST NUMBER: P643196

CATALOG NUMBER: ML5615LSVWFL759FS1E - 594WB - 1200LM - 2700K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	112	109	106	104	110	107	104	102	103	101	99	99	98	96	96	94	93	91																			
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	84	83																			
3	99	92	86	81	97	90	85	80	87	83	79	85	81	78	83	79	77	75																			
4	93	84	78	73	91	83	77	72	81	76	71	79	74	71	77	73	70	68																			
5	87	78	71	66	86	77	70	66	75	69	65	73	68	64	71	67	64	62																			
6	82	72	65	60	81	71	64	60	69	64	59	68	63	59	67	62	58	57																			
7	77	67	60	55	76	66	59	55	65	59	54	63	58	54	62	57	54	52																			
8	73	62	55	50	72	61	55	50	60	54	50	59	54	50	58	53	50	48																			
9	69	58	51	47	68	57	51	46	56	50	46	55	50	46	54	50	46	44																			
10	65	54	48	43	64	54	47	43	53	47	43	52	47	43	51	46	43	41																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	72255
5°	73434
10°	75702
15°	78726
20°	79866
25°	75979
30°	68337
35°	54950
40°	37912
45°	22585
50°	14283
55°	9923
60°	7578
65°	6145
70°	4962
75°	3843
80°	2318
85°	1177

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 22585 cd/sqm



TEST NUMBER: P643196

CATALOG NUMBER: ML5615LSVWFL759FS1E - 594WB - 1200LM - 2700K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	89.0	6.4
10°-20°	271.6	19.5
20°-30°	397.5	28.6
30°-40°	350.9	25.2
40°-50°	166.4	12.0
50°-60°	67.2	4.8
60°-70°	33.6	2.4
70°-80°	13.5	1.0
80°-90°	1.7	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	758.1	54.5
0°-40°	1108.9	79.7
0°-60°	1342.5	96.5
0°-90°	1391.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1391.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	915	
5°	927	89
15°	963	272
25°	872	397
35°	570	351
45°	202	166
55°	72	67
65°	33	34
75°	13	13
85°	1	2
90°	0	



TEST NUMBER: P643196

CATALOG NUMBER: ML5615LSVWFL759FS1E - 594WB - 1200LM - 2700K

CANDELA DISTRIBUTION (FULL):

	0°
0°	915.3
2.5°	919.1
5°	926.7
7.5°	935.5
10°	944.4
12.5°	954.5
15°	963.3
17.5°	964.6
20°	950.7
22.5°	917.8
25°	872.3
27.5°	817.9
30°	749.7
32.5°	666.2
35°	570.2
37.5°	469.0
40°	367.9
42.5°	276.9
45°	202.3
47.5°	151.7
50°	116.3
52.5°	89.8
55°	72.1
57.5°	58.2
60°	48.0
62.5°	40.5
65°	32.9
67.5°	27.8
70°	21.5
72.5°	16.4
75°	12.6
77.5°	8.8
80°	5.1
82.5°	2.5
85°	1.3
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)