

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P643197

Luminaire Tested: ML5615LSVWFL759FS1E - 594WB - 1200LM - 3000K

Issue Date: 2/17/2023

Test Information

Test Method: LM-79-2019
Report Number: P643197
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-78)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/17/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML5615LSVWFL759FS1E - 594WB - 1200LM - 3000K
Description: ML56 RR, 75D TIR OPTIC, 5" WHITE GIMBAL TRIM
Light Source: (1) STANDARD SELECTABLE LUMEN LED 90CRI / 3000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1430.9 lumens
Efficiency: N/A
Efficacy: 106.8 lumens/watt
Spacing Criteria (0/90/45): 1.19 / 1.19 / 1.09
Luminous Opening: Circular (Dia: 0.42' x H: 0')
CIE Type: Direct


Input Watts (W): 13.4
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P643197

CATALOG NUMBER: ML5615LSVWFL759FS1E - 594WB - 1200LM - 3000K

Luminous Intensity Polar Plot





TEST NUMBER: P643197

CATALOG NUMBER: ML5615LSVWFL759FS1E - 594WB - 1200LM - 3000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20					
RC	80					70					50					30					10					0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																										
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100					100			
1	112	109	106	104	110	107	104	102	103	101	99	99	98	96	96	94	93	91					91			
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	84	83					83			
3	99	92	86	81	97	90	85	80	87	83	79	85	81	78	83	79	77	75					75			
4	93	84	78	73	91	83	77	72	81	76	71	79	74	71	77	73	70	68					68			
5	87	78	71	66	86	77	70	66	75	69	65	73	68	64	71	67	64	62					62			
6	82	72	65	60	81	71	64	60	69	64	59	68	63	59	67	62	58	57					57			
7	77	67	60	55	76	66	59	55	65	59	54	63	58	54	62	57	54	52					52			
8	73	62	55	50	72	61	55	50	60	54	50	59	54	50	58	53	50	48					48			
9	69	58	51	47	68	57	51	46	56	50	46	55	50	46	54	50	46	44					44			
10	65	54	48	43	64	54	47	43	53	47	43	52	47	43	51	46	43	41					41			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	74315
5°	75526
10°	77858
15°	80974
20°	82142
25°	78148
30°	70288
35°	56511
40°	38994
45°	23232
50°	14688
55°	10198
60°	7799
65°	6314
70°	5101
75°	3965
80°	2364
85°	1177

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 23232 cd/sqm



TEST NUMBER: P643197

CATALOG NUMBER: ML5615LSVWFL759FS1E - 594WB - 1200LM - 3000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	91.6	6.4
10°-20°	279.3	19.5
20°-30°	408.8	28.6
30°-40°	360.9	25.2
40°-50°	171.1	12.0
50°-60°	69.1	4.8
60°-70°	34.5	2.4
70°-80°	13.9	1.0
80°-90°	1.8	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	779.7	54.5
0°-40°	1140.6	79.7
0°-60°	1380.8	96.5
0°-90°	1430.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1430.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	941	
5°	953	92
15°	991	279
25°	897	409
35°	586	361
45°	208	171
55°	74	69
65°	34	35
75°	13	14
85°	1	2
90°	0	



TEST NUMBER: P643197

CATALOG NUMBER: ML5615LSVWFL759FS1E - 594WB - 1200LM - 3000K

CANDELA DISTRIBUTION (FULL):

	0°
0°	941.4
2.5°	945.3
5°	953.1
7.5°	962.2
10°	971.3
12.5°	981.7
15°	990.8
17.5°	992.2
20°	977.8
22.5°	944.0
25°	897.2
27.5°	841.3
30°	771.1
32.5°	685.3
35°	586.4
37.5°	482.4
40°	378.4
42.5°	284.8
45°	208.1
47.5°	156.0
50°	119.6
52.5°	92.3
55°	74.1
57.5°	59.8
60°	49.4
62.5°	41.6
65°	33.8
67.5°	28.6
70°	22.1
72.5°	16.9
75°	13.0
77.5°	9.1
80°	5.2
82.5°	2.6
85°	1.3
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)