

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P643225

Luminaire Tested: ML5615LSVWFL759FS1E - 596WB - 900LM - 5000K

Issue Date: 2/17/2023

Test Information

Test Method: LM-79-2019
Report Number: P643225
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-81)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/17/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML5615LSVWFL759FS1E - 596WB - 900LM - 5000K
Description: ML56 RR, 75D TIR OPTIC, 5" SHALLOW WHITE BAFFLE TRIM
Light Source: (1) STANDARD SELECTABLE LUMEN LED 90CRI / 5000K CCT
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1245.3 lumens
Efficiency: N/A
Efficacy: 118.6 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 1.2 / 1.1
Luminous Opening: Circular (Dia: 0.42' x H: 0')
CIE Type: Direct

Input Watts (W): 10.5
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P643225
CATALOG NUMBER: ML5615LSVWFL759FS1E - 596WB - 900LM - 5000K

Luminous Intensity Polar Plot





TEST NUMBER: P643225

CATALOG NUMBER: ML5615LSVWFL759FS1E - 596WB - 900LM - 5000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100																
1	113	110	107	104	110	107	105	103	103	101	99	100	98	96	96	95	94	92			92																
2	106	101	96	92	104	99	95	91	95	92	89	92	90	87	90	87	85	83			83																
3	100	92	87	82	98	91	86	81	88	84	80	86	82	79	83	80	78	76			76																
4	94	85	79	74	92	84	78	73	82	77	73	80	75	72	78	74	71	69			69																
5	88	78	72	67	86	77	71	67	76	70	66	74	69	65	72	68	65	63			63																
6	83	73	66	61	81	72	65	61	70	65	60	69	64	60	67	63	59	58			58																
7	78	67	61	56	76	67	60	56	65	60	55	64	59	55	63	58	55	53			53																
8	73	63	56	51	72	62	56	51	61	55	51	60	55	51	59	54	50	49			49																
9	69	59	52	47	68	58	52	47	57	51	47	56	51	47	55	50	47	45			45																
10	66	55	48	44	65	54	48	44	53	48	44	53	47	44	52	47	43	42			42																

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	65474
5°	66445
10°	68584
15°	71322
20°	72448
25°	69176
30°	62431
35°	50873
40°	35645
45°	21211
50°	12576
55°	7680
60°	5210
65°	2970
70°	1569
75°	1403
80°	1546
85°	996

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 21211 cd/sqm



TEST NUMBER: P643225

CATALOG NUMBER: ML5615LSVWFL759FS1E - 596WB - 900LM - 5000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	80.6	6.5
10°-20°	246.1	19.8
20°-30°	361.6	29.0
30°-40°	324.6	26.1
40°-50°	155.1	12.5
50°-60°	53.4	4.3
60°-70°	17.2	1.4
70°-80°	5.0	0.4
80°-90°	1.7	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	688.3	55.3
0°-40°	1012.9	81.3
0°-60°	1221.5	98.1
0°-90°	1245.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1245.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	829	
5°	838	81
15°	873	246
25°	794	362
35°	528	325
45°	190	155
55°	56	53
65°	16	17
75°	5	5
85°	1	2
90°	0	



TEST NUMBER: P643225
CATALOG NUMBER: ML5615LSVWFL759FS1E - 596WB - 900LM - 5000K

CANDELA DISTRIBUTION (FULL):

	0°
0°	829.4
2.5°	832.8
5°	838.5
7.5°	847.6
10°	855.6
12.5°	864.7
15°	872.7
17.5°	873.8
20°	862.4
22.5°	834.0
25°	794.2
27.5°	744.1
30°	684.9
32.5°	613.3
35°	527.9
37.5°	436.9
40°	345.9
42.5°	260.5
45°	190.0
47.5°	139.9
50°	102.4
52.5°	74.0
55°	55.8
57.5°	43.2
60°	33.0
62.5°	23.9
65°	15.9
67.5°	10.2
70°	6.8
72.5°	5.7
75°	4.6
77.5°	3.4
80°	3.4
82.5°	2.3
85°	1.1
87.5°	1.1
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)