

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P643407

Luminaire Tested: ML5615LSVWFL9FS1E - 592H - 1200LM - 3000K

Issue Date: 2/17/2023

**Test Information**

Test Method: LM-79-2019  
Report Number: P643407  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-95)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 2/17/2023  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: HALO  
Catalog Number: ML5615LSVWFL9FS1E - 592H - 1200LM - 3000K  
Description: ML56 RR, MILKY OPTIC, 5" HAZE TRIM  
Light Source: (1) STANDARD SELECTABLE LUMEN LED 90CRI / 3000K CCT  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 1275.4 lumens  
Efficiency: N/A  
Efficacy: 95.2 lumens/watt  
Spacing Criteria (0/90/45): 0.89 / 0.89 / 0.97  
Luminous Opening: Circular (Dia: 0.42' x H: 0')  
CIE Type: Direct

Input Watts (W): 13.4  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT



TEST NUMBER: P643407  
CATALOG NUMBER: ML5615LSVWFL9FS1E - 592H - 1200LM - 3000K

### Luminous Intensity Polar Plot





TEST NUMBER: P643407

CATALOG NUMBER: ML5615LSVWFL9FS1E - 592H - 1200LM - 3000K

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100																
1	113	110	107	105	110	108	105	103	104	102	100	100	98	97	96	95	94	92			92																
2	107	101	97	93	104	99	95	92	96	93	90	93	90	88	90	88	86	84			84																
3	100	93	88	83	98	92	87	83	89	85	81	87	83	80	84	81	79	77			77																
4	95	86	80	75	93	85	79	75	83	78	74	81	76	73	79	75	72	71			71																
5	89	80	73	68	87	79	73	68	77	72	68	75	71	67	74	70	66	65			65																
6	84	74	67	63	82	73	67	62	72	66	62	70	65	62	69	64	61	60			60																
7	79	69	62	58	78	68	62	57	67	61	57	66	61	57	64	60	56	55			55																
8	75	64	58	53	73	64	57	53	63	57	53	61	56	53	60	56	52	51			51																
9	71	60	54	49	70	60	53	49	59	53	49	58	53	49	57	52	49	47			47																
10	67	56	50	46	66	56	50	46	55	50	46	54	49	46	54	49	45	44			44																

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	93963
5°	91953
10°	86547
15°	79421
20°	72565
25°	66171
30°	59404
35°	50276
40°	36727
45°	22942
50°	13104
55°	7157
60°	3694
65°	1700
70°	900
75°	397
80°	591
85°	0

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 45°  
 Luminance: 22942 cd/sqm



TEST NUMBER: P643407

CATALOG NUMBER: ML5615LSVWFL9FS1E - 592H - 1200LM - 3000K

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	108.2	8.5
10°-20°	272.3	21.4
20°-30°	348.4	27.3
30°-40°	319.5	25.0
40°-50°	164.3	12.9
50°-60°	50.1	3.9
60°-70°	10.4	0.8
70°-80°	2.1	0.2
80°-90°	0.2	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	728.9	57.2
0°-40°	1048.4	82.2
0°-60°	1262.8	99.0
0°-90°	1275.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1275.4	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	1190	
5°	1160	108
15°	972	272
25°	760	348
35°	522	319
45°	206	164
55°	52	50
65°	9	10
75°	1	2
85°	0	0
90°	0	



TEST NUMBER: P643407

CATALOG NUMBER: ML5615LSVWFL9FS1E - 592H - 1200LM - 3000K

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	1190.3
2.5°	1182.5
5°	1160.4
7.5°	1125.3
10°	1079.7
12.5°	1026.4
15°	971.8
17.5°	917.1
20°	863.8
22.5°	811.7
25°	759.7
27.5°	706.4
30°	651.7
32.5°	590.6
35°	521.7
37.5°	441.0
40°	356.4
42.5°	275.8
45°	205.5
47.5°	149.6
50°	106.7
52.5°	74.2
55°	52.0
57.5°	35.1
60°	23.4
62.5°	14.3
65°	9.1
67.5°	5.2
70°	3.9
72.5°	2.6
75°	1.3
77.5°	1.3
80°	1.3
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report





Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)