

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P643440

Luminaire Tested: ML5615LSVWFL9FS1E - 592W - 1200LM - 5000K

Issue Date: 2/17/2023

Test Information

Test Method: LM-79-2019
Report Number: P643440
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-96)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/17/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML5615LSVWFL9FS1E - 592W - 1200LM - 5000K
Description: ML56 RR, MILKY OPTIC, 5" WHITE TRIM
Light Source: (1) STANDARD SELECTABLE LUMEN LED 90CRI / 5000K CCT
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1402.3 lumens
Efficiency: N/A
Efficacy: 104.6 lumens/watt
Spacing Criteria (0/90/45): 1.16 / 1.16 / 1.14
Luminous Opening: Circular (Dia: 0.5' x H: 0')
CIE Type: Direct

Input Watts (W): 13.4
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P643440
CATALOG NUMBER: ML5615LSVWFL9FS1E - 592W - 1200LM - 5000K

Luminous Intensity Polar Plot





TEST NUMBER: P643440

CATALOG NUMBER: ML5615LSVWFL9FS1E - 592W - 1200LM - 5000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	111	107	104	101	109	105	102	99	101	99	96	97	95	93	94	92	91	89																			
2	103	97	91	87	101	95	90	86	92	88	84	89	85	82	86	83	80	78																			
3	96	88	81	76	94	86	80	75	83	78	74	81	76	73	78	75	71	70																			
4	90	80	72	67	87	78	72	66	76	70	66	74	69	65	72	68	64	62																			
5	84	73	65	60	82	72	65	59	70	64	59	68	62	58	66	61	58	56																			
6	78	67	59	54	76	66	59	53	64	58	53	63	57	53	61	56	52	50																			
7	73	61	54	49	72	61	54	48	59	53	48	58	52	48	57	52	48	46																			
8	69	57	49	44	67	56	49	44	55	49	44	54	48	44	53	47	44	42																			
9	65	53	45	41	63	52	45	41	51	45	40	50	44	40	49	44	40	38																			
10	61	49	42	37	60	49	42	37	48	41	37	47	41	37	46	41	37	35																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	45484
5°	45344
10°	44828
15°	44069
20°	43205
25°	42269
30°	40595
35°	36667
40°	29226
45°	20739
50°	15087
55°	11679
60°	10087
65°	9327
70°	8751
75°	8218
80°	7261
85°	5409

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 20739 cd/sqm



TEST NUMBER: P643440

CATALOG NUMBER: ML5615LSVWFL9FS1E - 592W - 1200LM - 5000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	78.0	5.6
10°-20°	218.8	15.6
20°-30°	320.6	22.9
30°-40°	335.9	24.0
40°-50°	212.3	15.1
50°-60°	113.6	8.1
60°-70°	71.5	5.1
70°-80°	40.9	2.9
80°-90°	10.6	0.8
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	617.4	44.0
0°-40°	953.3	68.0
0°-60°	1279.3	91.2
0°-90°	1402.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1402.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	830	
5°	824	78
15°	776	219
25°	699	321
35°	548	336
45°	268	212
55°	122	114
65°	72	71
75°	39	41
85°	9	11
90°	0	



TEST NUMBER: P643440

CATALOG NUMBER: ML5615LSVWFL9FS1E - 592W - 1200LM - 5000K

CANDELA DISTRIBUTION (FULL):

0°	
0°	829.7
2.5°	828.3
5°	824.0
7.5°	815.3
10°	805.3
12.5°	792.3
15°	776.5
17.5°	759.2
20°	740.6
22.5°	719.0
25°	698.8
27.5°	673.0
30°	641.3
32.5°	601.1
35°	547.9
37.5°	483.2
40°	408.4
42.5°	333.6
45°	267.5
47.5°	215.7
50°	176.9
52.5°	146.7
55°	122.2
57.5°	106.4
60°	92.0
62.5°	80.5
65°	71.9
67.5°	63.3
70°	54.6
72.5°	47.5
75°	38.8
77.5°	30.2
80°	23.0
82.5°	15.8
85°	8.6
87.5°	2.9
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)