

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P643521

Luminaire Tested: ML5615LSVWFL9FS1E - 594SNB - 900LM - 2700K

Issue Date: 2/17/2023

Test Information

Test Method: LM-79-2019
Report Number: P643521
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-102)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/17/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML5615LSVWFL9FS1E - 594SNB - 900LM - 2700K
Description: ML56 RR, MILKY OPTIC, 5" SATIN NICKLE GIMBAL TRIM
Light Source: (1) STANDARD SELECTABLE LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1079.0 lumens
Efficiency: N/A
Efficacy: 102.8 lumens/watt
Spacing Criteria (0/90/45): 1.19 / 1.19 / 1.26
Luminous Opening: Circular (Dia: 0.42' x H: 0')
CIE Type: Direct


Input Watts (W): 10.5
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P643521

CATALOG NUMBER: ML5615LSVWFL9FS1E - 594SNB - 900LM - 2700K

Luminous Intensity Polar Plot





TEST NUMBER: P643521

CATALOG NUMBER: ML5615LSVWFL9FS1E - 594SNB - 900LM - 2700K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	110	106	102	99	108	104	100	97	100	97	94	96	93	91	92	90	89	87																			
2	101	94	88	83	99	92	87	82	89	84	80	85	82	78	83	79	76	74																			
3	93	84	76	70	91	82	75	70	79	73	69	77	72	67	74	70	66	64																			
4	86	75	67	61	84	74	66	60	71	65	60	69	63	59	67	62	58	56																			
5	80	68	59	53	78	67	59	53	65	58	52	63	57	52	61	56	51	49																			
6	74	61	53	47	72	60	53	47	59	52	46	57	51	46	56	50	46	44																			
7	69	56	48	42	67	55	47	42	54	47	42	52	46	41	51	45	41	39																			
8	64	51	43	38	63	51	43	38	49	42	37	48	42	37	47	41	37	35																			
9	60	47	39	34	59	47	39	34	46	39	34	45	38	34	44	38	34	32																			
10	56	44	36	31	55	43	36	31	42	36	31	41	35	31	41	35	31	29																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	38326
5°	38314
10°	38115
15°	37716
20°	37266
25°	36461
30°	35331
35°	33883
40°	31812
45°	29216
50°	26257
55°	22957
60°	19404
65°	16232
70°	13595
75°	11590
80°	10001
85°	9963

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 29216 cd/sqm



TEST NUMBER: P643521

CATALOG NUMBER: ML5615LSVWFL9FS1E - 594SNB - 900LM - 2700K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	45.9	4.3
10°-20°	130.1	12.1
20°-30°	192.5	17.8
30°-40°	219.1	20.3
40°-50°	201.6	18.7
50°-60°	149.2	13.8
60°-70°	87.3	8.1
70°-80°	41.0	3.8
80°-90°	12.2	1.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	368.6	34.2
0°-40°	587.6	54.5
0°-60°	938.5	87.0
0°-90°	1079.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1079.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	486	
5°	484	46
15°	462	130
25°	419	193
35°	352	219
45°	262	202
55°	167	149
65°	87	87
75°	38	41
85°	11	12
90°	0	



TEST NUMBER: P643521

CATALOG NUMBER: ML5615LSVWFL9FS1E - 594SNB - 900LM - 2700K

CANDELA DISTRIBUTION (FULL):

0°	
0°	485.5
2.5°	484.5
5°	483.5
7.5°	480.5
10°	475.5
12.5°	469.5
15°	461.5
17.5°	452.5
20°	443.6
22.5°	431.6
25°	418.6
27.5°	404.6
30°	387.6
32.5°	370.6
35°	351.6
37.5°	330.7
40°	308.7
42.5°	285.7
45°	261.7
47.5°	237.8
50°	213.8
52.5°	189.8
55°	166.8
57.5°	143.9
60°	122.9
62.5°	103.9
65°	86.9
67.5°	71.9
70°	58.9
72.5°	48.0
75°	38.0
77.5°	29.0
80°	22.0
82.5°	16.0
85°	11.0
87.5°	7.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)