

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P643611

Luminaire Tested: ML5615LSVWFL9FS1E - 692SC - 900LM - 2700K

Issue Date: 2/17/2023

**Test Information**

Test Method: LM-79-2019  
Report Number: P643611  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-106)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 2/17/2023  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: HALO  
Catalog Number: ML5615LSVWFL9FS1E - 692SC - 900LM - 2700K  
Description: ML56 RR, MILKY OPTIC, 6" SPECULAR CLEAR TRIM  
Light Source: (1) STANDARD SELECTABLE LUMEN LED 90CRI / 2700K CCT  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 1036.0 lumens  
Efficiency: N/A  
Efficacy: 98.7 lumens/watt  
Spacing Criteria (0/90/45): 0.54 / 0.54 / 0.69  
Luminous Opening: Circular (Dia: 0.5' x H: 0')  
CIE Type: Direct

Input Watts (W): 10.5  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT



TEST NUMBER: P643611  
CATALOG NUMBER: ML5615LSVWFL9FS1E - 692SC - 900LM - 2700K

### Luminous Intensity Polar Plot





TEST NUMBER: P643611

CATALOG NUMBER: ML5615LSVWFL9FS1E - 692SC - 900LM - 2700K

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100																
1	113	110	107	105	111	108	106	103	104	102	100	100	99	97	97	95	94	93			93																
2	107	102	97	93	105	100	96	92	97	93	90	94	91	88	91	89	87	85			85																
3	101	94	88	84	99	92	87	83	90	85	82	87	84	81	85	82	79	78			78																
4	95	87	81	76	93	86	80	76	83	79	75	81	77	74	79	76	73	71			71																
5	90	81	74	70	88	80	74	69	78	73	69	76	72	68	74	71	67	66			66																
6	85	75	69	64	83	74	68	64	73	67	63	71	66	63	70	66	62	61			61																
7	80	70	64	59	79	69	63	59	68	63	59	67	62	58	66	61	58	56			56																
8	76	66	59	55	75	65	59	55	64	58	54	63	58	54	62	57	54	52			52																
9	72	62	55	51	71	61	55	51	60	55	51	59	54	51	58	54	50	49			49																
10	68	58	52	48	67	58	52	48	57	51	48	56	51	47	55	51	47	46			46																

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	80586
5°	75335
10°	61611
15°	46856
20°	37418
25°	31901
30°	28061
35°	25049
40°	21340
45°	15048
50°	8793
55°	4588
60°	2083
65°	649
70°	160
75°	0
80°	0
85°	0

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 45°  
 Luminance: 15048 cd/sqm



TEST NUMBER: P643611

CATALOG NUMBER: ML5615LSVWFL9FS1E - 692SC - 900LM - 2700K

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	122.1	11.8
10°-20°	232.8	22.5
20°-30°	244.1	23.6
30°-40°	232.8	22.5
40°-50°	150.3	14.5
50°-60°	46.6	4.5
60°-70°	6.8	0.7
70°-80°	0.4	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	599.0	57.8
0°-40°	831.9	80.3
0°-60°	1028.8	99.3
0°-90°	1036.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1036.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	1470	
5°	1369	122
15°	826	233
25°	527	244
35°	374	233
45°	194	150
55°	48	47
65°	5	7
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P643611

CATALOG NUMBER: ML5615LSVWFL9FS1E - 692SC - 900LM - 2700K

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	1470.0
2.5°	1444.0
5°	1369.0
7.5°	1249.9
10°	1106.8
12.5°	957.7
15°	825.6
17.5°	722.5
20°	641.4
22.5°	579.4
25°	527.4
27.5°	483.3
30°	443.3
32.5°	408.3
35°	374.3
37.5°	340.2
40°	298.2
42.5°	248.2
45°	194.1
47.5°	144.1
50°	103.1
52.5°	71.0
55°	48.0
57.5°	31.0
60°	19.0
62.5°	11.0
65°	5.0
67.5°	2.0
70°	1.0
72.5°	1.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report





Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)