

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P643692

Luminaire Tested: ML5615LSVWFL9FS1E - 694TBZB - 1200LM - 3000K

Issue Date: 2/17/2023

Test Information

Test Method: LM-79-2019
Report Number: P643692
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-114)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/17/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: HALO
Catalog Number: ML5615LSVWFL9FS1E - 694TBZB - 1200LM - 3000K
Description: ML56 RR, MILKY OPTIC, 6" TUSCON BRONZE GIMBAL TRIM
Light Source: (1) STANDARD SELECTABLE LUMEN LED 90CRI / 3000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1376.3 lumens
Efficiency: N/A
Efficacy: 102.7 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 1.2 / 1.27
Luminous Opening: Circular (Dia: 0.5' x H: 0')
CIE Type: Direct


Input Watts (W): 13.4
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P643692

CATALOG NUMBER: ML5615LSVWFL9FS1E - 694TBZB - 1200LM - 3000K

Luminous Intensity Polar Plot





TEST NUMBER: P643692

CATALOG NUMBER: ML5615LSVWFL9FS1E - 694TBZB - 1200LM - 3000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	110	106	102	99	107	104	100	97	100	97	94	96	93	91	92	90	89	87																			
2	101	94	88	83	99	92	87	82	89	84	80	85	82	78	82	79	76	74																			
3	93	84	76	70	91	82	75	70	79	73	69	77	72	67	74	70	66	64																			
4	86	75	67	61	84	74	66	60	71	65	60	69	63	59	67	62	58	56																			
5	80	68	59	53	78	67	59	53	64	58	52	63	57	52	61	56	51	49																			
6	74	61	53	47	72	60	53	47	59	52	46	57	51	46	56	50	46	44																			
7	69	56	48	42	67	55	47	42	54	47	41	52	46	41	51	45	41	39																			
8	64	51	43	38	63	51	43	38	49	42	37	48	42	37	47	41	37	35																			
9	60	47	39	34	59	47	39	34	46	39	34	45	38	34	44	38	34	32																			
10	56	44	36	31	55	43	36	31	42	36	31	41	35	31	40	35	31	29																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	33742
5°	33656
10°	33539
15°	33309
20°	32950
25°	32270
30°	31385
35°	30042
40°	28217
45°	25925
50°	23308
55°	20272
60°	17126
65°	14347
70°	12101
75°	10463
80°	9029
85°	8995

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 25925 cd/sqm



TEST NUMBER: P643692

CATALOG NUMBER: ML5615LSVWFL9FS1E - 694TBZB - 1200LM - 3000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	58.1	4.2
10°-20°	165.5	12.0
20°-30°	245.6	17.8
30°-40°	280.0	20.3
40°-50°	257.3	18.7
50°-60°	190.2	13.8
60°-70°	110.9	8.1
70°-80°	52.8	3.8
80°-90°	15.9	1.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	469.2	34.1
0°-40°	749.2	54.4
0°-60°	1196.7	86.9
0°-90°	1376.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1376.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	616	
5°	612	58
15°	587	165
25°	534	246
35°	449	280
45°	334	257
55°	212	190
65°	111	111
75°	49	53
85°	14	16
90°	0	



TEST NUMBER: P643692

CATALOG NUMBER: ML5615LSVWFL9FS1E - 694TBZB - 1200LM - 3000K

CANDELA DISTRIBUTION (FULL):

0°	
0°	615.5
2.5°	614.2
5°	611.6
7.5°	607.7
10°	602.5
12.5°	596.0
15°	586.9
17.5°	576.5
20°	564.8
22.5°	550.4
25°	533.5
27.5°	516.6
30°	495.8
32.5°	473.7
35°	448.9
37.5°	422.9
40°	394.3
42.5°	364.4
45°	334.4
47.5°	303.2
50°	273.3
52.5°	242.0
55°	212.1
57.5°	183.5
60°	156.2
62.5°	131.4
65°	110.6
67.5°	91.1
70°	75.5
72.5°	61.2
75°	49.4
77.5°	37.7
80°	28.6
82.5°	20.8
85°	14.3
87.5°	9.1
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)