

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: HALO

Report Number: P643703

Luminaire Tested: ML5615LSVWFL9FS1E - 694TBZB - 900LM - 3500K

Issue Date: 2/17/2023

**Test Information**

Test Method: LM-79-2019  
Report Number: P643703  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2212-866-114)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 2/17/2023  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: HALO  
Catalog Number: ML5615LSVWFL9FS1E - 694TBZB - 900LM - 3500K  
Description: ML56 RR, MILKY OPTIC, 6" TUSCON BRONZE GIMBAL TRIM  
Light Source: (1) STANDARD SELECTABLE LUMEN LED 90CRI / 3500K CCT  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 1117.8 lumens  
Efficiency: N/A  
Efficacy: 106.5 lumens/watt  
Spacing Criteria (0/90/45): 1.2 / 1.2 / 1.27  
Luminous Opening: Circular (Dia: 0.5' x H: 0')  
CIE Type: Direct

Input Watts (W): 10.5  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT



TEST NUMBER: P643703  
CATALOG NUMBER: ML5615LSVWFL9FS1E - 694TBZB - 900LM - 3500K

### Luminous Intensity Polar Plot





TEST NUMBER: P643703

CATALOG NUMBER: ML5615LSVWFL9FS1E - 694TBZB - 900LM - 3500K

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	110	106	102	99	107	104	100	97	100	97	94	96	93	91	92	90	89	87																			
2	101	94	88	83	99	92	87	82	89	84	80	85	82	78	82	79	76	74																			
3	93	84	76	70	91	82	75	70	79	73	69	77	72	67	74	70	66	64																			
4	86	75	67	61	84	74	66	60	71	65	60	69	63	59	67	62	58	56																			
5	80	68	59	53	78	67	59	53	64	58	52	63	57	52	61	56	51	49																			
6	74	61	53	47	72	60	53	47	59	52	46	57	51	46	56	50	46	44																			
7	69	56	48	42	67	55	47	42	54	47	41	52	46	41	51	45	41	39																			
8	64	51	43	38	63	51	43	38	49	42	37	48	42	37	47	41	37	35																			
9	60	47	39	34	59	47	39	34	46	39	34	45	38	34	44	38	34	32																			
10	56	44	36	31	55	43	36	31	42	36	31	41	35	31	40	35	31	29																			

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	27405
5°	27333
10°	27237
15°	27055
20°	26760
25°	26209
30°	25491
35°	24400
40°	22914
45°	21056
50°	18925
55°	16468
60°	13902
65°	11648
70°	9825
75°	8515
80°	7356
85°	7296

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 45°  
 Luminance: 21056 cd/sqm



TEST NUMBER: P643703

CATALOG NUMBER: ML5615LSVWFL9FS1E - 694TBZB - 900LM - 3500K

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	47.2	4.2
10°-20°	134.4	12.0
20°-30°	199.5	17.8
30°-40°	227.4	20.3
40°-50°	209.0	18.7
50°-60°	154.4	13.8
60°-70°	90.1	8.1
70°-80°	42.9	3.8
80°-90°	12.9	1.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	381.1	34.1
0°-40°	608.5	54.4
0°-60°	971.9	86.9
0°-90°	1117.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1117.8	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	500	
5°	497	47
15°	477	134
25°	433	200
35°	365	227
45°	272	209
55°	172	154
65°	90	90
75°	40	43
85°	12	13
90°	0	



TEST NUMBER: P643703

CATALOG NUMBER: ML5615LSVWFL9FS1E - 694TBZB - 900LM - 3500K

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	499.9
2.5°	498.8
5°	496.7
7.5°	493.6
10°	489.3
12.5°	484.1
15°	476.7
17.5°	468.2
20°	458.7
22.5°	447.1
25°	433.3
27.5°	419.6
30°	402.7
32.5°	384.7
35°	364.6
37.5°	343.5
40°	320.2
42.5°	295.9
45°	271.6
47.5°	246.3
50°	221.9
52.5°	196.6
55°	172.3
57.5°	149.0
60°	126.8
62.5°	106.7
65°	89.8
67.5°	74.0
70°	61.3
72.5°	49.7
75°	40.2
77.5°	30.6
80°	23.3
82.5°	16.9
85°	11.6
87.5°	7.4
90°	0.0

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report





Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)