

LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: HALO

Report Number: P622382

Luminaire Tested: **HLB6099WZRGBWMWR 6500K**

Issue Date: 9/27/2022

Tested By:

Approved By:



Cooper Lighting Solutions laboratories have been accredited by National Voluntary Laboratory Accreditation Program (NVLAP) that it adheres to the requirements of ISO/IEC 17025:2005 and appropriate IESNA test methods. This report must not be used to claim product certification, approval or endorsement by NVLAP, NIST or any agency of the Federal Government. Results contained in this report are valid for luminaire sample tested, as supplied by requestor. Information related to the luminaire tested has been supplied by requestor and can affect the validity of the test results. Report shall not be reproduced except in full without approval of Cooper Lighting Solutions Lighting Laboratory. Test performed at address noted above.

Test Information

Test Method: LM-79-08
 Report Number: P622382
 Test Lab: COOPER LIGHTING SOLUTIONS
 Issue Date: 9/27/2022
 Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
 Product Line: HALO
 Catalog Number: HLB6099WZRGBWMWR 6500K
 Description: 6 INCH HLB WiZ SELECTABLE CCT
 Light Source: (1) HIGH LUMEN LED 90CRI / 6500K CCT
 Ballast/Driver: -

Summary

Lumens per Lamp: N/A
 Luminaire Lumens: 1075.0 lumens
 Efficiency: N/A
 Efficacy: 90.3 lumens/watt
 Spacing Criteria (0/90/45): 1.22 / 1.22 / 1.34
 Luminous Opening: Circular (Dia: 0.42' x H: 0')
 CIE Type: Direct


Input Watts (W): 11.9
 Input Voltage (V): NR
 Input Current (Ain): NR
 Voltage Rise (V): NR
 Power Factor: NR
 Total Harmonic Distortion (THDi): NR
 Frequency (hertz): 60
 Stabilization Time: NR
 Operation Time: NR
 Ambient Temperature (°C): NR
 Test Distance: 25 FT



Meas		Calibratio	
Instrument	Identificatio		Calibration Due Date
Photometer	GONIO 1 IN0055	4/22/2021	10/22/2021
Power Meter	XITRON 2801 IN0197	12/1/2020	12/1/2021
AC Power Source	CHROMA 61505 IN0196	12/1/2020	12/1/2021
DC Power Supply	AGILENT E3634A IN0198	11/30/2020	11/30/2021
Room Thermometer	ONSET IN0143	12/1/2020	12/1/2021

TEST NUMBER: P622382
CATALOG NUMBER: HLB6099WZRGBWMWR 6500K

Luminous Intensity Polar Plot



TEST NUMBER: P622382
 CATALOG NUMBER: HLB6099WZRGBWMWR 6500K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100	100
1	109	104	100	96	106	102	98	95	98	95	92	94	91	89	90	88	86	84	84	84	84
2	99	91	84	79	97	89	83	78	86	80	76	82	78	74	79	76	72	70	70	70	70
3	90	80	72	65	88	78	71	65	75	69	64	73	67	63	70	65	61	59	59	59	59
4	83	71	62	55	81	70	61	55	67	60	54	65	59	54	63	57	53	51	51	51	51
5	76	63	54	48	74	62	54	48	60	53	47	58	52	46	56	51	46	44	44	44	44
6	70	57	48	42	68	56	48	42	54	47	41	53	46	41	51	45	40	38	38	38	38
7	65	52	43	37	64	51	43	37	49	42	36	48	41	36	47	41	36	34	34	34	34
8	61	47	39	33	59	47	38	33	45	38	33	44	37	32	43	37	32	30	30	30	30
9	57	43	35	30	55	43	35	30	42	34	29	41	34	29	40	34	29	27	27	27	27
10	53	40	32	27	52	40	32	27	39	32	27	38	31	27	37	31	26	25	25	25	25

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	31224
5°	31163
10°	31048
15°	30791
20°	30463
25°	30147
30°	29621
35°	29162
40°	28637
45°	28000
50°	27329
55°	26573
60°	25644
65°	24412
70°	22818
75°	20474
80°	17123
85°	10656

TEST NUMBER: P622382
 CATALOG NUMBER: HLB6099WZRGBWMWR 6500K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	37.3	3.5
10°-20°	106.2	9.9
20°-30°	159.2	14.8
30°-40°	189.3	17.6
40°-50°	193.8	18.0
50°-60°	172.6	16.1
60°-70°	129.6	12.1
70°-80°	71.4	6.6
80°-90°	15.7	1.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	302.7	28.2
0°-40°	492.0	45.8
0°-60°	858.4	79.8
0°-90°	1075.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1075.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	396	
5°	393	37
15°	377	106
25°	346	159
35°	303	189
45°	251	194
55°	193	173
65°	131	130
75°	67	71
85°	12	16
90°	0	

TEST NUMBER: P622382
CATALOG NUMBER: HLB6099WZRGBWMWR 6500K

CANDELA DISTRIBUTION (FULL):

0°	
0°	395.5
2.5°	394.5
5°	393.3
7.5°	389.7
10°	387.3
12.5°	382.6
15°	376.8
17.5°	369.6
20°	362.6
22.5°	354.4
25°	346.1
27.5°	335.5
30°	325.0
32.5°	314.4
35°	302.6
37.5°	290.8
40°	277.9
42.5°	264.9
45°	250.8
47.5°	237.9
50°	222.5
52.5°	208.4
55°	193.1
57.5°	177.8
60°	162.4
62.5°	147.2
65°	130.7
67.5°	115.4
70°	98.9
72.5°	83.6
75°	67.1
77.5°	51.8
80°	37.7
82.5°	23.5
85°	11.8
87.5°	3.6
90°	0.0

(END OF REPORT)