

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: HALO

Report Number: P328449

Luminaire Tested: **L815MED10WF940MB**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P328449
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1905-290-13)
Test Lab: INNOVATION CENTER(G3)
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: HALO
Catalog Number: L815MED10WF940MB
Description: Medium, 1000lm, 60D, 4000K, black finish
Light Source: (1) 4000K CCT, 90 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1253.0 lumens
Efficiency: N/A
Efficacy: 98.7 lumens/watt
Spacing Criteria (0/90/45): 0.96 / 0.96 / 0.88
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct


Input Watts (W): 12.7
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P328449

CATALOG NUMBER: L815MED10WF940MB

Luminous Intensity Polar Plot





TEST NUMBER: P328449

CATALOG NUMBER: L815MED10WF940MB

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	114	111	108	106	111	109	106	104	105	103	101		101	99	98		97	96	95	94
2	108	103	99	96	106	101	98	95	98	95	93		95	93	91		92	91	89	87
3	103	96	91	87	101	95	90	87	92	88	85		90	87	84		88	85	83	81
4	98	90	85	80	96	89	84	80	87	82	79		85	81	78		83	80	77	76
5	93	84	79	74	91	84	78	74	82	77	73		80	76	73		79	75	72	71
6	88	79	73	69	87	79	73	69	77	72	69		76	71	68		74	71	68	66
7	84	75	69	65	83	74	68	65	73	68	64		72	67	64		71	67	63	62
8	80	71	65	61	79	70	64	60	69	64	60		68	63	60		67	63	60	58
9	76	67	61	57	75	66	61	57	65	60	57		64	60	56		64	59	56	55
10	73	63	57	54	72	63	57	54	62	57	53		61	57	53		60	56	53	52

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	173338
5°	172526
10°	169937
15°	165750
20°	156740
25°	135457
30°	102818
35°	50037
40°	18710
45°	10519
50°	7407
55°	4882
60°	3651
65°	3035
70°	2308
75°	1191
80°	355
85°	0



TEST NUMBER: P328449

CATALOG NUMBER: L815MED10WF940MB

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	131.9	10.5
10°-20°	363.4	29.0
20°-30°	448.9	35.8
30°-40°	223.2	17.8
40°-50°	50.7	4.0
50°-60°	21.6	1.7
60°-70°	10.3	0.8
70°-80°	2.9	0.2
80°-90°	0.1	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	944.2	75.4
0°-40°	1167.4	93.2
0°-60°	1239.8	98.9
0°-90°	1253.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1253.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1405	
5°	1393	132
15°	1298	363
25°	995	449
35°	332	223
45°	60	51
55°	23	22
65°	10	10
75°	2	3
85°	0	0
90°	0	



TEST NUMBER: P328449

CATALOG NUMBER: L815MED10WF940MB

CANDELA DISTRIBUTION (FULL):

0°	
0°	1405.3
2.5°	1400.8
5°	1393.4
7.5°	1380.5
10°	1356.8
12.5°	1329.6
15°	1298.0
17.5°	1256.9
20°	1194.1
22.5°	1106.1
25°	995.3
27.5°	874.7
30°	721.9
32.5°	526.1
35°	332.3
37.5°	192.8
40°	116.2
42.5°	79.6
45°	60.3
47.5°	48.5
50°	38.6
52.5°	29.7
55°	22.7
57.5°	18.3
60°	14.8
62.5°	12.4
65°	10.4
67.5°	8.4
70°	6.4
72.5°	4.0
75°	2.5
77.5°	1.0
80°	0.5
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)