

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: HALO

Report Number: P328502

Luminaire Tested: **L815SML05FL927MB**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P328502  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1905-290-5)  
Test Lab: INNOVATION CENTER(G3)  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: HALO  
Catalog Number: L815SML05FL927MB  
Description: Small, 500lm, 45D, 2700K, black finish  
Light Source: (1) 2700K CCT, 90 CRI LEDS  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 575.0 lumens  
Efficiency: N/A  
Efficacy: 84.6 lumens/watt  
Spacing Criteria (0/90/45): 0.71 / 0.71 / 0.68  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct

Input Watts (W): 6.8  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P328502  
CATALOG NUMBER: L815SML05FL927MB

### Luminous Intensity Polar Plot





TEST NUMBER: P328502

CATALOG NUMBER: L815SML05FL927MB

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	114	112	109	107	112	109	107	106	105	104	102		102	100	99		98	97	96	95
2	109	105	101	98	107	103	100	97	100	97	95		97	95	93		94	93	91	89
3	105	99	94	91	103	97	93	90	95	91	89		93	90	87		90	88	86	85
4	100	93	88	85	98	92	88	84	90	86	83		88	85	82		86	84	81	80
5	96	88	83	80	94	88	83	79	86	82	78		84	81	78		83	80	77	76
6	92	84	79	75	91	83	78	75	82	77	74		81	77	74		79	76	73	72
7	88	80	75	71	87	79	74	71	78	74	70		77	73	70		76	72	70	68
8	85	76	71	67	83	76	71	67	75	70	67		74	70	67		73	69	66	65
9	81	73	68	64	80	72	67	64	71	67	64		71	67	64		70	66	63	62
10	78	70	65	61	77	69	64	61	69	64	61		68	64	61		67	63	61	59

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	229894
5°	225973
10°	211285
15°	183815
20°	140852
25°	91312
30°	50717
35°	22379
40°	9475
45°	6109
50°	4605
55°	3288
60°	2105
65°	1245
70°	641
75°	254
80°	0
85°	0



TEST NUMBER: P328502

CATALOG NUMBER: L815SML05FL927MB

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	95.5	16.6
10°-20°	220.9	38.4
20°-30°	173.8	30.2
30°-40°	58.1	10.1
40°-50°	16.1	2.8
50°-60°	7.7	1.3
60°-70°	2.6	0.4
70°-80°	0.4	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	490.1	85.2
0°-40°	548.2	95.3
0°-60°	572.0	99.5
0°-90°	575.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	575.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	1048	
5°	1027	95
15°	810	221
25°	377	174
35°	84	58
45°	20	16
55°	9	8
65°	2	3
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P328502

CATALOG NUMBER: L815SML05FL927MB

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	1048.4
2.5°	1045.2
5°	1026.6
7.5°	993.1
10°	948.9
12.5°	888.8
15°	809.7
17.5°	712.7
20°	603.6
22.5°	490.0
25°	377.4
27.5°	280.4
30°	200.3
32.5°	132.6
35°	83.6
37.5°	50.1
40°	33.1
42.5°	24.9
45°	19.7
47.5°	16.2
50°	13.5
52.5°	10.7
55°	8.6
57.5°	6.2
60°	4.8
62.5°	3.5
65°	2.4
67.5°	1.7
70°	1.0
72.5°	0.7
75°	0.3
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)