

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: INVUE

Report Number: P155439

Luminaire Tested: **VXS-E04-LED-E1-T3-7030**

Issue Date: 03/03/2020

Test Information

Test Method: LM-79-08
Report Number: P155439
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (P33672)
Test Lab: INNOVATION CENTER-P3
Issue Date: 03/03/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: INVUE
Catalog Number: VXS-E04-LED-E1-T3-7030
Description: VISION SITE SMALL LED LUMINAIRE
(4) LIGHTBARS WITH AccuLED OPTICS - TYPE 3
Light Source: (84) 3000K CCT, 70 CRI LEDs
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 11266.8 lumens
Efficiency: N/A
Efficacy: 115.9 lumens/watt
Luminous Opening: Rectangular (W 0.67' x L: 1' x H: 0')
IES Classification: Type III - Short - Semi-Cutoff
BUG Rating: B3 - U0 - G3

Input Watts (W): 97.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT




REPORT NUMBER: P155439

CATALOG NUMBER: VXS-E04-LED-E1-T3-7030

Iso-Footcandle Lines of Horizontal Illumination

× Max cd
 --- 1/2 Max cd




Based on 20 foot mounting height. Maximum calculated value = 3 fc
 Type III - Short - Semi-Cutoff

REPORT NUMBER: P155439

CATALOG NUMBER: VXS-E04-LED-E1-T3-7030

Luminous Intensity Polar Plot



REPORT NUMBER: P155439

CATALOG NUMBER: VXS-E04-LED-E1-T3-7030

FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	3890.8	0.0	3890.8
	% Fixture	34.5	0.0	34.5
Street Side	Lumens	7376.0	0.0	7376.0
	% Fixture	65.5	0.0	65.5
Total	Lumens	11266.8	0.0	11266.8
	% Fixture	100.0	0.0	100.0

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	116.3	1.0
10°-20°	343.2	3.0
20°-30°	589.8	5.2
30°-40°	957.7	8.5
40°-50°	1599.0	14.2
50°-60°	2517.8	22.3
60°-70°	3433.3	30.5
70°-80°	1486.2	13.2
80°-90°	223.5	2.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	11266.8	100.0
0°-180°	11266.8	100.0

Coefficient of Utilization



REPORT NUMBER: P155439


CATALOG NUMBER: VXS-E04-LED-E1-T3-7030

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	527.1	4.7			
FM	(30°-60°)	3146.4	27.9			
FH	(60°-80°)	3519.0	31.2			G2/5000
FVH	(80°-90°)	183.5	1.6			G2/225
BL	(0°-30°)	522.3	4.6	B2/1000		
BM	(30°-60°)	1928.0	17.1	B2/2500		
BH	(60°-80°)	1400.5	12.4	B3/2500		G3/2500
BVH	(80°-90°)	40.0	0.4			G1/100
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B3-U0-G3

Type III Short



REPORT NUMBER: P155439

CATALOG NUMBER: VXS-E04-LED-E1-T3-7030

CANDELA DISTRIBUTION (FULL):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
0°	1214.2	1214.2	1214.2	1214.2	1214.2	1214.2	1214.2	1214.2	1214.2	1214.2	1214.2
2.5°	1219.1	1223.9	1219.1	1220.2	1221.5	1220.2	1219.1	1219.1	1215.3	1217.8	1220.2
5°	1214.2	1217.8	1216.6	1217.8	1219.1	1217.8	1216.6	1217.8	1215.3	1216.6	1220.2
7.5°	1208.1	1206.8	1208.1	1210.5	1213.0	1213.0	1213.0	1214.2	1213.0	1213.0	1216.6
10°	1189.7	1191.0	1193.5	1197.1	1198.3	1202.0	1202.0	1205.6	1206.8	1209.3	1214.2
12.5°	1166.6	1167.9	1170.3	1172.7	1178.9	1184.9	1184.9	1193.5	1197.1	1203.2	1211.7
15°	1149.6	1150.8	1153.3	1155.6	1160.5	1166.6	1170.3	1180.0	1186.1	1197.1	1209.3
17.5°	1159.4	1158.1	1160.5	1161.8	1161.8	1166.6	1166.6	1174.0	1181.2	1191.0	1206.8
20°	1187.4	1187.4	1189.7	1189.7	1188.6	1191.0	1186.1	1186.1	1187.4	1192.2	1203.2
22.5°	1215.3	1214.2	1219.1	1221.5	1222.7	1226.3	1221.5	1220.2	1214.2	1210.5	1214.2
25°	1242.2	1240.9	1247.0	1250.7	1256.8	1260.4	1260.4	1260.4	1255.5	1249.4	1245.8
27.5°	1283.5	1283.5	1289.6	1293.3	1298.1	1305.5	1309.1	1309.1	1310.4	1301.9	1295.8
30°	1353.0	1354.2	1355.4	1360.3	1365.2	1367.6	1372.4	1376.2	1379.8	1374.9	1365.2
32.5°	1435.8	1428.5	1428.5	1435.8	1441.9	1449.2	1451.6	1456.5	1463.8	1460.1	1459.0
35°	1534.4	1532.0	1529.5	1532.0	1539.3	1547.9	1557.6	1566.1	1561.2	1568.5	1564.9
37.5°	1680.5	1683.0	1684.2	1684.2	1683.0	1685.4	1690.3	1698.9	1696.4	1698.9	1703.7
40°	1921.7	1913.2	1904.7	1905.9	1893.7	1896.2	1876.6	1885.2	1886.3	1877.8	1881.5
42.5°	2162.8	2167.7	2171.3	2181.0	2172.5	2167.7	2149.4	2149.4	2139.7	2131.2	2128.7
45°	2423.4	2433.2	2434.4	2453.9	2446.5	2462.4	2475.8	2472.1	2456.3	2455.1	2438.0
47.5°	2631.7	2647.5	2664.6	2687.7	2705.9	2741.2	2782.7	2803.4	2815.5	2825.3	2805.8
50°	2787.6	2794.8	2838.7	2875.2	2915.4	2973.9	3031.1	3105.4	3165.1	3193.1	3219.9
52.5°	2871.6	2889.8	2937.3	2994.6	3065.2	3152.8	3245.4	3363.5	3465.9	3534.1	3594.9
55°	2889.8	2908.1	2961.7	3034.7	3131.0	3249.1	3381.9	3542.6	3696.1	3827.6	3955.4
57.5°	2838.7	2859.4	2916.6	3000.6	3113.9	3257.6	3424.5	3635.1	3847.0	4060.1	4248.9
60°	2744.9	2770.5	2822.9	2905.7	3031.1	3193.1	3392.7	3657.1	3954.2	4280.5	4642.3
62.5°	2590.3	2617.1	2665.8	2757.1	2886.2	3065.2	3296.6	3625.4	4045.5	4559.5	5201.2
65°	2341.9	2354.0	2413.7	2506.2	2620.7	2818.0	3072.5	3469.5	4016.3	4731.2	5615.2
66°	2229.7	2250.5	2287.0	2361.3	2470.9	2656.1	2911.7	3314.8	3905.5	4671.5	5604.4
67.5°	2054.4	2070.3	2094.6	2144.6	2211.5	2347.9	2590.3	2971.4	3566.9	4369.4	5371.7
70°	1661.0	1668.4	1701.2	1718.3	1741.5	1786.5	1874.2	2093.4	2557.4	3311.2	4335.3
72.5°	1132.5	1153.3	1188.6	1237.3	1300.6	1361.5	1402.9	1430.9	1530.8	1975.2	2888.6
75°	830.6	852.4	897.5	962.1	1072.8	1199.5	1331.1	1391.9	1350.6	1293.3	1608.7
77.5°	482.3	511.5	549.2	611.3	713.7	881.7	1106.9	1306.7	1441.9	1450.4	1377.3
80°	203.4	207.0	230.2	261.9	325.2	443.3	618.7	906.0	1205.6	1407.8	1455.2
82.5°	46.3	57.2	73.1	86.4	105.9	146.1	216.8	360.5	651.5	1021.8	1332.2
85°	17.1	17.1	23.1	34.1	39.0	43.8	57.2	91.3	155.9	287.4	599.2
87.5°	0.0	1.2	2.5	2.5	4.9	6.1	9.7	13.4	12.2	11.0	36.6
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P155439

CATALOG NUMBER: VXS-E04-LED-E1-T3-7030

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	67.5°	70°	75°	80°	85°	90°	95°	100°
0°	1214.2	1214.2	1214.2	1214.2	1214.2	1214.2	1214.2	1214.2	1214.2	1214.2	1214.2
2.5°	1217.8	1216.6	1214.2	1214.2	1214.2	1214.2	1211.7	1213.0	1210.5	1211.7	1211.7
5°	1216.6	1216.6	1215.3	1213.0	1214.2	1214.2	1215.3	1213.0	1213.0	1214.2	1213.0
7.5°	1216.6	1215.3	1215.3	1215.3	1216.6	1215.3	1216.6	1216.6	1216.6	1217.8	1217.8
10°	1216.6	1216.6	1219.1	1220.2	1220.2	1221.5	1225.1	1225.1	1226.3	1227.6	1229.9
12.5°	1217.8	1222.7	1226.3	1229.9	1231.2	1233.7	1239.7	1239.7	1242.2	1245.8	1247.0
15°	1219.1	1226.3	1233.7	1236.1	1238.5	1243.4	1249.4	1251.9	1255.5	1259.2	1261.7
17.5°	1217.8	1227.6	1236.1	1239.7	1243.4	1249.4	1256.8	1259.2	1264.0	1268.9	1273.8
20°	1216.6	1229.9	1243.4	1248.3	1253.2	1261.7	1271.4	1277.5	1282.4	1289.6	1294.5
22.5°	1223.9	1239.7	1258.0	1265.3	1273.8	1284.8	1298.1	1305.5	1311.6	1318.9	1322.5
25°	1247.0	1259.2	1281.1	1293.3	1304.2	1322.5	1340.8	1349.3	1356.6	1362.7	1363.9
27.5°	1286.0	1289.6	1316.5	1332.2	1348.1	1377.3	1399.3	1405.4	1418.8	1423.6	1422.4
30°	1349.3	1343.2	1365.2	1389.5	1412.6	1452.8	1479.6	1495.4	1507.7	1507.7	1497.9
32.5°	1440.6	1430.9	1437.0	1465.0	1491.8	1550.3	1582.0	1602.6	1611.2	1608.7	1588.0
35°	1560.0	1553.9	1550.3	1572.2	1614.8	1683.0	1724.5	1735.3	1748.8	1746.3	1719.6
37.5°	1701.2	1696.4	1696.4	1722.0	1763.4	1864.5	1909.5	1916.8	1915.6	1896.2	1846.2
40°	1868.1	1865.7	1854.7	1869.3	1904.7	2036.2	2097.1	2106.8	2093.4	2061.8	2003.3
42.5°	2108.0	2093.4	2059.3	2067.9	2094.6	2222.5	2301.7	2328.4	2315.0	2283.4	2188.4
45°	2421.0	2405.2	2347.9	2340.6	2355.2	2467.3	2569.5	2575.6	2573.2	2533.1	2421.0
47.5°	2788.8	2764.5	2703.5	2684.0	2679.2	2782.7	2881.3	2891.1	2885.0	2825.3	2675.5
50°	3186.9	3151.7	3111.5	3098.1	3078.5	3152.8	3252.7	3254.0	3229.6	3146.8	3006.7
52.5°	3612.0	3599.8	3592.5	3579.1	3570.6	3635.1	3696.1	3659.5	3623.0	3536.5	3414.7
55°	4040.6	4090.6	4141.8	4146.6	4161.2	4230.7	4229.4	4129.5	4102.8	4055.2	3934.7
57.5°	4496.2	4681.2	4842.0	4891.9	4940.6	5069.7	5057.5	4958.9	4924.8	4866.3	4766.4
60°	5116.0	5615.2	6079.3	6190.1	6266.8	6421.5	6406.8	6254.6	6325.3	6320.4	6191.3
62.5°	5984.2	6814.8	7510.2	7680.6	7734.3	7751.3	7658.8	7494.3	7563.7	7641.7	7244.7
65°	6572.4	7549.1	8262.8	8394.3	8401.6	8198.2	7992.4	7798.8	7781.8	7714.7	7147.3
66°	6585.9	7585.7	8301.8	8429.6	8384.6	8106.9	7846.3	7651.4	7567.5	7420.1	6831.8
67.5°	6349.6	7357.9	8128.8	8264.0	8165.4	7772.0	7412.7	7161.9	6997.5	6758.8	6240.0
70°	5332.7	6332.5	7282.5	7534.5	7566.2	6979.2	6481.1	6186.4	5964.8	5637.2	5190.3
72.5°	3965.2	4868.8	5706.6	5947.8	6070.8	5601.9	5181.8	4957.6	4654.4	4309.8	3991.9
75°	2485.5	3123.6	3685.1	3854.3	3738.7	3375.8	3123.6	3029.8	2731.5	2525.7	2380.8
77.5°	1421.1	1620.9	1665.9	1601.5	1465.0	1121.6	797.6	590.7	512.6	567.5	625.9
80°	1387.0	1271.4	1013.2	891.4	807.4	555.3	326.3	224.0	186.3	191.2	207.0
82.5°	1502.8	1612.3	1327.4	1082.6	908.5	613.8	338.5	180.2	121.8	143.7	162.0
85°	976.7	1359.1	1223.9	1031.5	835.4	524.9	278.9	93.8	62.1	81.6	112.0
87.5°	98.7	108.4	92.5	125.4	93.8	43.8	22.0	13.4	12.2	14.6	22.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P155439

CATALOG NUMBER: VXS-E04-LED-E1-T3-7030

CANDELA DISTRIBUTION (continued):

	105°	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°
0°	1214.2	1214.2	1214.2	1214.2	1214.2	1214.2	1214.2	1214.2	1214.2	1214.2	1214.2
2.5°	1213.0	1213.0	1214.2	1215.3	1216.6	1217.8	1217.8	1217.8	1217.8	1220.2	1219.1
5°	1215.3	1217.8	1220.2	1221.5	1223.9	1223.9	1227.6	1226.3	1226.3	1229.9	1231.2
7.5°	1220.2	1223.9	1228.8	1227.6	1232.4	1231.2	1233.7	1233.7	1229.9	1231.2	1228.8
10°	1231.2	1236.1	1238.5	1234.8	1236.1	1231.2	1229.9	1223.9	1216.6	1213.0	1208.1
12.5°	1249.4	1254.3	1254.3	1248.3	1240.9	1229.9	1221.5	1208.1	1197.1	1191.0	1184.9
15°	1265.3	1270.2	1268.9	1259.2	1248.3	1231.2	1219.1	1203.2	1187.4	1177.6	1171.5
17.5°	1277.5	1279.9	1276.3	1262.9	1250.7	1234.8	1222.7	1205.6	1187.4	1175.1	1164.2
20°	1295.8	1293.3	1284.8	1267.8	1254.3	1239.7	1229.9	1215.3	1194.6	1178.9	1163.0
22.5°	1322.5	1312.7	1297.0	1278.7	1265.3	1251.9	1242.2	1226.3	1205.6	1186.1	1167.9
25°	1357.8	1338.3	1316.5	1297.0	1284.8	1270.2	1259.2	1242.2	1220.2	1198.3	1176.4
27.5°	1409.0	1374.9	1346.8	1329.8	1316.5	1298.1	1284.8	1262.9	1239.7	1214.2	1189.7
30°	1466.2	1420.0	1393.2	1379.8	1365.2	1345.7	1325.0	1297.0	1270.2	1242.2	1213.0
32.5°	1540.5	1484.5	1459.0	1445.5	1426.0	1401.7	1377.3	1345.7	1307.9	1271.4	1236.1
35°	1637.9	1580.7	1553.9	1533.2	1506.4	1474.7	1439.5	1396.8	1345.7	1297.0	1251.9
37.5°	1742.7	1680.5	1655.0	1633.1	1592.8	1551.5	1501.6	1439.5	1370.1	1305.5	1249.4
40°	1875.4	1818.1	1785.3	1747.6	1700.0	1628.2	1550.3	1460.1	1371.2	1292.1	1226.3
42.5°	2043.4	1986.2	1937.5	1877.8	1795.0	1684.2	1573.4	1456.5	1349.3	1259.2	1188.6
45°	2266.3	2196.9	2112.8	2008.2	1874.2	1719.6	1574.6	1433.4	1307.9	1208.1	1132.5
47.5°	2539.1	2433.2	2295.5	2119.0	1926.5	1729.3	1555.1	1387.0	1243.4	1135.0	1051.0
50°	2863.0	2696.2	2469.7	2210.3	1953.4	1714.6	1506.4	1317.6	1152.0	1036.4	936.5
52.5°	3233.3	2960.5	2626.8	2276.1	1952.1	1665.9	1423.6	1213.0	1032.7	903.6	808.6
55°	3668.0	3262.5	2788.8	2324.8	1918.0	1575.9	1297.0	1065.6	885.4	766.0	678.3
57.5°	4305.0	3752.0	3071.3	2400.3	1849.8	1437.0	1125.3	889.0	730.7	617.4	543.1
60°	5469.1	4569.2	3580.3	2552.5	1745.1	1233.7	924.4	700.2	567.5	476.2	426.2
62.5°	6345.9	5201.2	3855.5	2518.4	1534.4	982.8	685.6	510.3	417.7	355.6	323.9
65°	6220.5	5005.2	3562.1	2168.9	1203.2	693.0	455.4	347.0	287.4	258.1	239.9
66°	5936.8	4749.4	3307.6	1952.1	1040.0	576.1	375.1	291.1	247.3	226.5	214.3
67.5°	5398.5	4274.5	2852.1	1600.2	798.9	417.7	282.5	230.2	200.9	192.4	183.9
70°	4487.6	3408.6	2002.1	931.6	408.0	232.6	179.1	160.7	153.5	152.2	149.7
72.5°	3439.1	2412.4	1178.9	440.8	211.9	154.6	138.9	132.7	130.3	130.3	131.5
75°	2108.0	1355.4	521.2	215.5	148.6	130.3	123.0	120.5	119.4	120.5	119.4
77.5°	703.9	431.1	222.9	163.2	135.1	120.5	115.6	113.3	113.3	113.3	113.3
80°	215.5	187.6	170.5	151.0	127.9	114.5	107.2	105.9	107.2	108.4	104.8
82.5°	162.0	153.5	143.7	134.0	115.6	102.3	99.9	99.9	99.9	96.2	91.3
85°	119.4	118.1	97.4	91.3	85.3	85.3	85.3	85.3	81.6	75.5	70.7
87.5°	22.0	20.7	22.0	23.1	34.1	36.6	36.6	39.0	42.6	40.2	40.2
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P155439

CATALOG NUMBER: VXS-E04-LED-E1-T3-7030

CANDELA DISTRIBUTION (continued):

	160°	165°	170°	175°	180°
0°	1214.2	1214.2	1214.2	1214.2	1214.2
2.5°	1219.1	1217.8	1221.5	1219.1	1220.2
5°	1229.9	1228.8	1231.2	1228.8	1232.4
7.5°	1226.3	1223.9	1222.7	1223.9	1225.1
10°	1200.7	1198.3	1197.1	1195.9	1197.1
12.5°	1178.9	1174.0	1174.0	1171.5	1172.7
15°	1163.0	1159.4	1158.1	1155.6	1156.9
17.5°	1155.6	1149.6	1147.2	1144.8	1144.8
20°	1150.8	1143.5	1139.9	1137.4	1136.2
22.5°	1150.8	1139.9	1135.0	1132.5	1131.3
25°	1155.6	1142.3	1135.0	1131.3	1130.2
27.5°	1165.4	1148.4	1139.9	1135.0	1135.0
30°	1182.5	1160.5	1148.4	1142.3	1141.0
32.5°	1199.5	1170.3	1153.3	1145.9	1143.5
35°	1208.1	1170.3	1149.6	1137.4	1135.0
37.5°	1198.3	1154.5	1128.9	1110.7	1106.9
40°	1167.9	1121.6	1093.6	1076.6	1074.1
42.5°	1127.7	1082.6	1049.7	1037.6	1033.9
45°	1072.8	1019.3	986.4	969.3	970.6
47.5°	979.1	924.4	895.1	879.3	881.7
50°	868.3	814.7	789.1	772.1	775.8
52.5°	746.5	697.8	673.5	664.9	662.5
55°	618.7	580.9	563.8	554.1	550.5
57.5°	501.8	474.9	462.8	450.6	451.8
60°	395.8	382.4	378.8	365.4	364.1
62.5°	311.7	303.2	299.6	289.8	291.1
65°	236.3	233.8	236.3	230.2	232.6
66°	213.2	214.3	214.3	210.7	213.2
67.5°	183.9	186.3	189.9	186.3	188.8
70°	152.2	154.6	157.1	157.1	157.1
72.5°	132.7	135.1	136.4	136.4	136.4
75°	121.8	123.0	124.2	121.8	121.8
77.5°	114.5	114.5	112.0	110.8	109.6
80°	103.5	102.3	98.7	96.2	96.2
82.5°	86.4	84.0	81.6	77.9	77.9
85°	65.8	63.3	60.9	56.1	53.6
87.5°	34.1	35.3	34.1	28.0	24.4
90°	0.0	0.0	0.0	0.0	0.0

(END OF REPORT)