

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: LUMIERE

Report Number: P246985 (CONVERTED FROM TYPE C PHOTOMETRY)

Luminaire Tested: **206-8LED3036-12-XX-LSL**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P246985 (CONVERTED FROM TYPE C PHOTOMETRY)
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-1802-569-33)
Test Lab: INNOVATION CENTER(G2)
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: LUMIERE
Catalog Number: 206-8LED3036-12-XX-LSL
Description: CAMBRIA 203 LED LUMINAIRE, 8 WATT, 3000K CCT, 36 DEGREE WIDE OPTIC,
REGRESSED HOOD BLACK, LINEAR SPREAD LENS
Light Source: (1) SORAA 3000K 95 CRI LED
SM16-07-36D-930-03
Ballast/Driver: (1) CHROMA POWER SUPPLY IN0004

Summary


Lumens per Lamp:	N/A	NEMA Type:	5H x 4V
Luminaire Lumens:	270.7 lumens	Max Intensity:	485.8 candela
Efficiency:	N/A	Max Intensity Angle:	-12.5°H x 0°V
Efficacy:	34.7 lumens/watt		
Luminous Opening:	Circular (Dia: 0.17' x H: 0')		
Beam Angle (50%):	60.2°H x 33.3°V	Field Angle (10%):	79.2°H x 52.9°V
Beam Lumens:	186.3 lumens	Field Lumens:	255.7 lumens
Beam Efficiency:	68.8%	Field Efficiency:	94.5%
Input Watts (W):	7.8		
Input Voltage (V):	NR		
Input Current (Ain):	NR		
Voltage Rise (V):	NR		
Power Factor:	NR		
Total Harmonic Distortion (THDi):	NR		
Frequency (hertz):	60		
Stabilization Time:	NR		
Operation Time:	NR		
Ambient Temperature (°C):	NR		
Test Distance:	25 FT		



REPORT NUMBER: P246985 (CONVERTED FROM TYPE C PHOTOMETRY)

CATALOG NUMBER: 206-8LED3036-12-XX-LSL


Iso-Candela Plot






REPORT NUMBER: P246985 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 206-8LED3036-12-XX-LSL

Lumen Table




REPORT NUMBER: P246985 (CONVERTED FROM TYPE C PHOTOMETRY)
CATALOG NUMBER: 206-8LED3036-12-XX-LSL

Luminous Intensity Polar Plot



REPORT NUMBER: P246985 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 206-8LED3036-12-XX-LSL

Luminous Intensity Plot



Beam:
 H Angle: 60.2°
 V Angle: 33.3°
 Lumens: 186.3
 Efficiency: 68.8%

Field:
 H Angle: 79.2°
 V Angle: 52.9°
 Lumens: 255.7
 Efficiency: 94.5%

Spill:
 Lumens: 14.9
 Efficiency: 5.5%

— Vertical Distribution through -12.5-Deg
 - - Horizontal Distribution through 0-Deg



REPORT NUMBER: P246985 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 206-8LED3036-12-XX-LSL

FIELD
 BEAM

CANDELA DISTRIBUTION:

	-90°	-87.5°	-85°	-82.5°	-80°	-77.5°	-75°	-72.5°	-70°	-67.5°	-65°
90°	0	0	0	0	0	0	0	0	0	0	0
87.5°	0	0	0	0	0	0	0	0	0	0	0
85°	0	0	0	0	0	0	0	0	0	0	0
82.5°	0	0	0	0	0	0	0	0	0	0	0
80°	0	0	0	0	0	0	0	0	0	0	0
77.5°	0	0	0	0	0	0	0	0	0	0	0
75°	0	0	0	0	0	0	0	0	0	0	0
72.5°	0	0	0	0	0	0	0	0	0	0	0
70°	0	0	0	0	0	0	0	0	0	0	0
67.5°	0	0	0	0	0	0	0	0	0	0	0
65°	0	0	0	0	0	0	0	0	0	0	0
62.5°	0	0	0	0	0	0	0	0	0	0	0
60°	0	0	0	0	0	0	0	0	0	0	0
57.5°	0	0	0	0	0	0	0	0	0	0	0
55°	0	0	0	0	0	0	0	0	0	0	0
52.5°	0	0	0	0	0	0	0	0	0	0	0
50°	0	0	0	0	0	0	0	0	0	0	0
47.5°	0	0	0	0	0	0	0	0	0	0	0
45°	0	0	0	0	0	0	0	0	0	0	0
42.5°	0	0	0	0	0	0	0	0	0	0	0
40°	0	0	0	0	0	0	0	0	0	0	0
37.5°	0	0	0	0	0	0	0	0	0	0	0
35°	0	0	0	0	0	0	0	0	0	0	0
32.5°	0	0	0	0	0	0	0	0	0	0	0
30°	0	0	0	0	0	0	0	0	0	0	0
27.5°	0	0	0	0	0	0	0	0	0	0	0
25°	0	0	0	0	0	0	0	0	0	0	0
22.5°	0	0	0	0	0	0	0	0	0	0	0
20°	0	0	0	0	0	0	0	0	0	0	0
17.5°	0	0	0	0	0	0	0	0	0	0	0
15°	0	0	0	0	0	0	0	0	0	0	0
12.5°	0	0	0	0	0	0	0	0	0	0	0
10°	0	0	0	0	0	0	0	0	0	0	0
7.5°	0	0	0	0	0	0	0	0	0	0	0
5°	0	0	0	0	0	0	0	0	0	0	0
2.5°	0	0	0	0	0	0	0	0	0	0	0
0°	0	0	0	0	0	0	0	0	0	0	0
-2.5°	0	0	0	0	0	0	0	0	0	0	0
-5°	0	0	0	0	0	0	0	0	0	0	0
-7.5°	0	0	0	0	0	0	0	0	0	0	0
-10°	0	0	0	0	0	0	0	0	0	0	0
-12.5°	0	0	0	0	0	0	0	0	0	0	0
-15°	0	0	0	0	0	0	0	0	0	0	0
-17.5°	0	0	0	0	0	0	0	0	0	0	0
-20°	0	0	0	0	0	0	0	0	0	0	0



REPORT NUMBER: P246985 (CONVERTED FROM TYPE C PHOTOMETRY)

CATALOG NUMBER: 206-8LED3036-12-XX-LSL

CANDELA DISTRIBUTION (continued):

	-90°	-87.5°	-85°	-82.5°	-80°	-77.5°	-75°	-72.5°	-70°	-67.5°	-65°
-22.5°	0	0	0	0	0	0	0	0	0	0	0
-25°	0	0	0	0	0	0	0	0	0	0	0
-27.5°	0	0	0	0	0	0	0	0	0	0	0
-30°	0	0	0	0	0	0	0	0	0	0	0
-32.5°	0	0	0	0	0	0	0	0	0	0	0
-35°	0	0	0	0	0	0	0	0	0	0	0
-37.5°	0	0	0	0	0	0	0	0	0	0	0
-40°	0	0	0	0	0	0	0	0	0	0	0
-42.5°	0	0	0	0	0	0	0	0	0	0	0
-45°	0	0	0	0	0	0	0	0	0	0	0
-47.5°	0	0	0	0	0	0	0	0	0	0	0
-50°	0	0	0	0	0	0	0	0	0	0	0
-52.5°	0	0	0	0	0	0	0	0	0	0	0
-55°	0	0	0	0	0	0	0	0	0	0	0
-57.5°	0	0	0	0	0	0	0	0	0	0	0
-60°	0	0	0	0	0	0	0	0	0	0	0
-62.5°	0	0	0	0	0	0	0	0	0	0	0
-65°	0	0	0	0	0	0	0	0	0	0	0
-67.5°	0	0	0	0	0	0	0	0	0	0	0
-70°	0	0	0	0	0	0	0	0	0	0	0
-72.5°	0	0	0	0	0	0	0	0	0	0	0
-75°	0	0	0	0	0	0	0	0	0	0	0
-77.5°	0	0	0	0	0	0	0	0	0	0	0
-80°	0	0	0	0	0	0	0	0	0	0	0
-82.5°	0	0	0	0	0	0	0	0	0	0	0
-85°	0	0	0	0	0	0	0	0	0	0	0
-87.5°	0	0	0	0	0	0	0	0	0	0	0
-90°	0	0	0	0	0	0	0	0	0	0	0



REPORT NUMBER: P246985 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 206-8LED3036-12-XX-LSL

CANDELA DISTRIBUTION (continued):

	-62.5°	-60°	-57.5°	-55°	-52.5°	-50°	-47.5°	-45°	-42.5°	-40°	-37.5°
90°	0	0	0	0	0	0	0	0	0	0	0
87.5°	0	0	0	0	0	0	0	0	0	0	0
85°	0	0	0	0	0	0	0	0	0	0	0
82.5°	0	0	0	0	0	0	0	0	0	0	0
80°	0	0	0	0	0	0	0	0	0	0	0
77.5°	0	0	0	0	0	0	0	0	0	0	0
75°	0	0	0	0	0	0	0	0	0	0	0
72.5°	0	0	0	0	0	0	0	0	0	0	0
70°	0	0	0	0	0	0	0	0	0	0	0
67.5°	0	0	0	0	0	0	0	0	0	0	0
65°	0	0	0	0	0	0	0	0	0	0	0
62.5°	0	0	0	0	0	0	0	0	0	0	0
60°	0	0	0	0	0	0	0	0	0	0	0
57.5°	0	0	0	0	0	0	0	0	0	0	0
55°	0	0	0	0	0	0	0	0	0	0	0
52.5°	0	0	0	0	0	0	0	0	0	0	0
50°	0	0	0	0	0	0	0	0	0	1	1
47.5°	0	0	0	0	0	0	0	0	1	1	1
45°	0	0	0	0	0	0	0	1	1	1	1
42.5°	0	0	0	0	0	0	1	1	1	1	1
40°	0	0	0	0	0	1	1	1	1	1	1
37.5°	0	0	0	0	0	1	1	1	1	1	2
35°	0	0	0	0	1	1	1	1	1	2	2
32.5°	0	0	0	1	1	1	1	1	2	2	2
30°	0	0	0	1	1	1	1	2	2	2	4
27.5°	0	0	0	1	1	1	2	2	2	3	5
25°	0	0	1	1	1	1	2	2	3	5	8
22.5°	0	0	1	1	1	1	2	2	4	7	10
20°	0	0	1	1	1	2	2	3	6	9	16
17.5°	0	0	1	1	1	2	2	4	7	12	23
15°	0	0	1	1	1	2	3	5	9	15	30
12.5°	0	1	1	1	1	2	3	6	11	21	41
10°	0	1	1	1	2	2	3	7	12	27	50
7.5°	0	1	1	1	2	2	4	7	14	32	58
5°	0	1	1	1	2	2	4	8	16	37	64
2.5°	0	1	1	1	2	3	4	9	17	41	69
0°	0	1	1	1	2	3	4	9	18	44	72
-2.5°	0	1	1	1	2	3	4	9	17	41	69
-5°	0	1	1	1	2	2	4	8	16	37	64
-7.5°	0	1	1	1	2	2	4	7	14	32	58
-10°	0	1	1	1	2	2	3	7	12	27	50
-12.5°	0	1	1	1	1	2	3	6	11	21	41
-15°	0	0	1	1	1	2	3	5	9	15	30
-17.5°	0	0	1	1	1	2	2	4	7	12	23
-20°	0	0	1	1	1	2	2	3	6	9	16



REPORT NUMBER: P246985 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 206-8LED3036-12-XX-LSL

CANDELA DISTRIBUTION (continued):

	-62.5°	-60°	-57.5°	-55°	-52.5°	-50°	-47.5°	-45°	-42.5°	-40°	-37.5°
-22.5°	0	0	1	1	1	1	2	2	4	7	10
-25°	0	0	1	1	1	1	2	2	3	5	8
-27.5°	0	0	0	1	1	1	2	2	2	3	5
-30°	0	0	0	1	1	1	1	2	2	2	4
-32.5°	0	0	0	1	1	1	1	1	2	2	2
-35°	0	0	0	0	1	1	1	1	1	2	2
-37.5°	0	0	0	0	0	1	1	1	1	1	2
-40°	0	0	0	0	0	1	1	1	1	1	1
-42.5°	0	0	0	0	0	0	1	1	1	1	1
-45°	0	0	0	0	0	0	0	1	1	1	1
-47.5°	0	0	0	0	0	0	0	0	1	1	1
-50°	0	0	0	0	0	0	0	0	0	1	1
-52.5°	0	0	0	0	0	0	0	0	0	0	0
-55°	0	0	0	0	0	0	0	0	0	0	0
-57.5°	0	0	0	0	0	0	0	0	0	0	0
-60°	0	0	0	0	0	0	0	0	0	0	0
-62.5°	0	0	0	0	0	0	0	0	0	0	0
-65°	0	0	0	0	0	0	0	0	0	0	0
-67.5°	0	0	0	0	0	0	0	0	0	0	0
-70°	0	0	0	0	0	0	0	0	0	0	0
-72.5°	0	0	0	0	0	0	0	0	0	0	0
-75°	0	0	0	0	0	0	0	0	0	0	0
-77.5°	0	0	0	0	0	0	0	0	0	0	0
-80°	0	0	0	0	0	0	0	0	0	0	0
-82.5°	0	0	0	0	0	0	0	0	0	0	0
-85°	0	0	0	0	0	0	0	0	0	0	0
-87.5°	0	0	0	0	0	0	0	0	0	0	0
-90°	0	0	0	0	0	0	0	0	0	0	0



REPORT NUMBER: P246985 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 206-8LED3036-12-XX-LSL

CANDELA DISTRIBUTION (continued):

	-35°	-32.5°	-30°	-27.5°	-25°	-22.5°	-20°	-17.5°	-15°	-12.5°	-10°
90°	0	0	0	0	0	0	0	0	0	0	0
87.5°	0	0	0	0	0	0	0	0	0	0	0
85°	0	0	0	0	0	0	0	0	0	0	0
82.5°	0	0	0	0	0	0	0	0	0	0	0
80°	0	0	0	0	0	0	0	0	0	0	0
77.5°	0	0	0	0	0	0	0	0	0	0	0
75°	0	0	0	0	0	0	0	0	0	0	0
72.5°	0	0	0	0	0	0	0	0	0	0	0
70°	0	0	0	0	0	0	0	0	0	0	0
67.5°	0	0	0	0	0	0	0	0	0	0	0
65°	0	0	0	0	0	0	0	0	0	0	0
62.5°	0	0	0	0	0	0	0	0	0	0	0
60°	0	0	0	0	0	0	0	0	0	1	1
57.5°	0	0	0	0	1	1	1	1	1	1	1
55°	0	1	1	1	1	1	1	1	1	1	1
52.5°	1	1	1	1	1	1	1	1	1	1	1
50°	1	1	1	1	1	1	1	1	1	1	1
47.5°	1	1	1	1	1	1	1	1	1	1	2
45°	1	1	1	1	1	1	2	2	2	2	2
42.5°	1	1	2	2	2	2	2	3	3	3	3
40°	1	2	2	2	3	3	3	4	4	4	4
37.5°	2	2	2	3	4	4	5	5	5	5	5
35°	2	3	4	4	5	6	7	7	7	7	7
32.5°	3	5	5	7	8	10	11	13	13	11	12
30°	5	7	9	10	13	17	21	23	23	19	19
27.5°	8	11	15	20	23	29	37	41	42	37	31
25°	11	17	27	36	43	51	63	70	70	65	54
22.5°	18	30	45	59	75	87	98	106	109	106	94
20°	27	46	69	92	111	127	141	153	159	158	149
17.5°	42	69	99	128	151	173	192	208	219	221	215
15°	56	94	133	165	192	221	246	267	281	284	282
12.5°	72	116	162	201	238	270	300	320	335	345	342
10°	88	137	184	226	273	319	349	370	386	393	390
7.5°	103	155	204	249	297	345	383	416	431	432	428
5°	116	170	221	268	315	364	403	436	457	463	457
2.5°	126	182	235	281	329	378	418	451	470	475	473
0°	133	190	246	291	339	387	429	462	482	486	483
-2.5°	126	182	235	281	329	378	418	451	470	475	473
-5°	116	170	221	268	315	364	403	436	457	463	457
-7.5°	103	155	204	249	297	345	383	416	431	432	428
-10°	88	137	184	226	273	319	349	370	386	393	390
-12.5°	72	116	162	201	238	270	300	320	335	345	342
-15°	56	94	133	165	192	221	246	267	281	284	282
-17.5°	42	69	99	128	151	173	192	208	219	221	215
-20°	27	46	69	92	111	127	141	153	159	158	149



REPORT NUMBER: P246985 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 206-8LED3036-12-XX-LSL

CANDELA DISTRIBUTION (continued):

	-35°	-32.5°	-30°	-27.5°	-25°	-22.5°	-20°	-17.5°	-15°	-12.5°	-10°
-22.5°	18	30	45	59	75	87	98	106	109	106	94
-25°	11	17	27	36	43	51	63	70	70	65	54
-27.5°	8	11	15	20	23	29	37	41	42	37	31
-30°	5	7	9	10	13	17	21	23	23	19	19
-32.5°	3	5	5	7	8	10	11	13	13	11	12
-35°	2	3	4	4	5	6	7	7	7	7	7
-37.5°	2	2	2	3	4	4	5	5	5	5	5
-40°	1	2	2	2	3	3	3	4	4	4	4
-42.5°	1	1	2	2	2	2	2	3	3	3	3
-45°	1	1	1	1	1	1	2	2	2	2	2
-47.5°	1	1	1	1	1	1	1	1	1	1	2
-50°	1	1	1	1	1	1	1	1	1	1	1
-52.5°	1	1	1	1	1	1	1	1	1	1	1
-55°	0	1	1	1	1	1	1	1	1	1	1
-57.5°	0	0	0	0	1	1	1	1	1	1	1
-60°	0	0	0	0	0	0	0	0	0	1	1
-62.5°	0	0	0	0	0	0	0	0	0	0	0
-65°	0	0	0	0	0	0	0	0	0	0	0
-67.5°	0	0	0	0	0	0	0	0	0	0	0
-70°	0	0	0	0	0	0	0	0	0	0	0
-72.5°	0	0	0	0	0	0	0	0	0	0	0
-75°	0	0	0	0	0	0	0	0	0	0	0
-77.5°	0	0	0	0	0	0	0	0	0	0	0
-80°	0	0	0	0	0	0	0	0	0	0	0
-82.5°	0	0	0	0	0	0	0	0	0	0	0
-85°	0	0	0	0	0	0	0	0	0	0	0
-87.5°	0	0	0	0	0	0	0	0	0	0	0
-90°	0	0	0	0	0	0	0	0	0	0	0



REPORT NUMBER: P246985 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 206-8LED3036-12-XX-LSL

CANDELA DISTRIBUTION (continued):

	-7.5°	-5°	-2.5°	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°
90°	0	0	0	0	0	0	0	0	0	0	0
87.5°	0	0	0	0	0	0	0	0	0	0	0
85°	0	0	0	0	0	0	0	0	0	0	0
82.5°	0	0	0	0	0	0	0	0	0	0	0
80°	0	0	0	0	0	0	0	0	0	0	0
77.5°	0	0	0	0	0	0	0	0	0	0	0
75°	0	0	0	0	0	0	0	0	0	0	0
72.5°	0	0	0	0	0	0	0	0	0	0	0
70°	0	0	0	0	0	0	0	0	0	0	0
67.5°	0	0	0	0	0	0	0	0	0	0	0
65°	0	0	0	0	0	0	0	0	0	0	0
62.5°	0	0	0	0	0	0	0	0	0	0	0
60°	1	1	1	1	1	1	1	1	1	0	0
57.5°	1	1	1	1	1	1	1	1	1	1	1
55°	1	1	1	1	1	1	1	1	1	1	1
52.5°	1	1	1	1	1	1	1	1	1	1	1
50°	1	1	1	1	1	1	1	1	1	1	1
47.5°	2	2	2	2	2	2	2	2	1	1	1
45°	2	2	2	2	2	2	2	2	2	2	2
42.5°	3	3	3	3	3	3	3	3	3	3	3
40°	4	4	4	4	4	4	4	4	4	4	4
37.5°	5	5	5	4	5	5	5	5	5	5	5
35°	8	8	8	7	8	8	8	7	7	7	7
32.5°	12	11	11	10	11	11	12	12	11	13	13
30°	20	19	18	16	18	19	20	19	19	23	23
27.5°	34	35	33	30	33	35	34	31	37	42	41
25°	58	59	57	51	57	59	58	54	65	70	70
22.5°	91	93	91	84	91	93	91	94	106	109	106
20°	141	145	142	131	142	145	141	149	158	159	153
17.5°	204	205	200	188	200	205	204	215	221	219	208
15°	273	263	258	245	258	263	273	282	284	281	267
12.5°	331	316	310	295	310	316	331	342	345	335	320
10°	381	367	356	341	356	367	381	390	393	386	370
7.5°	418	407	393	379	393	407	418	428	432	431	416
5°	447	436	418	405	418	436	447	457	463	457	436
2.5°	466	451	431	418	431	451	466	473	475	470	451
0°	474	456	437	426	437	456	474	483	486	482	462
-2.5°	466	451	431	418	431	451	466	473	475	470	451
-5°	447	436	418	405	418	436	447	457	463	457	436
-7.5°	418	407	393	379	393	407	418	428	432	431	416
-10°	381	367	356	341	356	367	381	390	393	386	370
-12.5°	331	316	310	295	310	316	331	342	345	335	320
-15°	273	263	258	245	258	263	273	282	284	281	267
-17.5°	204	205	200	188	200	205	204	215	221	219	208
-20°	141	145	142	131	142	145	141	149	158	159	153



REPORT NUMBER: P246985 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 206-8LED3036-12-XX-LSL

CANDELA DISTRIBUTION (continued):

	-7.5°	-5°	-2.5°	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°
-22.5°	91	93	91	84	91	93	91	94	106	109	106
-25°	58	59	57	51	57	59	58	54	65	70	70
-27.5°	34	35	33	30	33	35	34	31	37	42	41
-30°	20	19	18	16	18	19	20	19	19	23	23
-32.5°	12	11	11	10	11	11	12	12	11	13	13
-35°	8	8	8	7	8	8	8	7	7	7	7
-37.5°	5	5	5	4	5	5	5	5	5	5	5
-40°	4	4	4	4	4	4	4	4	4	4	4
-42.5°	3	3	3	3	3	3	3	3	3	3	3
-45°	2	2	2	2	2	2	2	2	2	2	2
-47.5°	2	2	2	2	2	2	2	2	1	1	1
-50°	1	1	1	1	1	1	1	1	1	1	1
-52.5°	1	1	1	1	1	1	1	1	1	1	1
-55°	1	1	1	1	1	1	1	1	1	1	1
-57.5°	1	1	1	1	1	1	1	1	1	1	1
-60°	1	1	1	1	1	1	1	1	1	0	0
-62.5°	0	0	0	0	0	0	0	0	0	0	0
-65°	0	0	0	0	0	0	0	0	0	0	0
-67.5°	0	0	0	0	0	0	0	0	0	0	0
-70°	0	0	0	0	0	0	0	0	0	0	0
-72.5°	0	0	0	0	0	0	0	0	0	0	0
-75°	0	0	0	0	0	0	0	0	0	0	0
-77.5°	0	0	0	0	0	0	0	0	0	0	0
-80°	0	0	0	0	0	0	0	0	0	0	0
-82.5°	0	0	0	0	0	0	0	0	0	0	0
-85°	0	0	0	0	0	0	0	0	0	0	0
-87.5°	0	0	0	0	0	0	0	0	0	0	0
-90°	0	0	0	0	0	0	0	0	0	0	0



REPORT NUMBER: P246985 (CONVERTED FROM TYPE C PHOTOMETRY)

CATALOG NUMBER: 206-8LED3036-12-XX-LSL

CANDELA DISTRIBUTION (continued):

	20°	22.5°	25°	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°
90°	0	0	0	0	0	0	0	0	0	0	0
87.5°	0	0	0	0	0	0	0	0	0	0	0
85°	0	0	0	0	0	0	0	0	0	0	0
82.5°	0	0	0	0	0	0	0	0	0	0	0
80°	0	0	0	0	0	0	0	0	0	0	0
77.5°	0	0	0	0	0	0	0	0	0	0	0
75°	0	0	0	0	0	0	0	0	0	0	0
72.5°	0	0	0	0	0	0	0	0	0	0	0
70°	0	0	0	0	0	0	0	0	0	0	0
67.5°	0	0	0	0	0	0	0	0	0	0	0
65°	0	0	0	0	0	0	0	0	0	0	0
62.5°	0	0	0	0	0	0	0	0	0	0	0
60°	0	0	0	0	0	0	0	0	0	0	0
57.5°	1	1	1	0	0	0	0	0	0	0	0
55°	1	1	1	1	1	1	0	0	0	0	0
52.5°	1	1	1	1	1	1	1	0	0	0	0
50°	1	1	1	1	1	1	1	1	1	0	0
47.5°	1	1	1	1	1	1	1	1	1	1	0
45°	2	1	1	1	1	1	1	1	1	1	1
42.5°	2	2	2	2	2	1	1	1	1	1	1
40°	3	3	3	2	2	2	1	1	1	1	1
37.5°	5	4	4	3	2	2	2	2	1	1	1
35°	7	6	5	4	4	3	2	2	2	1	1
32.5°	11	10	8	7	5	5	3	2	2	2	1
30°	21	17	13	10	9	7	5	4	2	2	2
27.5°	37	29	23	20	15	11	8	5	3	2	2
25°	63	51	43	36	27	17	11	8	5	3	2
22.5°	98	87	75	59	45	30	18	10	7	4	2
20°	141	127	111	92	69	46	27	16	9	6	3
17.5°	192	173	151	128	99	69	42	23	12	7	4
15°	246	221	192	165	133	94	56	30	15	9	5
12.5°	300	270	238	201	162	116	72	41	21	11	6
10°	349	319	273	226	184	137	88	50	27	12	7
7.5°	383	345	297	249	204	155	103	58	32	14	7
5°	403	364	315	268	221	170	116	64	37	16	8
2.5°	418	378	329	281	235	182	126	69	41	17	9
0°	429	387	339	291	246	190	133	72	44	18	9
-2.5°	418	378	329	281	235	182	126	69	41	17	9
-5°	403	364	315	268	221	170	116	64	37	16	8
-7.5°	383	345	297	249	204	155	103	58	32	14	7
-10°	349	319	273	226	184	137	88	50	27	12	7
-12.5°	300	270	238	201	162	116	72	41	21	11	6
-15°	246	221	192	165	133	94	56	30	15	9	5
-17.5°	192	173	151	128	99	69	42	23	12	7	4
-20°	141	127	111	92	69	46	27	16	9	6	3



REPORT NUMBER: P246985 (CONVERTED FROM TYPE C PHOTOMETRY)

CATALOG NUMBER: 206-8LED3036-12-XX-LSL

CANDELA DISTRIBUTION (continued):

	20°	22.5°	25°	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°
-22.5°	98	87	75	59	45	30	18	10	7	4	2
-25°	63	51	43	36	27	17	11	8	5	3	2
-27.5°	37	29	23	20	15	11	8	5	3	2	2
-30°	21	17	13	10	9	7	5	4	2	2	2
-32.5°	11	10	8	7	5	5	3	2	2	2	1
-35°	7	6	5	4	4	3	2	2	2	1	1
-37.5°	5	4	4	3	2	2	2	2	1	1	1
-40°	3	3	3	2	2	2	1	1	1	1	1
-42.5°	2	2	2	2	2	1	1	1	1	1	1
-45°	2	1	1	1	1	1	1	1	1	1	1
-47.5°	1	1	1	1	1	1	1	1	1	1	0
-50°	1	1	1	1	1	1	1	1	1	0	0
-52.5°	1	1	1	1	1	1	1	0	0	0	0
-55°	1	1	1	1	1	1	0	0	0	0	0
-57.5°	1	1	1	0	0	0	0	0	0	0	0
-60°	0	0	0	0	0	0	0	0	0	0	0
-62.5°	0	0	0	0	0	0	0	0	0	0	0
-65°	0	0	0	0	0	0	0	0	0	0	0
-67.5°	0	0	0	0	0	0	0	0	0	0	0
-70°	0	0	0	0	0	0	0	0	0	0	0
-72.5°	0	0	0	0	0	0	0	0	0	0	0
-75°	0	0	0	0	0	0	0	0	0	0	0
-77.5°	0	0	0	0	0	0	0	0	0	0	0
-80°	0	0	0	0	0	0	0	0	0	0	0
-82.5°	0	0	0	0	0	0	0	0	0	0	0
-85°	0	0	0	0	0	0	0	0	0	0	0
-87.5°	0	0	0	0	0	0	0	0	0	0	0
-90°	0	0	0	0	0	0	0	0	0	0	0



REPORT NUMBER: P246985 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 206-8LED3036-12-XX-LSL

CANDELA DISTRIBUTION (continued):

	47.5°	50°	52.5°	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°
90°	0	0	0	0	0	0	0	0	0	0	0
87.5°	0	0	0	0	0	0	0	0	0	0	0
85°	0	0	0	0	0	0	0	0	0	0	0
82.5°	0	0	0	0	0	0	0	0	0	0	0
80°	0	0	0	0	0	0	0	0	0	0	0
77.5°	0	0	0	0	0	0	0	0	0	0	0
75°	0	0	0	0	0	0	0	0	0	0	0
72.5°	0	0	0	0	0	0	0	0	0	0	0
70°	0	0	0	0	0	0	0	0	0	0	0
67.5°	0	0	0	0	0	0	0	0	0	0	0
65°	0	0	0	0	0	0	0	0	0	0	0
62.5°	0	0	0	0	0	0	0	0	0	0	0
60°	0	0	0	0	0	0	0	0	0	0	0
57.5°	0	0	0	0	0	0	0	0	0	0	0
55°	0	0	0	0	0	0	0	0	0	0	0
52.5°	0	0	0	0	0	0	0	0	0	0	0
50°	0	0	0	0	0	0	0	0	0	0	0
47.5°	0	0	0	0	0	0	0	0	0	0	0
45°	0	0	0	0	0	0	0	0	0	0	0
42.5°	1	0	0	0	0	0	0	0	0	0	0
40°	1	1	0	0	0	0	0	0	0	0	0
37.5°	1	1	0	0	0	0	0	0	0	0	0
35°	1	1	1	0	0	0	0	0	0	0	0
32.5°	1	1	1	1	0	0	0	0	0	0	0
30°	1	1	1	1	0	0	0	0	0	0	0
27.5°	2	1	1	1	0	0	0	0	0	0	0
25°	2	1	1	1	1	0	0	0	0	0	0
22.5°	2	1	1	1	1	0	0	0	0	0	0
20°	2	2	1	1	1	0	0	0	0	0	0
17.5°	2	2	1	1	1	0	0	0	0	0	0
15°	3	2	1	1	1	0	0	0	0	0	0
12.5°	3	2	1	1	1	1	0	0	0	0	0
10°	3	2	2	1	1	1	0	0	0	0	0
7.5°	4	2	2	1	1	1	0	0	0	0	0
5°	4	2	2	1	1	1	0	0	0	0	0
2.5°	4	3	2	1	1	1	0	0	0	0	0
0°	4	3	2	1	1	1	0	0	0	0	0
-2.5°	4	3	2	1	1	1	0	0	0	0	0
-5°	4	2	2	1	1	1	0	0	0	0	0
-7.5°	4	2	2	1	1	1	0	0	0	0	0
-10°	3	2	2	1	1	1	0	0	0	0	0
-12.5°	3	2	1	1	1	1	0	0	0	0	0
-15°	3	2	1	1	1	0	0	0	0	0	0
-17.5°	2	2	1	1	1	0	0	0	0	0	0
-20°	2	2	1	1	1	0	0	0	0	0	0



REPORT NUMBER: P246985 (CONVERTED FROM TYPE C PHOTOMETRY)

CATALOG NUMBER: 206-8LED3036-12-XX-LSL

CANDELA DISTRIBUTION (continued):

	47.5°	50°	52.5°	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°
-22.5°	2	1	1	1	1	0	0	0	0	0	0
-25°	2	1	1	1	1	0	0	0	0	0	0
-27.5°	2	1	1	1	0	0	0	0	0	0	0
-30°	1	1	1	1	0	0	0	0	0	0	0
-32.5°	1	1	1	1	0	0	0	0	0	0	0
-35°	1	1	1	0	0	0	0	0	0	0	0
-37.5°	1	1	0	0	0	0	0	0	0	0	0
-40°	1	1	0	0	0	0	0	0	0	0	0
-42.5°	1	0	0	0	0	0	0	0	0	0	0
-45°	0	0	0	0	0	0	0	0	0	0	0
-47.5°	0	0	0	0	0	0	0	0	0	0	0
-50°	0	0	0	0	0	0	0	0	0	0	0
-52.5°	0	0	0	0	0	0	0	0	0	0	0
-55°	0	0	0	0	0	0	0	0	0	0	0
-57.5°	0	0	0	0	0	0	0	0	0	0	0
-60°	0	0	0	0	0	0	0	0	0	0	0
-62.5°	0	0	0	0	0	0	0	0	0	0	0
-65°	0	0	0	0	0	0	0	0	0	0	0
-67.5°	0	0	0	0	0	0	0	0	0	0	0
-70°	0	0	0	0	0	0	0	0	0	0	0
-72.5°	0	0	0	0	0	0	0	0	0	0	0
-75°	0	0	0	0	0	0	0	0	0	0	0
-77.5°	0	0	0	0	0	0	0	0	0	0	0
-80°	0	0	0	0	0	0	0	0	0	0	0
-82.5°	0	0	0	0	0	0	0	0	0	0	0
-85°	0	0	0	0	0	0	0	0	0	0	0
-87.5°	0	0	0	0	0	0	0	0	0	0	0
-90°	0	0	0	0	0	0	0	0	0	0	0



REPORT NUMBER: P246985 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 206-8LED3036-12-XX-LSL

CANDELA DISTRIBUTION (continued):

	75°	77.5°	80°	82.5°	85°	87.5°	90°
90°	0	0	0	0	0	0	0
87.5°	0	0	0	0	0	0	0
85°	0	0	0	0	0	0	0
82.5°	0	0	0	0	0	0	0
80°	0	0	0	0	0	0	0
77.5°	0	0	0	0	0	0	0
75°	0	0	0	0	0	0	0
72.5°	0	0	0	0	0	0	0
70°	0	0	0	0	0	0	0
67.5°	0	0	0	0	0	0	0
65°	0	0	0	0	0	0	0
62.5°	0	0	0	0	0	0	0
60°	0	0	0	0	0	0	0
57.5°	0	0	0	0	0	0	0
55°	0	0	0	0	0	0	0
52.5°	0	0	0	0	0	0	0
50°	0	0	0	0	0	0	0
47.5°	0	0	0	0	0	0	0
45°	0	0	0	0	0	0	0
42.5°	0	0	0	0	0	0	0
40°	0	0	0	0	0	0	0
37.5°	0	0	0	0	0	0	0
35°	0	0	0	0	0	0	0
32.5°	0	0	0	0	0	0	0
30°	0	0	0	0	0	0	0
27.5°	0	0	0	0	0	0	0
25°	0	0	0	0	0	0	0
22.5°	0	0	0	0	0	0	0
20°	0	0	0	0	0	0	0
17.5°	0	0	0	0	0	0	0
15°	0	0	0	0	0	0	0
12.5°	0	0	0	0	0	0	0
10°	0	0	0	0	0	0	0
7.5°	0	0	0	0	0	0	0
5°	0	0	0	0	0	0	0
2.5°	0	0	0	0	0	0	0
0°	0	0	0	0	0	0	0
-2.5°	0	0	0	0	0	0	0
-5°	0	0	0	0	0	0	0
-7.5°	0	0	0	0	0	0	0
-10°	0	0	0	0	0	0	0
-12.5°	0	0	0	0	0	0	0
-15°	0	0	0	0	0	0	0
-17.5°	0	0	0	0	0	0	0
-20°	0	0	0	0	0	0	0



REPORT NUMBER: P246985 (CONVERTED FROM TYPE C PHOTOMETRY)

CATALOG NUMBER: 206-8LED3036-12-XX-LSL

CANDELA DISTRIBUTION (continued):

	75°	77.5°	80°	82.5°	85°	87.5°	90°
-22.5°	0	0	0	0	0	0	0
-25°	0	0	0	0	0	0	0
-27.5°	0	0	0	0	0	0	0
-30°	0	0	0	0	0	0	0
-32.5°	0	0	0	0	0	0	0
-35°	0	0	0	0	0	0	0
-37.5°	0	0	0	0	0	0	0
-40°	0	0	0	0	0	0	0
-42.5°	0	0	0	0	0	0	0
-45°	0	0	0	0	0	0	0
-47.5°	0	0	0	0	0	0	0
-50°	0	0	0	0	0	0	0
-52.5°	0	0	0	0	0	0	0
-55°	0	0	0	0	0	0	0
-57.5°	0	0	0	0	0	0	0
-60°	0	0	0	0	0	0	0
-62.5°	0	0	0	0	0	0	0
-65°	0	0	0	0	0	0	0
-67.5°	0	0	0	0	0	0	0
-70°	0	0	0	0	0	0	0
-72.5°	0	0	0	0	0	0	0
-75°	0	0	0	0	0	0	0
-77.5°	0	0	0	0	0	0	0
-80°	0	0	0	0	0	0	0
-82.5°	0	0	0	0	0	0	0
-85°	0	0	0	0	0	0	0
-87.5°	0	0	0	0	0	0	0
-90°	0	0	0	0	0	0	0

(END OF REPORT)