

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: LUMIERE

Report Number: G2-1802-569-33 (CONVERTED FROM TYPE C PHOTOMETRY)

Luminaire Tested: **206-8LED4036-12-XX-LSL**

Test Date: 04/06/18

**Test Information**

Test Method: LM-79-08  
Report Number: G2-1802-569-33 (CONVERTED FROM TYPE C PHOTOMETRY)  
Test Lab: INNOVATION CENTER(G2)  
Test Date: 04/06/18  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: LUMIERE  
Catalog Number: 206-8LED4036-12-XX-LSL  
Description: CAMBRIA 203 LED LUMINAIRE, 8 WATT, 4000K CCT, 36 DEGREE WIDE OPTIC,  
REGRESSED HOOD BLACK, LINEAR SPREAD LENS  
Light Source: (1) SORAA 4000K 95 CRI LED  
SM16-07-36D-940-03  
Ballast/Driver: (1) CHROMA POWER SUPPLY IN0004


**Summary**

Lumens per Lamp:	N/A	NEMA Type:	5H x 4V
Luminaire Lumens:	305.3 lumens	Max Intensity:	548 candela
Efficiency:	N/A	Max Intensity Angle:	-12.5°H x 0°V
Efficacy:	39.1 lumens/watt		
Luminous Opening:	Circular (Dia: 0.17' x H: 0')		
Beam Angle (50%):	60.2°H x 33.3°V	Field Angle (10%):	79.2°H x 52.9°V
Beam Lumens:	210.1 lumens	Field Lumens:	288.5 lumens
Beam Efficiency:	68.8%	Field Efficiency:	94.5%
Input Watts (W):	7.8		
Input Voltage (V):	12.0		
Input Current (Ain):	0.681		
Voltage Rise (V):	NR		
Power Factor:	0.9907		
Total Harmonic Distortion (THDi):	27.5%		
Frequency (hertz):	60		
Stabilization Time:	0.5 HR		
Operation Time:	3 HR		
Ambient Temperature (°C):	24.9		
Test Distance:	25 FT		



REPORT NUMBER: G2-1802-569-33 (CONVERTED FROM TYPE C PHOTOMETRY)  
CATALOG NUMBER: 206-8LED4036-12-XX-LSL


### Iso-Candela Plot






REPORT NUMBER: G2-1802-569-33 (CONVERTED FROM TYPE C PHOTOMETRY)  
 CATALOG NUMBER: 206-8LED4036-12-XX-LSL

### Lumen Table




REPORT NUMBER: G2-1802-569-33 (CONVERTED FROM TYPE C PHOTOMETRY)  
CATALOG NUMBER: 206-8LED4036-12-XX-LSL

### Luminous Intensity Polar Plot



REPORT NUMBER: G2-1802-569-33 (CONVERTED FROM TYPE C PHOTOMETRY)  
 CATALOG NUMBER: 206-8LED4036-12-XX-LSL

### Luminous Intensity Plot



**Beam:**  
 H Angle: 60.2°  
 V Angle: 33.3°  
 Lumens: 210.1  
 Efficiency: 68.8%

**Field:**  
 H Angle: 79.2°  
 V Angle: 52.9°  
 Lumens: 288.5  
 Efficiency: 94.5%

**Spill:**  
 Lumens: 16.8  
 Efficiency: 5.5%

— Vertical Distribution through -12.5-Deg  
 - - - Horizontal Distribution through 0-Deg



REPORT NUMBER: G2-1802-569-33 (CONVERTED FROM TYPE C PHOTOMETRY)  
 CATALOG NUMBER: 206-8LED4036-12-XX-LSL

FIELD  
 BEAM

**CANDELA DISTRIBUTION:**

	-90°	-87.5°	-85°	-82.5°	-80°	-77.5°	-75°	-72.5°	-70°	-67.5°	-65°
90°	0	0	0	0	0	0	0	0	0	0	0
87.5°	0	0	0	0	0	0	0	0	0	0	0
85°	0	0	0	0	0	0	0	0	0	0	0
82.5°	0	0	0	0	0	0	0	0	0	0	0
80°	0	0	0	0	0	0	0	0	0	0	0
77.5°	0	0	0	0	0	0	0	0	0	0	0
75°	0	0	0	0	0	0	0	0	0	0	0
72.5°	0	0	0	0	0	0	0	0	0	0	0
70°	0	0	0	0	0	0	0	0	0	0	0
67.5°	0	0	0	0	0	0	0	0	0	0	0
65°	0	0	0	0	0	0	0	0	0	0	0
62.5°	0	0	0	0	0	0	0	0	0	0	0
60°	0	0	0	0	0	0	0	0	0	0	0
57.5°	0	0	0	0	0	0	0	0	0	0	0
55°	0	0	0	0	0	0	0	0	0	0	0
52.5°	0	0	0	0	0	0	0	0	0	0	0
50°	0	0	0	0	0	0	0	0	0	0	0
47.5°	0	0	0	0	0	0	0	0	0	0	0
45°	0	0	0	0	0	0	0	0	0	0	0
42.5°	0	0	0	0	0	0	0	0	0	0	0
40°	0	0	0	0	0	0	0	0	0	0	0
37.5°	0	0	0	0	0	0	0	0	0	0	0
35°	0	0	0	0	0	0	0	0	0	0	0
32.5°	0	0	0	0	0	0	0	0	0	0	0
30°	0	0	0	0	0	0	0	0	0	0	0
27.5°	0	0	0	0	0	0	0	0	0	0	0
25°	0	0	0	0	0	0	0	0	0	0	0
22.5°	0	0	0	0	0	0	0	0	0	0	0
20°	0	0	0	0	0	0	0	0	0	0	0
17.5°	0	0	0	0	0	0	0	0	0	0	0
15°	0	0	0	0	0	0	0	0	0	0	0
12.5°	0	0	0	0	0	0	0	0	0	0	0
10°	0	0	0	0	0	0	0	0	0	0	0
7.5°	0	0	0	0	0	0	0	0	0	0	0
5°	0	0	0	0	0	0	0	0	0	0	0
2.5°	0	0	0	0	0	0	0	0	0	0	0
0°	0	0	0	0	0	0	0	0	0	0	0
-2.5°	0	0	0	0	0	0	0	0	0	0	0
-5°	0	0	0	0	0	0	0	0	0	0	0
-7.5°	0	0	0	0	0	0	0	0	0	0	0
-10°	0	0	0	0	0	0	0	0	0	0	0
-12.5°	0	0	0	0	0	0	0	0	0	0	0
-15°	0	0	0	0	0	0	0	0	0	0	0
-17.5°	0	0	0	0	0	0	0	0	0	0	0
-20°	0	0	0	0	0	0	0	0	0	0	0



REPORT NUMBER: G2-1802-569-33 (CONVERTED FROM TYPE C PHOTOMETRY)  
 CATALOG NUMBER: 206-8LED4036-12-XX-LSL

**CANDELA DISTRIBUTION (continued):**

	-90°	-87.5°	-85°	-82.5°	-80°	-77.5°	-75°	-72.5°	-70°	-67.5°	-65°
-22.5°	0	0	0	0	0	0	0	0	0	0	0
-25°	0	0	0	0	0	0	0	0	0	0	0
-27.5°	0	0	0	0	0	0	0	0	0	0	0
-30°	0	0	0	0	0	0	0	0	0	0	0
-32.5°	0	0	0	0	0	0	0	0	0	0	0
-35°	0	0	0	0	0	0	0	0	0	0	0
-37.5°	0	0	0	0	0	0	0	0	0	0	0
-40°	0	0	0	0	0	0	0	0	0	0	0
-42.5°	0	0	0	0	0	0	0	0	0	0	0
-45°	0	0	0	0	0	0	0	0	0	0	0
-47.5°	0	0	0	0	0	0	0	0	0	0	0
-50°	0	0	0	0	0	0	0	0	0	0	0
-52.5°	0	0	0	0	0	0	0	0	0	0	0
-55°	0	0	0	0	0	0	0	0	0	0	0
-57.5°	0	0	0	0	0	0	0	0	0	0	0
-60°	0	0	0	0	0	0	0	0	0	0	0
-62.5°	0	0	0	0	0	0	0	0	0	0	0
-65°	0	0	0	0	0	0	0	0	0	0	0
-67.5°	0	0	0	0	0	0	0	0	0	0	0
-70°	0	0	0	0	0	0	0	0	0	0	0
-72.5°	0	0	0	0	0	0	0	0	0	0	0
-75°	0	0	0	0	0	0	0	0	0	0	0
-77.5°	0	0	0	0	0	0	0	0	0	0	0
-80°	0	0	0	0	0	0	0	0	0	0	0
-82.5°	0	0	0	0	0	0	0	0	0	0	0
-85°	0	0	0	0	0	0	0	0	0	0	0
-87.5°	0	0	0	0	0	0	0	0	0	0	0
-90°	0	0	0	0	0	0	0	0	0	0	0





REPORT NUMBER: G2-1802-569-33 (CONVERTED FROM TYPE C PHOTOMETRY)  
 CATALOG NUMBER: 206-8LED4036-12-XX-LSL

**CANDELA DISTRIBUTION (continued):**

	-62.5°	-60°	-57.5°	-55°	-52.5°	-50°	-47.5°	-45°	-42.5°	-40°	-37.5°
90°	0	0	0	0	0	0	0	0	0	0	0
87.5°	0	0	0	0	0	0	0	0	0	0	0
85°	0	0	0	0	0	0	0	0	0	0	0
82.5°	0	0	0	0	0	0	0	0	0	0	0
80°	0	0	0	0	0	0	0	0	0	0	0
77.5°	0	0	0	0	0	0	0	0	0	0	0
75°	0	0	0	0	0	0	0	0	0	0	0
72.5°	0	0	0	0	0	0	0	0	0	0	0
70°	0	0	0	0	0	0	0	0	0	0	0
67.5°	0	0	0	0	0	0	0	0	0	0	0
65°	0	0	0	0	0	0	0	0	0	0	0
62.5°	0	0	0	0	0	0	0	0	0	0	0
60°	0	0	0	0	0	0	0	0	0	0	0
57.5°	0	0	0	0	0	0	0	0	0	0	0
55°	0	0	0	0	0	0	0	0	0	0	0
52.5°	0	0	0	0	0	0	0	0	0	0	1
50°	0	0	0	0	0	0	0	0	0	1	1
47.5°	0	0	0	0	0	0	0	0	1	1	1
45°	0	0	0	0	0	0	0	1	1	1	1
42.5°	0	0	0	0	0	0	1	1	1	1	1
40°	0	0	0	0	0	1	1	1	1	1	1
37.5°	0	0	0	0	1	1	1	1	1	1	2
35°	0	0	0	0	1	1	1	1	1	2	2
32.5°	0	0	0	1	1	1	1	1	2	2	3
30°	0	0	0	1	1	1	1	2	2	3	4
27.5°	0	0	0	1	1	1	2	2	3	4	6
25°	0	0	1	1	1	1	2	2	3	6	9
22.5°	0	0	1	1	1	2	2	3	5	8	12
20°	0	0	1	1	1	2	2	3	6	11	18
17.5°	0	0	1	1	1	2	2	4	8	13	25
15°	0	1	1	1	1	2	3	5	10	17	34
12.5°	0	1	1	1	2	2	4	7	12	24	46
10°	0	1	1	1	2	2	4	8	14	30	57
7.5°	0	1	1	1	2	3	4	8	16	36	66
5°	0	1	1	1	2	3	5	9	18	42	72
2.5°	0	1	1	1	2	3	5	10	19	47	78
0°	0	1	1	1	2	3	5	10	20	50	81
-2.5°	0	1	1	1	2	3	5	10	19	47	78
-5°	0	1	1	1	2	3	5	9	18	42	72
-7.5°	0	1	1	1	2	3	4	8	16	36	66
-10°	0	1	1	1	2	2	4	8	14	30	57
-12.5°	0	1	1	1	2	2	4	7	12	24	46
-15°	0	1	1	1	1	2	3	5	10	17	34
-17.5°	0	0	1	1	1	2	2	4	8	13	25
-20°	0	0	1	1	1	2	2	3	6	11	18



REPORT NUMBER: G2-1802-569-33 (CONVERTED FROM TYPE C PHOTOMETRY)  
 CATALOG NUMBER: 206-8LED4036-12-XX-LSL

**CANDELA DISTRIBUTION (continued):**

	-62.5°	-60°	-57.5°	-55°	-52.5°	-50°	-47.5°	-45°	-42.5°	-40°	-37.5°
-22.5°	0	0	1	1	1	2	2	3	5	8	12
-25°	0	0	1	1	1	1	2	2	3	6	9
-27.5°	0	0	0	1	1	1	2	2	3	4	6
-30°	0	0	0	1	1	1	1	2	2	3	4
-32.5°	0	0	0	1	1	1	1	1	2	2	3
-35°	0	0	0	0	1	1	1	1	1	2	2
-37.5°	0	0	0	0	1	1	1	1	1	1	2
-40°	0	0	0	0	0	1	1	1	1	1	1
-42.5°	0	0	0	0	0	0	1	1	1	1	1
-45°	0	0	0	0	0	0	0	1	1	1	1
-47.5°	0	0	0	0	0	0	0	0	1	1	1
-50°	0	0	0	0	0	0	0	0	0	1	1
-52.5°	0	0	0	0	0	0	0	0	0	0	1
-55°	0	0	0	0	0	0	0	0	0	0	0
-57.5°	0	0	0	0	0	0	0	0	0	0	0
-60°	0	0	0	0	0	0	0	0	0	0	0
-62.5°	0	0	0	0	0	0	0	0	0	0	0
-65°	0	0	0	0	0	0	0	0	0	0	0
-67.5°	0	0	0	0	0	0	0	0	0	0	0
-70°	0	0	0	0	0	0	0	0	0	0	0
-72.5°	0	0	0	0	0	0	0	0	0	0	0
-75°	0	0	0	0	0	0	0	0	0	0	0
-77.5°	0	0	0	0	0	0	0	0	0	0	0
-80°	0	0	0	0	0	0	0	0	0	0	0
-82.5°	0	0	0	0	0	0	0	0	0	0	0
-85°	0	0	0	0	0	0	0	0	0	0	0
-87.5°	0	0	0	0	0	0	0	0	0	0	0
-90°	0	0	0	0	0	0	0	0	0	0	0



REPORT NUMBER: G2-1802-569-33 (CONVERTED FROM TYPE C PHOTOMETRY)  
 CATALOG NUMBER: 206-8LED4036-12-XX-LSL

**CANDELA DISTRIBUTION (continued):**

	-35°	-32.5°	-30°	-27.5°	-25°	-22.5°	-20°	-17.5°	-15°	-12.5°	-10°
90°	0	0	0	0	0	0	0	0	0	0	0
87.5°	0	0	0	0	0	0	0	0	0	0	0
85°	0	0	0	0	0	0	0	0	0	0	0
82.5°	0	0	0	0	0	0	0	0	0	0	0
80°	0	0	0	0	0	0	0	0	0	0	0
77.5°	0	0	0	0	0	0	0	0	0	0	0
75°	0	0	0	0	0	0	0	0	0	0	0
72.5°	0	0	0	0	0	0	0	0	0	0	0
70°	0	0	0	0	0	0	0	0	0	0	0
67.5°	0	0	0	0	0	0	0	0	0	0	0
65°	0	0	0	0	0	0	0	0	0	0	0
62.5°	0	0	0	0	0	0	0	0	0	0	0
60°	0	0	0	0	0	0	0	0	1	1	1
57.5°	0	0	0	0	1	1	1	1	1	1	1
55°	0	1	1	1	1	1	1	1	1	1	1
52.5°	1	1	1	1	1	1	1	1	1	1	1
50°	1	1	1	1	1	1	1	1	1	1	1
47.5°	1	1	1	1	1	1	1	1	1	2	2
45°	1	1	1	1	1	2	2	2	2	2	2
42.5°	1	1	2	2	2	2	3	3	3	3	3
40°	2	2	2	2	3	3	4	4	4	4	4
37.5°	2	2	3	4	4	5	5	6	5	5	6
35°	2	3	4	5	6	7	8	8	8	8	8
32.5°	4	5	6	7	9	11	13	15	14	12	13
30°	6	8	10	12	15	19	23	26	26	21	21
27.5°	9	12	17	22	26	33	42	46	48	41	35
25°	13	20	30	41	49	58	71	79	79	74	61
22.5°	20	34	50	67	84	98	110	120	123	119	106
20°	31	51	78	104	126	144	159	173	180	178	168
17.5°	48	78	111	144	170	195	217	235	247	249	242
15°	63	106	150	186	217	249	277	301	316	320	318
12.5°	81	130	183	227	268	304	339	361	378	389	385
10°	100	154	207	255	307	360	393	417	436	444	440
7.5°	116	175	230	281	335	389	432	469	486	487	483
5°	131	192	249	302	356	410	454	491	516	522	516
2.5°	142	205	265	317	371	426	472	509	530	536	534
0°	150	214	277	328	382	437	484	521	544	548	545
-2.5°	142	205	265	317	371	426	472	509	530	536	534
-5°	131	192	249	302	356	410	454	491	516	522	516
-7.5°	116	175	230	281	335	389	432	469	486	487	483
-10°	100	154	207	255	307	360	393	417	436	444	440
-12.5°	81	130	183	227	268	304	339	361	378	389	385
-15°	63	106	150	186	217	249	277	301	316	320	318
-17.5°	48	78	111	144	170	195	217	235	247	249	242
-20°	31	51	78	104	126	144	159	173	180	178	168



REPORT NUMBER: G2-1802-569-33 (CONVERTED FROM TYPE C PHOTOMETRY)  
 CATALOG NUMBER: 206-8LED4036-12-XX-LSL

**CANDELA DISTRIBUTION (continued):**

	-35°	-32.5°	-30°	-27.5°	-25°	-22.5°	-20°	-17.5°	-15°	-12.5°	-10°
-22.5°	20	34	50	67	84	98	110	120	123	119	106
-25°	13	20	30	41	49	58	71	79	79	74	61
-27.5°	9	12	17	22	26	33	42	46	48	41	35
-30°	6	8	10	12	15	19	23	26	26	21	21
-32.5°	4	5	6	7	9	11	13	15	14	12	13
-35°	2	3	4	5	6	7	8	8	8	8	8
-37.5°	2	2	3	4	4	5	5	6	5	5	6
-40°	2	2	2	2	3	3	4	4	4	4	4
-42.5°	1	1	2	2	2	2	3	3	3	3	3
-45°	1	1	1	1	1	2	2	2	2	2	2
-47.5°	1	1	1	1	1	1	1	1	1	2	2
-50°	1	1	1	1	1	1	1	1	1	1	1
-52.5°	1	1	1	1	1	1	1	1	1	1	1
-55°	0	1	1	1	1	1	1	1	1	1	1
-57.5°	0	0	0	0	1	1	1	1	1	1	1
-60°	0	0	0	0	0	0	0	0	1	1	1
-62.5°	0	0	0	0	0	0	0	0	0	0	0
-65°	0	0	0	0	0	0	0	0	0	0	0
-67.5°	0	0	0	0	0	0	0	0	0	0	0
-70°	0	0	0	0	0	0	0	0	0	0	0
-72.5°	0	0	0	0	0	0	0	0	0	0	0
-75°	0	0	0	0	0	0	0	0	0	0	0
-77.5°	0	0	0	0	0	0	0	0	0	0	0
-80°	0	0	0	0	0	0	0	0	0	0	0
-82.5°	0	0	0	0	0	0	0	0	0	0	0
-85°	0	0	0	0	0	0	0	0	0	0	0
-87.5°	0	0	0	0	0	0	0	0	0	0	0
-90°	0	0	0	0	0	0	0	0	0	0	0



REPORT NUMBER: G2-1802-569-33 (CONVERTED FROM TYPE C PHOTOMETRY)  
 CATALOG NUMBER: 206-8LED4036-12-XX-LSL

**CANDELA DISTRIBUTION (continued):**

	-7.5°	-5°	-2.5°	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°
90°	0	0	0	0	0	0	0	0	0	0	0
87.5°	0	0	0	0	0	0	0	0	0	0	0
85°	0	0	0	0	0	0	0	0	0	0	0
82.5°	0	0	0	0	0	0	0	0	0	0	0
80°	0	0	0	0	0	0	0	0	0	0	0
77.5°	0	0	0	0	0	0	0	0	0	0	0
75°	0	0	0	0	0	0	0	0	0	0	0
72.5°	0	0	0	0	0	0	0	0	0	0	0
70°	0	0	0	0	0	0	0	0	0	0	0
67.5°	0	0	0	0	0	0	0	0	0	0	0
65°	0	0	0	0	0	0	0	0	0	0	0
62.5°	0	0	0	0	0	0	0	0	0	0	0
60°	1	1	1	1	1	1	1	1	1	1	0
57.5°	1	1	1	1	1	1	1	1	1	1	1
55°	1	1	1	1	1	1	1	1	1	1	1
52.5°	1	1	1	1	1	1	1	1	1	1	1
50°	1	1	1	1	1	1	1	1	1	1	1
47.5°	2	2	2	2	2	2	2	2	2	1	1
45°	2	2	2	2	2	2	2	2	2	2	2
42.5°	3	3	3	3	3	3	3	3	3	3	3
40°	4	4	4	4	4	4	4	4	4	4	4
37.5°	6	6	5	5	5	6	6	6	5	5	6
35°	9	9	8	8	8	9	9	8	8	8	8
32.5°	13	13	12	11	12	13	13	13	12	14	15
30°	22	22	20	18	20	22	22	21	21	26	26
27.5°	38	39	38	34	38	39	38	35	41	48	46
25°	65	66	64	58	64	66	65	61	74	79	79
22.5°	103	105	103	95	103	105	103	106	119	123	120
20°	159	164	160	148	160	164	159	168	178	180	173
17.5°	230	231	226	212	226	231	230	242	249	247	235
15°	308	297	291	276	291	297	308	318	320	316	301
12.5°	373	357	350	333	350	357	373	385	389	378	361
10°	430	414	402	385	402	414	430	440	444	436	417
7.5°	472	459	443	428	443	459	472	483	487	486	469
5°	504	492	471	457	471	492	504	516	522	516	491
2.5°	525	508	486	471	486	508	525	534	536	530	509
0°	534	514	492	480	492	514	534	545	548	544	521
-2.5°	525	508	486	471	486	508	525	534	536	530	509
-5°	504	492	471	457	471	492	504	516	522	516	491
-7.5°	472	459	443	428	443	459	472	483	487	486	469
-10°	430	414	402	385	402	414	430	440	444	436	417
-12.5°	373	357	350	333	350	357	373	385	389	378	361
-15°	308	297	291	276	291	297	308	318	320	316	301
-17.5°	230	231	226	212	226	231	230	242	249	247	235
-20°	159	164	160	148	160	164	159	168	178	180	173



REPORT NUMBER: G2-1802-569-33 (CONVERTED FROM TYPE C PHOTOMETRY)  
 CATALOG NUMBER: 206-8LED4036-12-XX-LSL

**CANDELA DISTRIBUTION (continued):**

	-7.5°	-5°	-2.5°	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°
-22.5°	103	105	103	95	103	105	103	106	119	123	120
-25°	65	66	64	58	64	66	65	61	74	79	79
-27.5°	38	39	38	34	38	39	38	35	41	48	46
-30°	22	22	20	18	20	22	22	21	21	26	26
-32.5°	13	13	12	11	12	13	13	13	12	14	15
-35°	9	9	8	8	8	9	9	8	8	8	8
-37.5°	6	6	5	5	5	6	6	6	5	5	6
-40°	4	4	4	4	4	4	4	4	4	4	4
-42.5°	3	3	3	3	3	3	3	3	3	3	3
-45°	2	2	2	2	2	2	2	2	2	2	2
-47.5°	2	2	2	2	2	2	2	2	2	1	1
-50°	1	1	1	1	1	1	1	1	1	1	1
-52.5°	1	1	1	1	1	1	1	1	1	1	1
-55°	1	1	1	1	1	1	1	1	1	1	1
-57.5°	1	1	1	1	1	1	1	1	1	1	1
-60°	1	1	1	1	1	1	1	1	1	1	0
-62.5°	0	0	0	0	0	0	0	0	0	0	0
-65°	0	0	0	0	0	0	0	0	0	0	0
-67.5°	0	0	0	0	0	0	0	0	0	0	0
-70°	0	0	0	0	0	0	0	0	0	0	0
-72.5°	0	0	0	0	0	0	0	0	0	0	0
-75°	0	0	0	0	0	0	0	0	0	0	0
-77.5°	0	0	0	0	0	0	0	0	0	0	0
-80°	0	0	0	0	0	0	0	0	0	0	0
-82.5°	0	0	0	0	0	0	0	0	0	0	0
-85°	0	0	0	0	0	0	0	0	0	0	0
-87.5°	0	0	0	0	0	0	0	0	0	0	0
-90°	0	0	0	0	0	0	0	0	0	0	0



REPORT NUMBER: G2-1802-569-33 (CONVERTED FROM TYPE C PHOTOMETRY)  
 CATALOG NUMBER: 206-8LED4036-12-XX-LSL

**CANDELA DISTRIBUTION (continued):**

	20°	22.5°	25°	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°
90°	0	0	0	0	0	0	0	0	0	0	0
87.5°	0	0	0	0	0	0	0	0	0	0	0
85°	0	0	0	0	0	0	0	0	0	0	0
82.5°	0	0	0	0	0	0	0	0	0	0	0
80°	0	0	0	0	0	0	0	0	0	0	0
77.5°	0	0	0	0	0	0	0	0	0	0	0
75°	0	0	0	0	0	0	0	0	0	0	0
72.5°	0	0	0	0	0	0	0	0	0	0	0
70°	0	0	0	0	0	0	0	0	0	0	0
67.5°	0	0	0	0	0	0	0	0	0	0	0
65°	0	0	0	0	0	0	0	0	0	0	0
62.5°	0	0	0	0	0	0	0	0	0	0	0
60°	0	0	0	0	0	0	0	0	0	0	0
57.5°	1	1	1	0	0	0	0	0	0	0	0
55°	1	1	1	1	1	1	0	0	0	0	0
52.5°	1	1	1	1	1	1	1	1	0	0	0
50°	1	1	1	1	1	1	1	1	1	0	0
47.5°	1	1	1	1	1	1	1	1	1	1	0
45°	2	2	1	1	1	1	1	1	1	1	1
42.5°	3	2	2	2	2	1	1	1	1	1	1
40°	4	3	3	2	2	2	2	1	1	1	1
37.5°	5	5	4	4	3	2	2	2	1	1	1
35°	8	7	6	5	4	3	2	2	2	1	1
32.5°	13	11	9	7	6	5	4	3	2	2	1
30°	23	19	15	12	10	8	6	4	3	2	2
27.5°	42	33	26	22	17	12	9	6	4	3	2
25°	71	58	49	41	30	20	13	9	6	3	2
22.5°	110	98	84	67	50	34	20	12	8	5	3
20°	159	144	126	104	78	51	31	18	11	6	3
17.5°	217	195	170	144	111	78	48	25	13	8	4
15°	277	249	217	186	150	106	63	34	17	10	5
12.5°	339	304	268	227	183	130	81	46	24	12	7
10°	393	360	307	255	207	154	100	57	30	14	8
7.5°	432	389	335	281	230	175	116	66	36	16	8
5°	454	410	356	302	249	192	131	72	42	18	9
2.5°	472	426	371	317	265	205	142	78	47	19	10
0°	484	437	382	328	277	214	150	81	50	20	10
-2.5°	472	426	371	317	265	205	142	78	47	19	10
-5°	454	410	356	302	249	192	131	72	42	18	9
-7.5°	432	389	335	281	230	175	116	66	36	16	8
-10°	393	360	307	255	207	154	100	57	30	14	8
-12.5°	339	304	268	227	183	130	81	46	24	12	7
-15°	277	249	217	186	150	106	63	34	17	10	5
-17.5°	217	195	170	144	111	78	48	25	13	8	4
-20°	159	144	126	104	78	51	31	18	11	6	3



REPORT NUMBER: G2-1802-569-33 (CONVERTED FROM TYPE C PHOTOMETRY)  
 CATALOG NUMBER: 206-8LED4036-12-XX-LSL

**CANDELA DISTRIBUTION (continued):**

	20°	22.5°	25°	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°
-22.5°	110	98	84	67	50	34	20	12	8	5	3
-25°	71	58	49	41	30	20	13	9	6	3	2
-27.5°	42	33	26	22	17	12	9	6	4	3	2
-30°	23	19	15	12	10	8	6	4	3	2	2
-32.5°	13	11	9	7	6	5	4	3	2	2	1
-35°	8	7	6	5	4	3	2	2	2	1	1
-37.5°	5	5	4	4	3	2	2	2	1	1	1
-40°	4	3	3	2	2	2	2	1	1	1	1
-42.5°	3	2	2	2	2	1	1	1	1	1	1
-45°	2	2	1	1	1	1	1	1	1	1	1
-47.5°	1	1	1	1	1	1	1	1	1	1	0
-50°	1	1	1	1	1	1	1	1	1	0	0
-52.5°	1	1	1	1	1	1	1	1	0	0	0
-55°	1	1	1	1	1	1	0	0	0	0	0
-57.5°	1	1	1	0	0	0	0	0	0	0	0
-60°	0	0	0	0	0	0	0	0	0	0	0
-62.5°	0	0	0	0	0	0	0	0	0	0	0
-65°	0	0	0	0	0	0	0	0	0	0	0
-67.5°	0	0	0	0	0	0	0	0	0	0	0
-70°	0	0	0	0	0	0	0	0	0	0	0
-72.5°	0	0	0	0	0	0	0	0	0	0	0
-75°	0	0	0	0	0	0	0	0	0	0	0
-77.5°	0	0	0	0	0	0	0	0	0	0	0
-80°	0	0	0	0	0	0	0	0	0	0	0
-82.5°	0	0	0	0	0	0	0	0	0	0	0
-85°	0	0	0	0	0	0	0	0	0	0	0
-87.5°	0	0	0	0	0	0	0	0	0	0	0
-90°	0	0	0	0	0	0	0	0	0	0	0





REPORT NUMBER: G2-1802-569-33 (CONVERTED FROM TYPE C PHOTOMETRY)  
 CATALOG NUMBER: 206-8LED4036-12-XX-LSL

**CANDELA DISTRIBUTION (continued):**

	47.5°	50°	52.5°	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°
90°	0	0	0	0	0	0	0	0	0	0	0
87.5°	0	0	0	0	0	0	0	0	0	0	0
85°	0	0	0	0	0	0	0	0	0	0	0
82.5°	0	0	0	0	0	0	0	0	0	0	0
80°	0	0	0	0	0	0	0	0	0	0	0
77.5°	0	0	0	0	0	0	0	0	0	0	0
75°	0	0	0	0	0	0	0	0	0	0	0
72.5°	0	0	0	0	0	0	0	0	0	0	0
70°	0	0	0	0	0	0	0	0	0	0	0
67.5°	0	0	0	0	0	0	0	0	0	0	0
65°	0	0	0	0	0	0	0	0	0	0	0
62.5°	0	0	0	0	0	0	0	0	0	0	0
60°	0	0	0	0	0	0	0	0	0	0	0
57.5°	0	0	0	0	0	0	0	0	0	0	0
55°	0	0	0	0	0	0	0	0	0	0	0
52.5°	0	0	0	0	0	0	0	0	0	0	0
50°	0	0	0	0	0	0	0	0	0	0	0
47.5°	0	0	0	0	0	0	0	0	0	0	0
45°	0	0	0	0	0	0	0	0	0	0	0
42.5°	1	0	0	0	0	0	0	0	0	0	0
40°	1	1	0	0	0	0	0	0	0	0	0
37.5°	1	1	1	0	0	0	0	0	0	0	0
35°	1	1	1	0	0	0	0	0	0	0	0
32.5°	1	1	1	1	0	0	0	0	0	0	0
30°	1	1	1	1	0	0	0	0	0	0	0
27.5°	2	1	1	1	0	0	0	0	0	0	0
25°	2	1	1	1	1	0	0	0	0	0	0
22.5°	2	2	1	1	1	0	0	0	0	0	0
20°	2	2	1	1	1	0	0	0	0	0	0
17.5°	2	2	1	1	1	0	0	0	0	0	0
15°	3	2	1	1	1	1	0	0	0	0	0
12.5°	4	2	2	1	1	1	0	0	0	0	0
10°	4	2	2	1	1	1	0	0	0	0	0
7.5°	4	3	2	1	1	1	0	0	0	0	0
5°	5	3	2	1	1	1	0	0	0	0	0
2.5°	5	3	2	1	1	1	0	0	0	0	0
0°	5	3	2	1	1	1	0	0	0	0	0
-2.5°	5	3	2	1	1	1	0	0	0	0	0
-5°	5	3	2	1	1	1	0	0	0	0	0
-7.5°	4	3	2	1	1	1	0	0	0	0	0
-10°	4	2	2	1	1	1	0	0	0	0	0
-12.5°	4	2	2	1	1	1	0	0	0	0	0
-15°	3	2	1	1	1	1	0	0	0	0	0
-17.5°	2	2	1	1	1	0	0	0	0	0	0
-20°	2	2	1	1	1	0	0	0	0	0	0



REPORT NUMBER: G2-1802-569-33 (CONVERTED FROM TYPE C PHOTOMETRY)  
 CATALOG NUMBER: 206-8LED4036-12-XX-LSL

**CANDELA DISTRIBUTION (continued):**

	47.5°	50°	52.5°	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°
-22.5°	2	2	1	1	1	0	0	0	0	0	0
-25°	2	1	1	1	1	0	0	0	0	0	0
-27.5°	2	1	1	1	0	0	0	0	0	0	0
-30°	1	1	1	1	0	0	0	0	0	0	0
-32.5°	1	1	1	1	0	0	0	0	0	0	0
-35°	1	1	1	0	0	0	0	0	0	0	0
-37.5°	1	1	1	0	0	0	0	0	0	0	0
-40°	1	1	0	0	0	0	0	0	0	0	0
-42.5°	1	0	0	0	0	0	0	0	0	0	0
-45°	0	0	0	0	0	0	0	0	0	0	0
-47.5°	0	0	0	0	0	0	0	0	0	0	0
-50°	0	0	0	0	0	0	0	0	0	0	0
-52.5°	0	0	0	0	0	0	0	0	0	0	0
-55°	0	0	0	0	0	0	0	0	0	0	0
-57.5°	0	0	0	0	0	0	0	0	0	0	0
-60°	0	0	0	0	0	0	0	0	0	0	0
-62.5°	0	0	0	0	0	0	0	0	0	0	0
-65°	0	0	0	0	0	0	0	0	0	0	0
-67.5°	0	0	0	0	0	0	0	0	0	0	0
-70°	0	0	0	0	0	0	0	0	0	0	0
-72.5°	0	0	0	0	0	0	0	0	0	0	0
-75°	0	0	0	0	0	0	0	0	0	0	0
-77.5°	0	0	0	0	0	0	0	0	0	0	0
-80°	0	0	0	0	0	0	0	0	0	0	0
-82.5°	0	0	0	0	0	0	0	0	0	0	0
-85°	0	0	0	0	0	0	0	0	0	0	0
-87.5°	0	0	0	0	0	0	0	0	0	0	0
-90°	0	0	0	0	0	0	0	0	0	0	0



REPORT NUMBER: G2-1802-569-33 (CONVERTED FROM TYPE C PHOTOMETRY)  
 CATALOG NUMBER: 206-8LED4036-12-XX-LSL

**CANDELA DISTRIBUTION (continued):**

	75°	77.5°	80°	82.5°	85°	87.5°	90°
90°	0	0	0	0	0	0	0
87.5°	0	0	0	0	0	0	0
85°	0	0	0	0	0	0	0
82.5°	0	0	0	0	0	0	0
80°	0	0	0	0	0	0	0
77.5°	0	0	0	0	0	0	0
75°	0	0	0	0	0	0	0
72.5°	0	0	0	0	0	0	0
70°	0	0	0	0	0	0	0
67.5°	0	0	0	0	0	0	0
65°	0	0	0	0	0	0	0
62.5°	0	0	0	0	0	0	0
60°	0	0	0	0	0	0	0
57.5°	0	0	0	0	0	0	0
55°	0	0	0	0	0	0	0
52.5°	0	0	0	0	0	0	0
50°	0	0	0	0	0	0	0
47.5°	0	0	0	0	0	0	0
45°	0	0	0	0	0	0	0
42.5°	0	0	0	0	0	0	0
40°	0	0	0	0	0	0	0
37.5°	0	0	0	0	0	0	0
35°	0	0	0	0	0	0	0
32.5°	0	0	0	0	0	0	0
30°	0	0	0	0	0	0	0
27.5°	0	0	0	0	0	0	0
25°	0	0	0	0	0	0	0
22.5°	0	0	0	0	0	0	0
20°	0	0	0	0	0	0	0
17.5°	0	0	0	0	0	0	0
15°	0	0	0	0	0	0	0
12.5°	0	0	0	0	0	0	0
10°	0	0	0	0	0	0	0
7.5°	0	0	0	0	0	0	0
5°	0	0	0	0	0	0	0
2.5°	0	0	0	0	0	0	0
0°	0	0	0	0	0	0	0
-2.5°	0	0	0	0	0	0	0
-5°	0	0	0	0	0	0	0
-7.5°	0	0	0	0	0	0	0
-10°	0	0	0	0	0	0	0
-12.5°	0	0	0	0	0	0	0
-15°	0	0	0	0	0	0	0
-17.5°	0	0	0	0	0	0	0
-20°	0	0	0	0	0	0	0



REPORT NUMBER: G2-1802-569-33 (CONVERTED FROM TYPE C PHOTOMETRY)  
CATALOG NUMBER: 206-8LED4036-12-XX-LSL

**CANDELA DISTRIBUTION (continued):**

	75°	77.5°	80°	82.5°	85°	87.5°	90°
-22.5°	0	0	0	0	0	0	0
-25°	0	0	0	0	0	0	0
-27.5°	0	0	0	0	0	0	0
-30°	0	0	0	0	0	0	0
-32.5°	0	0	0	0	0	0	0
-35°	0	0	0	0	0	0	0
-37.5°	0	0	0	0	0	0	0
-40°	0	0	0	0	0	0	0
-42.5°	0	0	0	0	0	0	0
-45°	0	0	0	0	0	0	0
-47.5°	0	0	0	0	0	0	0
-50°	0	0	0	0	0	0	0
-52.5°	0	0	0	0	0	0	0
-55°	0	0	0	0	0	0	0
-57.5°	0	0	0	0	0	0	0
-60°	0	0	0	0	0	0	0
-62.5°	0	0	0	0	0	0	0
-65°	0	0	0	0	0	0	0
-67.5°	0	0	0	0	0	0	0
-70°	0	0	0	0	0	0	0
-72.5°	0	0	0	0	0	0	0
-75°	0	0	0	0	0	0	0
-77.5°	0	0	0	0	0	0	0
-80°	0	0	0	0	0	0	0
-82.5°	0	0	0	0	0	0	0
-85°	0	0	0	0	0	0	0
-87.5°	0	0	0	0	0	0	0
-90°	0	0	0	0	0	0	0

(END OF REPORT)