

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: LUMIERE

Report Number: P220506

Luminaire Tested: **9003-W1-[RW, RI]-LED2797-S-BK-L1-UNV**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P220506  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P29472)  
Test Lab: INNOVATION CENTER-P2  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: LUMIERE  
Catalog Number: 9003-W1-[RW, RI]-LED2797-S-BK-L1-UNV  
Description: LUMIERE LANTERRA 9003 LED WALL LUMINAIRE, RECESSED LENS, SPOT OPTIC, BLACK HOUSING.  
Light Source: (1) 2700K CCT, 97 CRI LED  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 575.7 lumens  
Efficiency: N/A  
Efficacy: 58.7 lumens/watt  
Spacing Criteria (0/90/45): 0.27 / 0.27 / 0.27  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct


Input Watts (W): 9.8  
Input Voltage (V): 120  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P220506

CATALOG NUMBER: 9003-W1-[RW, RI]-LED2797-S-BK-L1-UNV

### Luminous Intensity Polar Plot





TEST NUMBER: P220506

CATALOG NUMBER: 9003-W1-[RW, RI]-LED2797-S-BK-L1-UNV

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	115	113	112	110	113	111	110	108	107	106	105	104	103	102	100	100	99	97
2	112	109	106	104	110	107	105	102	104	102	100	101	100	98	98	97	96	95
3	109	105	101	99	107	103	100	98	101	98	96	99	97	95	97	95	94	92
4	106	101	98	95	105	100	97	94	98	95	93	96	94	92	95	93	91	90
5	103	98	94	92	102	97	94	91	96	93	91	94	92	90	93	91	89	88
6	101	95	92	89	100	95	91	89	93	90	88	92	90	88	91	89	87	86
7	99	93	89	87	98	92	89	86	91	88	86	90	88	86	89	87	85	84
8	96	91	87	84	95	90	87	84	89	86	84	88	86	84	88	85	83	82
9	94	88	85	82	94	88	85	82	87	84	82	87	84	82	86	83	82	81
10	92	87	83	81	92	86	83	81	86	83	80	85	82	80	84	82	80	79

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	1082084
5°	828988
10°	347778
15°	146766
20°	95465
25°	41833
30°	5672
35°	2142
40°	1517
45°	1178
50°	1023
55°	1032
60°	833
65°	571
70°	256
75°	0
80°	0
85°	0



TEST NUMBER: P220506

CATALOG NUMBER: 9003-W1-[RW, RI]-LED2797-S-BK-L1-UNV

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	283.5	49.2
10°-20°	197.7	34.3
20°-30°	81.5	14.2
30°-40°	6.4	1.1
40°-50°	3.1	0.5
50°-60°	2.3	0.4
60°-70°	1.1	0.2
70°-80°	0.2	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	562.7	97.7
0°-40°	569.1	98.9
0°-60°	574.5	99.8
0°-90°	575.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	575.7	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	4935	
5°	3766	284
15°	646	198
25°	173	81
35°	8	6
45°	4	3
55°	3	2
65°	1	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P220506

CATALOG NUMBER: 9003-W1-[RW, RI]-LED2797-S-BK-L1-UNV

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	4934.7
1°	4871.8
2°	4724.3
3°	4484.2
4°	4163.8
5°	3766.1
6°	3323.5
7°	2859.8
8°	2382.8
9°	1945.6
10°	1561.9
11°	1258.1
12°	1033.3
13°	867.6
14°	746.6
15°	646.5
16°	565.7
17°	513.0
18°	472.5
19°	436.8
20°	409.1
21°	383.7
22°	345.1
23°	292.4
24°	232.4
25°	172.9
26°	120.2
27°	72.0
28°	40.2
29°	26.9
30°	22.4
32.5°	14.4
35°	8.0
37.5°	6.1
40°	5.3
42.5°	4.6
45°	3.8
47.5°	3.4
50°	3.0
52.5°	2.7
55°	2.7
57.5°	2.3
60°	1.9
62.5°	1.5
65°	1.1



TEST NUMBER: P220506

CATALOG NUMBER: 9003-W1-[RW, RI]-LED2797-S-BK-L1-UNV

**CANDELA DISTRIBUTION (continued):**

	0°
67.5°	0.8
70°	0.4
72.5°	0.4
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)