

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: LUMIERE

Report Number: P220533

Luminaire Tested: **9003-W1-[RW, RI]-LED3597-M-BK-L2-UNV**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P220533
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P29473)
Test Lab: INNOVATION CENTER-P2
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: LUMIERE
Catalog Number: 9003-W1-[RW, RI]-LED3597-M-BK-L2-UNV
Description: LUMIERE LANTERRA 9003 LED WALL LUMINAIRE, RECESSED LENS, MEDIUM FLOOD OPTIC, BLACK HOUSING.
Light Source: (1) 3500K CCT, 97 CRI LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1154.8 lumens
Efficiency: N/A
Efficacy: 57.5 lumens/watt
Spacing Criteria (0/90/45): 0.4 / 0.4 / 0.4
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct


Input Watts (W): 20.1
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P220533

CATALOG NUMBER: 9003-W1-[RW, RI]-LED3597-M-BK-L2-UNV

Luminous Intensity Polar Plot





TEST NUMBER: P220533

CATALOG NUMBER: 9003-W1-[RW, RI]-LED3597-M-BK-L2-UNV

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	115	113	111	109	113	111	109	108	107	106	104	103	102	101	100	99	98	97
2	111	108	105	102	109	106	103	101	103	101	99	100	98	97	98	96	95	94
3	108	103	100	97	106	102	99	96	100	97	95	97	95	93	95	93	92	91
4	105	99	96	93	103	98	95	92	96	93	91	95	92	90	93	91	89	88
5	102	96	92	89	100	95	91	88	93	90	88	92	89	87	91	88	86	85
6	99	93	89	86	98	92	88	85	91	87	85	89	87	84	88	86	84	83
7	96	90	86	83	95	89	85	83	88	85	82	87	84	82	86	83	81	80
8	94	87	83	80	93	87	83	80	86	82	80	85	82	80	84	81	79	78
9	91	85	81	78	90	84	80	78	83	80	78	83	80	77	82	79	77	76
10	89	82	78	76	88	82	78	76	81	78	76	81	78	75	80	77	75	74

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1214179
5°	1088045
10°	764404
15°	410218
20°	215782
25°	96465
30°	18661
35°	6853
40°	3893
45°	3225
50°	2729
55°	2141
60°	1754
65°	1245
70°	513
75°	0
80°	0
85°	0



TEST NUMBER: P220533

CATALOG NUMBER: 9003-W1-[RW, RI]-LED3597-M-BK-L2-UNV

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	422.9	36.6
10°-20°	509.6	44.1
20°-30°	185.9	16.1
30°-40°	20.5	1.8
40°-50°	8.1	0.7
50°-60°	5.1	0.4
60°-70°	2.4	0.2
70°-80°	0.3	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1118.5	96.9
0°-40°	1139.0	98.6
0°-60°	1152.2	99.8
0°-90°	1154.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1154.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	5537	
5°	4943	423
15°	1807	510
25°	399	186
35°	26	21
45°	10	8
55°	6	5
65°	2	2
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P220533

CATALOG NUMBER: 9003-W1-[RW, RI]-LED3597-M-BK-L2-UNV

CANDELA DISTRIBUTION (FULL):

0°	
0°	5537.1
1°	5492.2
2°	5413.8
3°	5298.5
4°	5139.2
5°	4943.0
6°	4708.4
7°	4433.0
8°	4120.8
9°	3782.1
10°	3433.0
11°	3081.6
12°	2733.3
13°	2404.2
14°	2090.4
15°	1807.0
16°	1546.8
17°	1334.6
18°	1162.5
19°	1026.4
20°	924.7
21°	841.4
22°	746.2
23°	633.3
24°	515.6
25°	398.7
26°	287.4
27°	188.1
28°	118.5
29°	86.5
30°	73.7
32.5°	49.6
35°	25.6
37.5°	16.8
40°	13.6
42.5°	12.0
45°	10.4
47.5°	8.8
50°	8.0
52.5°	6.4
55°	5.6
57.5°	4.8
60°	4.0
62.5°	3.2
65°	2.4



TEST NUMBER: P220533

CATALOG NUMBER: 9003-W1-[RW, RI]-LED3597-M-BK-L2-UNV

CANDELA DISTRIBUTION (continued):

	0°
67.5°	1.6
70°	0.8
72.5°	0.8
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)