

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: LUMIERE

Report Number: P220891

Luminaire Tested: **9004-W1-[RW, RI]-LED2790-W-BK-L1-UNV**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P220891
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P29494)
Test Lab: INNOVATION CENTER-P2
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: LUMIERE
Catalog Number: 9004-W1-[RW, RI]-LED2790-W-BK-L1-UNV
Description: LUMIERE LANTERRA 9004 LED WALL LUMINAIRE, RECESSED LENS, WIDE FLOOD OPTIC, BLACK HOUSING.
Light Source: (1) 2700K CCT, 90 CRI LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 752.8 lumens
Efficiency: N/A
Efficacy: 76.8 lumens/watt
Spacing Criteria (0/90/45): 0.85 / 0.85 / 0.83
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct


Input Watts (W): 9.8
Input Voltage (V): 120
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P220891

CATALOG NUMBER: 9004-W1-[RW, RI]-LED2790-W-BK-L1-UNV

Luminous Intensity Polar Plot





TEST NUMBER: P220891

CATALOG NUMBER: 9004-W1-[RW, RI]-LED2790-W-BK-L1-UNV

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	114	111	109	107	111	109	107	105	105	103	102	101	100	99	98	97	96	94
2	109	104	100	97	107	102	99	96	99	96	94	96	94	92	94	92	90	89
3	104	98	93	89	102	96	92	89	94	90	87	91	88	86	89	87	85	83
4	99	92	87	83	97	91	86	82	89	85	81	87	83	80	85	82	80	78
5	94	87	81	77	93	86	81	77	84	80	76	82	79	76	81	78	75	73
6	90	82	76	72	89	81	76	72	80	75	72	78	74	71	77	73	71	69
7	86	77	72	68	85	77	71	68	75	71	67	74	70	67	73	69	67	65
8	82	73	68	64	81	73	67	64	72	67	64	71	66	63	70	66	63	62
9	79	70	64	60	78	69	64	60	68	63	60	67	63	60	67	63	60	58
10	75	66	61	57	74	66	61	57	65	60	57	64	60	57	64	60	57	55

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	124875
5°	126912
10°	122330
15°	112450
20°	96005
25°	80651
30°	60375
35°	18943
40°	11223
45°	6820
50°	2840
55°	473
60°	321
65°	175
70°	108
75°	143
80°	0
85°	0



TEST NUMBER: P220891

CATALOG NUMBER: 9004-W1-[RW, RI]-LED2790-W-BK-L1-UNV

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	96.3	12.8
10°-20°	242.9	32.3
20°-30°	270.5	35.9
30°-40°	107.9	14.3
40°-50°	30.8	4.1
50°-60°	3.4	0.5
60°-70°	0.6	0.1
70°-80°	0.3	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	609.7	81.0
0°-40°	717.6	95.3
0°-60°	751.8	99.9
0°-90°	752.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	752.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1012	
5°	1025	96
15°	881	243
25°	593	271
35°	126	108
45°	39	31
55°	2	3
65°	1	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P220891

CATALOG NUMBER: 9004-W1-[RW, RI]-LED2790-W-BK-L1-UNV

CANDELA DISTRIBUTION (FULL):

0°	
0°	1012.4
1°	1012.1
2°	1014.0
3°	1018.7
4°	1023.1
5°	1025.0
6°	1023.7
7°	1017.1
8°	1005.8
9°	991.9
10°	976.7
11°	960.3
12°	943.3
13°	924.4
14°	903.6
15°	880.6
16°	853.7
17°	825.0
18°	793.8
19°	762.0
20°	731.4
21°	701.7
22°	673.3
23°	645.6
24°	619.4
25°	592.6
26°	567.4
27°	545.6
28°	522.9
29°	482.9
30°	423.9
32.5°	247.9
35°	125.8
37.5°	93.0
40°	69.7
42.5°	51.7
45°	39.1
47.5°	29.0
50°	14.8
52.5°	3.8
55°	2.2
57.5°	1.6
60°	1.3
62.5°	0.9
65°	0.6



TEST NUMBER: P220891

CATALOG NUMBER: 9004-W1-[RW, RI]-LED2790-W-BK-L1-UNV

CANDELA DISTRIBUTION (continued):

	0°
67.5°	0.3
70°	0.3
72.5°	0.3
75°	0.3
77.5°	0.3
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)