

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: LUMIERE

Report Number: P220944

Luminaire Tested: **9004-W1-FL-LED2790-M-WT-L1-UNV**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P220944  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P29497)  
Test Lab: INNOVATION CENTER-P2  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: LUMIERE  
Catalog Number: 9004-W1-FL-LED2790-M-WT-L1-UNV  
Description: LUMIERE LANTERRA 9004 LED WALL LUMINAIRE, FLUSH LENS, MEDIUM FLOOD OPTIC, WHITE HOUSING.  
Light Source: (1) 2700K CCT, 90 CRI LED  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 891.3 lumens  
Efficiency: N/A  
Efficacy: 91.0 lumens/watt  
Spacing Criteria (0/90/45): 0.43 / 0.43 / 0.44  
Luminous Opening: Circular (Dia: 0.33' x H: 0')  
CIE Type: Direct


Input Watts (W): 9.8  
Input Voltage (V): 120  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P220944

CATALOG NUMBER: 9004-W1-FL-LED2790-M-WT-L1-UNV

### Luminous Intensity Polar Plot





TEST NUMBER: P220944

CATALOG NUMBER: 9004-W1-FL-LED2790-M-WT-L1-UNV

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	114	112	110	108	112	110	108	106	106	104	103		102	101	100		99	98	97	95
2	110	106	102	99	108	104	101	98	101	98	96		98	96	94		95	94	92	91
3	106	100	96	93	104	99	95	92	96	93	90		94	91	89		92	90	88	86
4	101	95	91	87	100	94	90	86	92	88	85		90	87	85		88	86	84	82
5	97	91	86	82	96	90	85	82	88	84	81		86	83	80		85	82	80	78
6	94	86	82	78	92	86	81	78	84	80	77		83	79	77		82	79	76	75
7	90	83	78	74	89	82	77	74	81	77	74		80	76	73		79	75	73	72
8	87	79	74	71	86	79	74	71	78	74	71		77	73	70		76	73	70	69
9	84	76	71	68	83	76	71	68	75	71	68		74	70	67		73	70	67	66
10	81	73	68	65	80	73	68	65	72	68	65		71	68	65		71	67	65	64

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	359725
5°	330096
10°	242544
15°	141194
20°	76998
25°	54725
30°	49323
35°	38849
40°	8630
45°	2372
50°	787
55°	473
60°	321
65°	175
70°	108
75°	143
80°	0
85°	0



TEST NUMBER: P220944

CATALOG NUMBER: 9004-W1-FL-LED2790-M-WT-L1-UNV

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	230.9	25.9
10°-20°	308.2	34.6
20°-30°	192.8	21.6
30°-40°	143.0	16.0
40°-50°	13.3	1.5
50°-60°	2.2	0.2
60°-70°	0.7	0.1
70°-80°	0.3	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	731.9	82.1
0°-40°	874.9	98.2
0°-60°	890.3	99.9
0°-90°	891.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	891.3	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	2916	
5°	2666	231
15°	1106	308
25°	402	193
35°	258	143
45°	14	13
55°	2	2
65°	1	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P220944

CATALOG NUMBER: 9004-W1-FL-LED2790-M-WT-L1-UNV

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	2916.4
1°	2897.1
2°	2864.3
3°	2817.0
4°	2752.1
5°	2666.0
6°	2559.0
7°	2430.0
8°	2279.6
9°	2111.8
10°	1936.5
11°	1757.0
12°	1583.2
13°	1413.9
14°	1253.0
15°	1105.7
16°	971.7
17°	854.7
18°	749.7
19°	660.7
20°	586.6
21°	528.0
22°	481.0
23°	446.3
24°	420.7
25°	402.1
26°	388.2
27°	376.3
28°	365.2
29°	355.8
30°	346.3
32.5°	320.1
35°	258.0
37.5°	156.1
40°	53.6
42.5°	18.6
45°	13.6
47.5°	9.8
50°	4.1
52.5°	3.2
55°	2.2
57.5°	1.6
60°	1.3
62.5°	0.9
65°	0.6



TEST NUMBER: P220944

CATALOG NUMBER: 9004-W1-FL-LED2790-M-WT-L1-UNV

**CANDELA DISTRIBUTION (continued):**

	0°
67.5°	0.6
70°	0.3
72.5°	0.3
75°	0.3
77.5°	0.3
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)