

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: LUMIERE

Report Number: P221081

Luminaire Tested: **9004-W1-FL-LED2797-F-BK-L1-UNV**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P221081
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P29498)
Test Lab: INNOVATION CENTER-P2
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: LUMIERE
Catalog Number: 9004-W1-FL-LED2797-F-BK-L1-UNV
Description: LUMIERE LANTERRA 9004 LED WALL LUMINAIRE, FLUSH LENS, FLOOD OPTIC, BLACK HOUSING.
Light Source: (1) 2700K CCT, 97 CRI LED
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 839.2 lumens
Efficiency: N/A
Efficacy: 85.6 lumens/watt
Spacing Criteria (0/90/45): 0.58 / 0.58 / 0.56
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 9.8
Input Voltage (V): 120
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P221081
CATALOG NUMBER: 9004-W1-FL-LED2797-F-BK-L1-UNV

Luminous Intensity Polar Plot





TEST NUMBER: P221081

CATALOG NUMBER: 9004-W1-FL-LED2797-F-BK-L1-UNV

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	114	112	110	108	112	110	108	106	106	104	103		102	101	100		99	98	97	95
2	110	105	102	99	107	104	100	98	100	98	96		97	95	94		95	93	92	90
3	105	99	95	92	103	98	94	91	96	92	90		93	90	88		91	89	87	85
4	101	94	89	86	99	93	89	85	91	87	84		89	86	83		87	85	82	81
5	97	89	84	81	95	88	84	80	87	83	80		85	82	79		84	81	78	77
6	93	85	80	76	91	84	79	76	83	79	75		81	78	75		80	77	74	73
7	89	81	76	72	88	80	75	72	79	75	72		78	74	71		77	74	71	70
8	85	77	72	69	84	77	72	69	76	71	68		75	71	68		74	70	68	67
9	82	74	69	65	81	74	69	65	73	68	65		72	68	65		71	67	65	64
10	79	71	66	63	78	70	66	62	70	65	62		69	65	62		68	65	62	61

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	230138
5°	222264
10°	195688
15°	150312
20°	92973
25°	57610
30°	47998
35°	38427
40°	8373
45°	1779
50°	345
55°	194
60°	148
65°	88
70°	108
75°	143
80°	0
85°	0



TEST NUMBER: P221081

CATALOG NUMBER: 9004-W1-FL-LED2797-F-BK-L1-UNV

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	163.9	19.5
10°-20°	315.7	37.6
20°-30°	207.3	24.7
30°-40°	139.8	16.7
40°-50°	11.0	1.3
50°-60°	0.8	0.1
60°-70°	0.4	0.0
70°-80°	0.3	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	686.9	81.9
0°-40°	826.7	98.5
0°-60°	838.5	99.9
0°-90°	839.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	839.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1866	
5°	1795	164
15°	1177	316
25°	423	207
35°	255	140
45°	10	11
55°	1	1
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P221081

CATALOG NUMBER: 9004-W1-FL-LED2797-F-BK-L1-UNV

CANDELA DISTRIBUTION (FULL):

0°	
0°	1865.8
1°	1857.7
2°	1845.7
3°	1832.5
4°	1817.0
5°	1795.1
6°	1765.0
7°	1725.8
8°	1677.6
9°	1621.8
10°	1562.4
11°	1497.2
12°	1426.2
13°	1348.7
14°	1266.3
15°	1177.1
16°	1083.3
17°	986.3
18°	889.2
19°	798.0
20°	708.3
21°	630.5
22°	560.7
23°	502.8
24°	458.1
25°	423.3
26°	398.1
27°	378.8
28°	362.5
29°	349.0
30°	337.0
32.5°	311.9
35°	255.2
37.5°	151.7
40°	52.0
42.5°	15.5
45°	10.2
47.5°	6.4
50°	1.8
52.5°	0.9
55°	0.9
57.5°	0.6
60°	0.6
62.5°	0.6
65°	0.3



TEST NUMBER: P221081

CATALOG NUMBER: 9004-W1-FL-LED2797-F-BK-L1-UNV

CANDELA DISTRIBUTION (continued):

	0°
67.5°	0.3
70°	0.3
72.5°	0.3
75°	0.3
77.5°	0.3
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)