

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: LUMIERE

Report Number: P229002

Luminaire Tested: **9004-W1-FL-LED2797-W-WT-L1-UNV**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P229002  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P29499)  
Test Lab: INNOVATION CENTER-P2  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: LUMIERE  
Catalog Number: 9004-W1-FL-LED2797-W-WT-L1-UNV  
Description: LUMIERE LANTERRA 9004 LED WALL LUMINAIRE, FLUSH LENS, WIDE FLOOD OPTIC, WHITE HOUSING.  
Light Source: (1) 2700K CCT, 97 CRI LED  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 815.6 lumens  
Efficiency: N/A  
Efficacy: 83.2 lumens/watt  
Spacing Criteria (0/90/45): 0.86 / 0.86 / 0.91  
Luminous Opening: Circular (Dia: 0.33' x H: 0')  
CIE Type: Direct


Input Watts (W): 9.8  
Input Voltage (V): 120  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P229002

CATALOG NUMBER: 9004-W1-FL-LED2797-W-WT-L1-UNV

### Luminous Intensity Polar Plot





TEST NUMBER: P229002

CATALOG NUMBER: 9004-W1-FL-LED2797-W-WT-L1-UNV

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	114	111	108	106	111	109	106	104	105	103	101	101	99	98	97	96	95	94
2	108	103	99	96	106	101	98	95	98	95	92	95	93	90	92	90	89	87
3	102	96	91	87	100	95	90	86	92	88	85	90	86	84	87	85	82	81
4	97	90	84	80	95	89	83	79	86	82	79	84	81	78	83	79	77	75
5	92	84	78	74	91	83	78	73	81	76	73	80	75	72	78	74	72	70
6	88	79	73	68	86	78	72	68	76	71	68	75	71	67	74	70	67	65
7	83	74	68	64	82	73	68	64	72	67	63	71	66	63	70	66	63	61
8	79	70	64	60	78	69	63	59	68	63	59	67	62	59	66	62	59	57
9	75	66	60	56	74	65	60	56	64	59	56	63	59	55	63	58	55	54
10	72	62	56	53	71	62	56	52	61	56	52	60	55	52	59	55	52	51

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	114403
5°	116536
10°	112836
15°	103920
20°	89061
25°	75942
30°	64947
35°	48546
40°	17229
45°	8059
50°	5335
55°	3591
60°	1801
65°	438
70°	325
75°	286
80°	0
85°	0



TEST NUMBER: P229002

CATALOG NUMBER: 9004-W1-FL-LED2797-W-WT-L1-UNV

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	88.6	10.9
10°-20°	224.6	27.5
20°-30°	256.4	31.4
30°-40°	188.2	23.1
40°-50°	39.9	4.9
50°-60°	15.1	1.9
60°-70°	2.2	0.3
70°-80°	0.6	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	569.6	69.8
0°-40°	757.8	92.9
0°-60°	812.9	99.7
0°-90°	815.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	815.6	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	928	
5°	941	89
15°	814	225
25°	558	256
35°	322	188
45°	46	40
55°	17	15
65°	2	2
75°	1	1
85°	0	0
90°	0	



TEST NUMBER: P229002

CATALOG NUMBER: 9004-W1-FL-LED2797-W-WT-L1-UNV

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	927.5
1°	927.2
2°	929.6
3°	934.2
4°	938.6
5°	941.2
6°	940.7
7°	935.7
8°	926.0
9°	914.1
10°	900.9
11°	886.0
12°	870.8
13°	853.6
14°	834.8
15°	813.8
16°	789.8
17°	763.2
18°	735.8
19°	706.8
20°	678.5
21°	652.2
22°	626.7
23°	602.7
24°	579.9
25°	558.0
26°	536.7
27°	515.1
28°	494.3
29°	475.0
30°	456.0
32.5°	404.9
35°	322.4
37.5°	217.8
40°	107.0
42.5°	60.2
45°	46.2
47.5°	36.2
50°	27.8
52.5°	21.9
55°	16.7
57.5°	12.0
60°	7.3
62.5°	2.0
65°	1.5



TEST NUMBER: P229002

CATALOG NUMBER: 9004-W1-FL-LED2797-W-WT-L1-UNV

**CANDELA DISTRIBUTION (continued):**

	0°
67.5°	1.2
70°	0.9
72.5°	0.9
75°	0.6
77.5°	0.3
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)