

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: LUMIERE

Report Number: P229003

Luminaire Tested: **9004-W1-FL-LED3097-W-WT-L1-UNV**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P229003  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P29499)  
Test Lab: INNOVATION CENTER-P2  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: LUMIERE  
Catalog Number: 9004-W1-FL-LED3097-W-WT-L1-UNV  
Description: LUMIERE LANTERRA 9004 LED WALL LUMINAIRE, FLUSH LENS, WIDE FLOOD OPTIC, WHITE HOUSING.  
Light Source: (1) 3000K CCT, 97 CRI LED  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 823.3 lumens  
Efficiency: N/A  
Efficacy: 84.0 lumens/watt  
Spacing Criteria (0/90/45): 0.86 / 0.86 / 0.91  
Luminous Opening: Circular (Dia: 0.33' x H: 0')  
CIE Type: Direct


Input Watts (W): 9.8  
Input Voltage (V): 120  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P229003

CATALOG NUMBER: 9004-W1-FL-LED3097-W-WT-L1-UNV

### Luminous Intensity Polar Plot





TEST NUMBER: P229003

CATALOG NUMBER: 9004-W1-FL-LED3097-W-WT-L1-UNV

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	114	111	108	106	111	109	106	104	105	103	101	101	99	98	97	96	95	94
2	108	103	99	96	106	101	98	95	98	95	92	95	93	90	92	90	89	87
3	102	96	91	87	100	95	90	86	92	88	85	90	86	84	87	85	82	81
4	97	90	84	80	95	89	83	79	86	82	79	84	81	78	83	79	77	75
5	92	84	78	74	91	83	78	73	81	76	73	80	75	72	78	74	72	70
6	88	79	73	68	86	78	72	68	76	71	68	75	71	67	74	70	67	65
7	83	74	68	64	82	73	68	64	72	67	63	71	66	63	70	66	63	61
8	79	70	64	60	78	69	63	59	68	63	59	67	62	59	66	62	59	57
9	75	66	60	56	74	65	60	56	64	59	56	63	59	55	63	58	55	54
10	72	62	56	53	71	62	56	52	61	56	52	60	55	52	59	55	52	51

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	115489
5°	117638
10°	113901
15°	104903
20°	89901
25°	76663
30°	65559
35°	49013
40°	17390
45°	8129
50°	5373
55°	3613
60°	1826
65°	438
70°	325
75°	286
80°	0
85°	0



TEST NUMBER: P229003

CATALOG NUMBER: 9004-W1-FL-LED3097-W-WT-L1-UNV

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	89.4	10.9
10°-20°	226.7	27.5
20°-30°	258.8	31.4
30°-40°	190.0	23.1
40°-50°	40.3	4.9
50°-60°	15.2	1.9
60°-70°	2.2	0.3
70°-80°	0.6	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	575.0	69.8
0°-40°	765.0	92.9
0°-60°	820.5	99.7
0°-90°	823.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	823.3	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	936	
5°	950	89
15°	822	227
25°	563	259
35°	326	190
45°	47	40
55°	17	15
65°	2	2
75°	1	1
85°	0	0
90°	0	



TEST NUMBER: P229003

CATALOG NUMBER: 9004-W1-FL-LED3097-W-WT-L1-UNV

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	936.3
1°	936.0
2°	938.3
3°	943.0
4°	947.5
5°	950.1
6°	949.5
7°	944.5
8°	934.8
9°	922.7
10°	909.4
11°	894.4
12°	879.0
13°	861.6
14°	842.7
15°	821.5
16°	797.3
17°	770.4
18°	742.7
19°	713.5
20°	684.9
21°	658.3
22°	632.6
23°	608.4
24°	585.4
25°	563.3
26°	541.7
27°	519.9
28°	499.0
29°	479.5
30°	460.3
32.5°	408.7
35°	325.5
37.5°	219.8
40°	108.0
42.5°	60.8
45°	46.6
47.5°	36.6
50°	28.0
52.5°	22.1
55°	16.8
57.5°	12.1
60°	7.4
62.5°	2.1
65°	1.5



TEST NUMBER: P229003

CATALOG NUMBER: 9004-W1-FL-LED3097-W-WT-L1-UNV

**CANDELA DISTRIBUTION (continued):**

	0°
67.5°	1.2
70°	0.9
72.5°	0.9
75°	0.6
77.5°	0.3
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)