

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: LUMIERE

Report Number: P221053

Luminaire Tested: **9004-W1-FL-LED4080-M-BK-L1-UNV**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P221053  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P29497)  
Test Lab: INNOVATION CENTER-P2  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: LUMIERE  
Catalog Number: 9004-W1-FL-LED4080-M-BK-L1-UNV  
Description: LUMIERE LANTERRA 9004 LED WALL LUMINAIRE, FLUSH LENS, MEDIUM FLOOD OPTIC, BLACK HOUSING.  
Light Source: (1) 4000K CCT, 80 CRI LED  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 1181.5 lumens  
Efficiency: N/A  
Efficacy: 120.6 lumens/watt  
Spacing Criteria (0/90/45): 0.43 / 0.43 / 0.44  
Luminous Opening: Circular (Dia: 0.33' x H: 0')  
CIE Type: Direct

Input Watts (W): 9.8  
Input Voltage (V): 120  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P221053  
CATALOG NUMBER: 9004-W1-FL-LED4080-M-BK-L1-UNV

### Luminous Intensity Polar Plot





TEST NUMBER: P221053

CATALOG NUMBER: 9004-W1-FL-LED4080-M-BK-L1-UNV

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	114	112	110	108	112	110	108	106	106	104	103		102	101	100		99	98	97	95
2	110	106	102	99	108	104	101	98	101	98	96		98	96	94		95	94	92	91
3	106	100	96	93	104	99	95	92	96	93	90		94	91	89		92	90	88	86
4	101	95	91	87	100	94	90	86	92	88	85		90	87	85		88	86	84	82
5	97	91	86	82	96	90	85	82	88	84	81		86	83	80		85	82	80	78
6	94	86	82	78	92	86	81	78	84	80	77		83	79	77		82	79	76	75
7	90	83	78	74	89	82	77	74	81	77	74		80	76	73		79	75	73	72
8	87	79	74	71	86	79	74	71	78	74	71		77	73	70		76	73	70	69
9	84	76	71	68	83	76	71	68	75	71	68		74	70	67		73	70	67	66
10	81	73	68	65	80	73	68	65	72	68	65		71	68	65		71	67	65	64

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	476805
5°	437531
10°	321488
15°	187152
20°	102069
25°	72540
30°	65374
35°	51497
40°	11448
45°	3140
50°	1036
55°	624
60°	419
65°	233
70°	144
75°	191
80°	0
85°	0



TEST NUMBER: P221053

CATALOG NUMBER: 9004-W1-FL-LED4080-M-BK-L1-UNV

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	306.1	25.9
10°-20°	408.5	34.6
20°-30°	255.5	21.6
30°-40°	189.5	16.0
40°-50°	17.7	1.5
50°-60°	2.8	0.2
60°-70°	1.0	0.1
70°-80°	0.4	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	970.1	82.1
0°-40°	1159.6	98.2
0°-60°	1180.1	99.9
0°-90°	1181.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1181.5	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	3866	
5°	3534	306
15°	1466	409
25°	533	255
35°	342	190
45°	18	18
55°	3	3
65°	1	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P221053

CATALOG NUMBER: 9004-W1-FL-LED4080-M-BK-L1-UNV

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	3865.6
1°	3840.1
2°	3796.6
3°	3733.9
4°	3647.8
5°	3533.7
6°	3392.0
7°	3221.0
8°	3021.6
9°	2799.2
10°	2566.8
11°	2328.9
12°	2098.6
13°	1874.1
14°	1660.9
15°	1465.6
16°	1288.0
17°	1132.9
18°	993.7
19°	875.8
20°	777.6
21°	699.8
22°	637.5
23°	591.5
24°	557.7
25°	533.0
26°	514.6
27°	498.7
28°	484.1
29°	471.5
30°	459.0
32.5°	424.3
35°	342.0
37.5°	206.9
40°	71.1
42.5°	24.7
45°	18.0
47.5°	13.0
50°	5.4
52.5°	4.2
55°	2.9
57.5°	2.1
60°	1.7
62.5°	1.3
65°	0.8



TEST NUMBER: P221053

CATALOG NUMBER: 9004-W1-FL-LED4080-M-BK-L1-UNV

**CANDELA DISTRIBUTION (continued):**

	0°
67.5°	0.8
70°	0.4
72.5°	0.4
75°	0.4
77.5°	0.4
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)