

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: LUMIERE

Report Number: P220863

Luminaire Tested: **9004-W1-[RW, RI]-LED3597-M-BK-L3-UNV**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P220863
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P29492)
Test Lab: INNOVATION CENTER-P2
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: LUMIERE
Catalog Number: 9004-W1-[RW, RI]-LED3597-M-BK-L3-UNV
Description: LUMIERE LANTERRA 9004 LED WALL LUMINAIRE, RECESSED LENS, MEDIUM FLOOD OPTIC, BLACK HOUSING.
Light Source: (1) 3500K CCT, 97 CRI LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1981.4 lumens
Efficiency: N/A
Efficacy: 69.5 lumens/watt
Spacing Criteria (0/90/45): 0.43 / 0.43 / 0.44
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct


Input Watts (W): 28.5
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P220863

CATALOG NUMBER: 9004-W1-[RW, RI]-LED3597-M-BK-L3-UNV

Luminous Intensity Polar Plot





TEST NUMBER: P220863

CATALOG NUMBER: 9004-W1-[RW, RI]-LED3597-M-BK-L3-UNV

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	115	113	111	109	112	110	109	107	106	105	104	103	102	101	99	99	98	96
2	111	107	104	101	109	105	102	100	102	100	98	99	97	96	96	95	94	92
3	107	102	98	95	105	100	97	94	98	95	93	96	93	91	94	92	90	89
4	103	97	93	90	102	96	92	89	94	91	88	92	90	87	91	88	86	85
5	100	93	89	86	98	92	88	85	91	87	85	89	86	84	88	85	83	82
6	96	90	85	82	95	89	85	82	88	84	81	86	83	81	85	82	80	79
7	93	86	82	79	92	86	81	78	85	81	78	84	80	78	83	80	77	76
8	90	83	79	76	89	83	78	76	82	78	75	81	77	75	80	77	75	74
9	88	80	76	73	87	80	76	73	79	75	73	78	75	72	78	75	72	71
10	85	78	73	70	84	77	73	70	77	73	70	76	73	70	75	72	70	69

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	910303
5°	835169
10°	616197
15°	359671
20°	195042
25°	137839
30°	99884
35°	12423
40°	4251
45°	1675
50°	1075
55°	860
60°	592
65°	467
70°	289
75°	381
80°	568
85°	0



TEST NUMBER: P220863

CATALOG NUMBER: 9004-W1-[RW, RI]-LED3597-M-BK-L3-UNV

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	584.8	29.5
10°-20°	784.3	39.6
20°-30°	475.8	24.0
30°-40°	121.7	6.1
40°-50°	8.7	0.4
50°-60°	3.6	0.2
60°-70°	1.6	0.1
70°-80°	0.8	0.0
80°-90°	0.1	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1844.9	93.1
0°-40°	1966.7	99.3
0°-60°	1978.9	99.9
0°-90°	1981.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1981.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	7380	
5°	6745	585
15°	2817	784
25°	1013	476
35°	82	122
45°	10	9
55°	4	4
65°	2	2
75°	1	1
85°	0	0
90°	0	



TEST NUMBER: P220863

CATALOG NUMBER: 9004-W1-[RW, RI]-LED3597-M-BK-L3-UNV

CANDELA DISTRIBUTION (FULL):

0°	
0°	7380.1
1°	7332.8
2°	7248.8
3°	7128.7
4°	6964.6
5°	6745.2
6°	6471.4
7°	6163.1
8°	5769.2
9°	5348.9
10°	4919.8
11°	4468.2
12°	4024.7
13°	3600.4
14°	3192.9
15°	2816.6
16°	2480.3
17°	2176.9
18°	1906.3
19°	1678.1
20°	1485.9
21°	1334.6
22°	1214.5
23°	1125.7
24°	1062.4
25°	1012.8
26°	972.7
27°	938.3
28°	897.5
29°	823.0
30°	701.3
32.5°	333.9
35°	82.5
37.5°	44.8
40°	26.4
42.5°	12.0
45°	9.6
47.5°	8.0
50°	5.6
52.5°	4.8
55°	4.0
57.5°	3.2
60°	2.4
62.5°	2.4
65°	1.6



TEST NUMBER: P220863

CATALOG NUMBER: 9004-W1-[RW, RI]-LED3597-M-BK-L3-UNV

CANDELA DISTRIBUTION (continued):

	0°
67.5°	0.8
70°	0.8
72.5°	0.8
75°	0.8
77.5°	0.8
80°	0.8
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)