

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: LUMIERE

Report Number: P220943

Luminaire Tested: **9004-W1-FL-LED4097-S-WT-L3-UNV**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P220943
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P29496)
Test Lab: INNOVATION CENTER-P2
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: LUMIERE
Catalog Number: 9004-W1-FL-LED4097-S-WT-L3-UNV
Description: LUMIERE LANTERRA 9004 LED WALL LUMINAIRE, FLUSH LENS, SPOT OPTIC, WHITE HOUSING.
Light Source: (1) 4000K CCT, 97 CRI LED
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2221.2 lumens
Efficiency: N/A
Efficacy: 77.7 lumens/watt
Spacing Criteria (0/90/45): 0.27 / 0.27 / 0.27
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 28.6
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P220943
CATALOG NUMBER: 9004-W1-FL-LED4097-S-WT-L3-UNV

Luminous Intensity Polar Plot





TEST NUMBER: P220943

CATALOG NUMBER: 9004-W1-FL-LED4097-S-WT-L3-UNV

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	115	112	110	108	112	110	108	107	106	105	104	103	101	100	99	98	98	96
2	110	106	103	100	108	105	102	99	102	99	97	99	97	95	96	95	93	92
3	106	101	97	94	104	100	96	93	97	94	92	95	93	90	93	91	89	88
4	102	97	92	89	101	95	91	88	93	90	87	92	89	86	90	87	85	84
5	99	92	88	84	97	91	87	84	90	86	83	88	85	83	87	84	82	81
6	95	89	84	81	94	88	83	80	86	83	80	85	82	79	84	81	79	78
7	92	85	80	77	91	85	80	77	83	79	77	82	79	76	81	78	76	75
8	89	82	77	74	88	82	77	74	81	77	74	80	76	74	79	76	73	72
9	87	79	75	72	86	79	74	71	78	74	71	77	74	71	76	73	71	70
10	84	77	72	69	83	76	72	69	76	72	69	75	71	69	74	71	69	68

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1720326
5°	1339103
10°	557719
15°	235818
20°	161846
25°	129170
30°	119368
35°	97664
40°	20562
45°	4710
50°	1669
55°	1355
60°	789
65°	467
70°	289
75°	381
80°	0
85°	0



TEST NUMBER: P220943

CATALOG NUMBER: 9004-W1-FL-LED4097-S-WT-L3-UNV

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	812.8	36.6
10°-20°	569.6	25.6
20°-30°	449.0	20.2
30°-40°	353.5	15.9
40°-50°	28.6	1.3
50°-60°	5.5	0.2
60°-70°	1.5	0.1
70°-80°	0.7	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1831.4	82.5
0°-40°	2184.8	98.4
0°-60°	2218.9	99.9
0°-90°	2221.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2221.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	13947	
5°	10815	813
15°	1847	570
25°	949	449
35°	649	353
45°	27	29
55°	6	6
65°	2	1
75°	1	1
85°	0	0
90°	0	



TEST NUMBER: P220943

CATALOG NUMBER: 9004-W1-FL-LED4097-S-WT-L3-UNV

CANDELA DISTRIBUTION (FULL):

0°	
0°	13947.2
1°	13755.3
2°	13356.4
3°	12738.0
4°	11891.9
5°	10815.2
6°	9571.9
7°	8228.7
8°	6910.9
9°	5584.4
10°	4452.9
11°	3549.8
12°	2894.9
13°	2431.0
14°	2094.8
15°	1846.7
16°	1660.3
17°	1524.0
18°	1420.1
19°	1321.0
20°	1233.0
21°	1160.0
22°	1095.0
23°	1037.9
24°	988.0
25°	949.1
26°	919.8
27°	897.6
28°	876.2
29°	857.1
30°	838.1
32.5°	790.5
35°	648.6
37.5°	386.9
40°	127.7
42.5°	38.1
45°	27.0
47.5°	19.0
50°	8.7
52.5°	7.9
55°	6.3
57.5°	4.8
60°	3.2
62.5°	1.6
65°	1.6



TEST NUMBER: P220943

CATALOG NUMBER: 9004-W1-FL-LED4097-S-WT-L3-UNV

CANDELA DISTRIBUTION (continued):

	0°
67.5°	0.8
70°	0.8
72.5°	0.8
75°	0.8
77.5°	0.8
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)