

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: LUMIERE

Report Number: P246978

Luminaire Tested: **203-SS-8LED3025-12-CS**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P246978
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-1802-569-8)
Test Lab: INNOVATION CENTER(G2)
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: LUMIERE
Catalog Number: 203-SS-8LED3025-12-CS
Description: CAMBRIA 203 LED LUMINAIRE, 8 WATT, 3000K CCT, 25 DEGREE NARROW OPTIC, REGRESSED HOOD SILVER
Light Source: (1) SORAA 3000K 90 CRI LED
SM16-07-25D-930-03
Ballast/Driver: (1) CHROMA POWER SUPPLY IN0004

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 320.7 lumens
Efficiency: N/A
Efficacy: 43.9 lumens/watt
Spacing Criteria (0/90/45): 0.31 / 0.31 / 0.34
Luminous Opening: Circular (Dia: 0.17' x H: 0')
CIE Type: Direct


Input Watts (W): 7.3
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P246978

CATALOG NUMBER: 203-SS-8LED3025-12-CS

Luminous Intensity Polar Plot





TEST NUMBER: P246978

CATALOG NUMBER: 203-SS-8LED3025-12-CS

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10			
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100
1	115	113	111	110	113	111	109	108	107	106	105	103	102	101	100	99	99	97	97	97
2	112	108	105	103	110	106	104	102	103	101	99	100	99	97	98	97	95	94	94	94
3	108	104	100	97	106	102	99	97	100	97	95	98	96	94	96	94	92	91	91	91
4	105	100	96	93	104	99	95	93	97	94	92	95	93	91	93	91	90	88	88	88
5	102	97	93	90	101	96	92	89	94	91	89	93	90	88	91	89	87	86	86	86
6	99	94	90	87	98	93	89	86	92	88	86	90	87	85	89	87	85	84	84	84
7	97	91	87	84	96	90	86	84	89	86	83	88	85	83	87	85	83	82	82	82
8	95	88	84	82	94	88	84	82	87	84	81	86	83	81	85	83	81	80	80	80
9	92	86	82	80	91	86	82	79	85	82	79	84	81	79	83	81	79	78	78	78
10	90	84	80	78	89	84	80	78	83	80	77	82	79	77	82	79	77	76	76	76

AVERAGE LUMINANCE (cd/sqm):

0°	
0°	1030917
5°	824962
10°	464569
15°	230006
20°	113567
25°	49702
30°	12135
35°	5903
40°	3414
45°	2442
50°	2686
55°	2322
60°	1776
65°	1051
70°	1298
75°	0
80°	0
85°	0



TEST NUMBER: P246978

CATALOG NUMBER: 203-SS-8LED3025-12-CS

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	134.3	41.9
10°-20°	130.2	40.6
20°-30°	42.9	13.4
30°-40°	6.8	2.1
40°-50°	3.0	0.9
50°-60°	2.4	0.7
60°-70°	1.0	0.3
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	307.4	95.8
0°-40°	314.2	98.0
0°-60°	319.6	99.7
0°-90°	320.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	320.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2090	
5°	1666	134
15°	450	130
25°	91	43
35°	10	7
45°	4	3
55°	3	2
65°	1	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P246978

CATALOG NUMBER: 203-SS-8LED3025-12-CS

CANDELA DISTRIBUTION (FULL):

0°	
0°	2089.5
1°	2060.2
2°	2000.8
3°	1912.2
4°	1798.7
5°	1665.7
6°	1522.1
7°	1370.5
8°	1216.3
9°	1070.9
10°	927.3
12.5°	633.8
15°	450.3
17.5°	319.1
20°	216.3
22.5°	141.8
25°	91.3
27.5°	41.7
30°	21.3
32.5°	14.2
35°	9.8
37.5°	7.1
40°	5.3
42.5°	4.4
45°	3.5
47.5°	3.5
50°	3.5
52.5°	2.7
55°	2.7
57.5°	2.7
60°	1.8
62.5°	0.9
65°	0.9
67.5°	0.9
70°	0.9
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)