

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: METALUX

Report Number: P276026

Luminaire Tested: **24CZ2-35-UNV-L93050-W2A1-U-5000K**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P276026
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1805-783-5)
Test Lab: INNOVATION CENTER(G3)
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: METALUX
Catalog Number: 24CZ2-35-UNV-L93050-W2A1-U-5000K
Description: CRUZE 2.0 2x4 TUNABLE WHITE LED TROFFER
WITH RIBBED LENS
Light Source: (168) 90 CRI LEDS TUNED TO 5000K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3142.8 lumens
Efficiency: N/A
Efficacy: 115.8 lumens/watt
Spacing Criteria (0/90/45): 1.21 / 1.27 / 1.37
Luminous Opening: Rectangular (W 2' x L: 4' x H: 0')
CIE Type: Direct


Input Watts (W): 27.13368
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P276026

CATALOG NUMBER: 24CZ2-35-UNV-L93050-W2A1-U-5000K

Luminous Intensity Polar Plot





TEST NUMBER: P276026

CATALOG NUMBER: 24CZ2-35-UNV-L93050-W2A1-U-5000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	108	103	98	94	105	100	96	92	96	93	89	92	89	87	89	86	84	82
2	98	89	82	76	95	87	80	75	83	78	73	80	75	71	77	73	70	67
3	89	78	69	62	86	76	68	62	73	66	61	70	64	60	68	63	58	56
4	81	69	59	52	79	67	59	52	65	57	51	62	56	51	60	55	50	48
5	74	61	52	45	72	60	51	45	58	50	44	56	49	44	54	48	43	41
6	69	55	46	39	67	54	45	39	52	44	39	50	44	38	49	43	38	36
7	64	50	41	35	62	49	40	34	47	40	34	46	39	34	45	38	34	32
8	59	45	37	31	58	45	36	31	43	36	30	42	35	30	41	35	30	28
9	55	42	33	28	54	41	33	28	40	33	27	39	32	27	38	32	27	25
10	52	38	30	25	51	38	30	25	37	30	25	36	29	25	35	29	25	23

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	1420	1420	1420
5°	1420	1414	1422
10°	1412	1410	1420
15°	1400	1403	1417
20°	1380	1391	1412
25°	1358	1378	1406
30°	1331	1362	1400
35°	1303	1346	1396
40°	1269	1328	1398
45°	1237	1315	1405
50°	1203	1308	1418
55°	1166	1307	1444
60°	1121	1312	1482
65°	1062	1332	1546
70°	986	1366	1634
75°	900	1434	1772
80°	740	1544	1772
85°	567	1425	1522



TEST NUMBER: P276026

CATALOG NUMBER: 24CZ2-35-UNV-L93050-W2A1-U-5000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	99.8	3.2
10°-20°	284.9	9.1
20°-30°	428.7	13.6
30°-40°	513.8	16.3
40°-50°	535.4	17.0
50°-60°	498.2	15.9
60°-70°	410.3	13.1
70°-80°	279.4	8.9
80°-90°	92.2	2.9
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	813.4	25.9
0°-40°	1327.3	42.2
0°-60°	2360.9	75.1
0°-90°	3142.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3142.8	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1055	1055	1055	1055	1055	
5°	1051	1051	1047	1052	1053	100
15°	1005	1006	1007	1016	1017	283
25°	915	919	928	944	947	421
35°	793	802	819	841	850	496
45°	650	664	691	726	738	502
55°	497	514	557	601	616	443
65°	334	362	418	468	486	331
75°	173	212	276	325	341	182
85°	37	71	92	99	99	45
90°	0	0	0	0	0	



TEST NUMBER: P276026

CATALOG NUMBER: 24CZ2-35-UNV-L93050-W2A1-U-5000K

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1055.2	1055.2	1055.2	1055.2	1055.2
2.5°	1055.2	1055.2	1050.0	1055.2	1055.2
5°	1051.0	1051.0	1046.8	1052.0	1053.1
7.5°	1043.7	1044.7	1040.5	1046.8	1047.9
10°	1033.2	1034.2	1032.1	1038.4	1039.5
12.5°	1020.6	1021.6	1021.6	1029.0	1030.0
15°	1004.8	1005.9	1006.9	1016.4	1017.4
17.5°	984.9	988.1	990.2	1001.7	1003.8
20°	963.9	967.1	971.3	983.9	986.0
22.5°	939.8	944.0	951.4	965.0	968.1
25°	914.6	918.8	928.3	944.0	947.2
27.5°	886.3	892.6	904.2	920.9	925.1
30°	857.0	863.2	876.9	894.7	901.0
32.5°	825.5	833.9	849.6	869.5	875.8
35°	793.0	802.4	819.2	841.2	849.6
37.5°	758.4	768.8	788.8	812.9	823.4
40°	722.7	735.3	756.3	784.6	796.1
42.5°	687.0	698.6	724.8	755.2	767.8
45°	650.3	664.0	691.2	725.8	738.4
47.5°	612.6	626.2	658.7	695.4	707.0
50°	574.8	588.4	625.1	664.0	677.6
52.5°	533.9	551.7	593.7	632.5	646.1
55°	497.2	514.0	557.0	601.0	615.7
57.5°	455.2	475.2	522.4	568.5	584.2
60°	416.4	437.4	487.7	534.9	550.7
62.5°	376.6	399.6	453.1	501.4	519.2
65°	333.6	361.9	418.5	467.8	485.6
67.5°	294.7	324.1	383.9	434.2	450.0
70°	250.7	286.4	347.2	397.5	415.4
72.5°	212.9	248.6	312.6	361.9	379.7
75°	173.1	211.9	275.9	325.2	340.9
77.5°	133.2	176.2	240.2	278.0	283.2
80°	95.5	140.6	199.3	221.3	228.7
82.5°	67.1	108.0	146.8	161.5	165.7
85°	36.7	71.3	92.3	98.6	98.6
87.5°	15.7	30.4	36.7	37.8	38.8
90°	0.0	0.0	0.0	0.0	0.0

(END OF REPORT)