

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: McGRAW-EDISON

Report Number: P940421

Luminaire Tested: **GALN-SB3C-727-U-SL4-HSS**

Issue Date: 1/21/2025

### Test Information

Test Method: LM-79-08  
Report Number: P940421  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2405-108-10)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/21/2025  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: McGRAW-EDISON  
Catalog Number: GALN-SB3C-727-U-SL4-HSS  
Description: GALLEON AREA AND ROADWAY HIGH DENSITY LED LUMINAIRE  
(3) 70 CRI, 2700K, 615mA LIGHTSQUARES WITH 26 LEDS EACH AND TYPE IV SPILL  
LIGHT ELIMINATOR OPTICS WITH HOUSE SIDE SHIELD  
Light Source: -  
Ballast/Driver: -

### Summary

Lumens per Lamp: N/A  
Luminaire Lumens: 14549 lumens  
Efficiency: N/A  
Efficacy: 97.6 lumens/watt  
Luminous Opening: Rectangular (W 1' x L: 1' x H: 0')  
IES Classification: Type IV - Short  
BUG Rating: B2 - U0 - G3  
  
Input Watts (W): 149.1  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT




REPORT NUMBER: P940421

CATALOG NUMBER: GALN-SB3C-727-U-SL4-HSS

## Iso-Footcandle Lines of Horizontal Illumination


✕ Max cd  
 - - - 1/2 Max cd



Based on 25 foot mounting height. Maximum calculated value = 3.5 fc  
 Type IV - Short - N/A

REPORT NUMBER: P940421  
CATALOG NUMBER: GALN-SB3C-727-U-SL4-HSS

## Luminous Intensity Polar Plot



REPORT NUMBER: P940421

CATALOG NUMBER: GALN-SB3C-727-U-SL4-HSS


**FLUX DISTRIBUTION:**

|                    |           | Downward | Upward | Total   |
|--------------------|-----------|----------|--------|---------|
| <b>House Side</b>  | Lumens    | 1878.9   | 0.0    | 1878.9  |
|                    | % Fixture | 12.9     | 0.0    | 12.9    |
| <b>Street Side</b> | Lumens    | 12670.2  | 0.0    | 12670.2 |
|                    | % Fixture | 87.1     | 0.0    | 87.1    |
| <b>Total</b>       | Lumens    | 14549.0  | 0.0    | 14549.0 |
|                    | % Fixture | 100.0    | 0.0    | 100.0   |

**ZONAL LUMENS:**

| Zone      | Lumens  | % Fixture |
|-----------|---------|-----------|
| 0°-10°    | 175.9   | 1.2       |
| 10°-20°   | 477.8   | 3.3       |
| 20°-30°   | 773.1   | 5.3       |
| 30°-40°   | 1141.3  | 7.8       |
| 40°-50°   | 1920.9  | 13.2      |
| 50°-60°   | 2982.6  | 20.5      |
| 60°-70°   | 3732.1  | 25.7      |
| 70°-80°   | 3055.5  | 21.0      |
| 80°-90°   | 289.7   | 2.0       |
| 90°-100°  | 0.0     | 0.0       |
| 100°-110° | 0.0     | 0.0       |
| 110°-120° | 0.0     | 0.0       |
| 120°-130° | 0.0     | 0.0       |
| 130°-140° | 0.0     | 0.0       |
| 140°-150° | 0.0     | 0.0       |
| 150°-160° | 0.0     | 0.0       |
| 160°-170° | 0.0     | 0.0       |
| 170°-180° | 0.0     | 0.0       |
| 0°-90°    | 14549.0 | 100.0     |
| 0°-180°   | 14549.0 | 100.0     |

**Coefficient of Utilization**



REPORT NUMBER: P940421


CATALOG NUMBER: GALN-SB3C-727-U-SL4-HSS

**LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:**

| Zone |             | Lumens | % Fixture | Zone Rating/Lumen Limit |      |         |
|------|-------------|--------|-----------|-------------------------|------|---------|
|      |             |        |           | B                       | U    | G       |
| FL   | (0°-30°)    | 965.6  | 6.6       |                         |      |         |
| FM   | (30°-60°)   | 4891.1 | 33.6      |                         |      |         |
| FH   | (60°-80°)   | 6525.9 | 44.9      |                         |      | G3/7500 |
| FVH  | (80°-90°)   | 287.5  | 2.0       |                         |      | G3/500  |
| BL   | (0°-30°)    | 461.2  | 3.2       | B1/500                  |      |         |
| BM   | (30°-60°)   | 1153.7 | 7.9       | B2/2500                 |      |         |
| BH   | (60°-80°)   | 261.7  | 1.8       | B1/500                  |      | G1/500  |
| BVH  | (80°-90°)   | 2.2    | 0.0       |                         |      | G0/10   |
| UL   | (90°-100°)  | 0.0    | 0.0       |                         | U0/0 |         |
| UH   | (100°-180°) | 0.0    | 0.0       |                         | U0/0 |         |

**BUG Rating: B2-U0-G3**

Type IV Short



REPORT NUMBER: P940421

CATALOG NUMBER: GALN-SB3C-727-U-SL4-HSS

**CANDELA DISTRIBUTION (FULL):**

|       | 0°     | 5°     | 15°    | 25°     | 35°     | 40°     | 45°     | 55°    | 65°    | 75°    | 85°    |
|-------|--------|--------|--------|---------|---------|---------|---------|--------|--------|--------|--------|
| 0°    | 1926.4 | 1926.4 | 1926.4 | 1926.4  | 1926.4  | 1926.4  | 1926.4  | 1926.4 | 1926.4 | 1926.4 | 1926.4 |
| 2.5°  | 1984.5 | 1992.2 | 1987.8 | 1979.0  | 1976.8  | 1972.4  | 1966.9  | 1964.8 | 1957.1 | 1950.5 | 1942.8 |
| 5°    | 2040.4 | 2048.0 | 2042.6 | 2030.5  | 2025.0  | 2019.5  | 2011.9  | 2005.3 | 1990.0 | 1975.7 | 1958.2 |
| 7.5°  | 2101.7 | 2108.3 | 2101.7 | 2084.2  | 2075.4  | 2068.9  | 2057.9  | 2048.0 | 2030.5 | 2009.7 | 1987.8 |
| 10°   | 2169.7 | 2175.2 | 2165.3 | 2142.3  | 2128.0  | 2118.2  | 2108.3  | 2097.3 | 2080.9 | 2057.9 | 2031.6 |
| 12.5° | 2233.2 | 2239.8 | 2224.5 | 2197.1  | 2180.6  | 2170.8  | 2159.8  | 2151.0 | 2134.6 | 2112.7 | 2085.3 |
| 15°   | 2291.3 | 2301.2 | 2274.9 | 2245.3  | 2226.7  | 2219.0  | 2208.0  | 2202.5 | 2191.6 | 2176.2 | 2151.0 |
| 17.5° | 2335.1 | 2341.7 | 2314.3 | 2279.3  | 2258.4  | 2253.0  | 2245.3  | 2248.6 | 2246.4 | 2238.7 | 2222.3 |
| 20°   | 2372.4 | 2376.8 | 2340.6 | 2297.9  | 2274.9  | 2276.0  | 2273.8  | 2284.7 | 2289.1 | 2289.1 | 2288.0 |
| 22.5° | 2418.4 | 2419.5 | 2373.5 | 2319.8  | 2292.4  | 2300.1  | 2303.4  | 2315.4 | 2324.2 | 2332.9 | 2352.7 |
| 25°   | 2478.7 | 2476.5 | 2421.7 | 2348.3  | 2324.2  | 2335.1  | 2342.8  | 2347.2 | 2357.1 | 2371.3 | 2416.2 |
| 27.5° | 2568.5 | 2562.0 | 2491.8 | 2394.3  | 2365.8  | 2375.7  | 2389.9  | 2387.7 | 2383.4 | 2394.3 | 2469.9 |
| 30°   | 2682.5 | 2673.7 | 2580.6 | 2459.0  | 2432.7  | 2441.4  | 2445.8  | 2426.1 | 2394.3 | 2404.2 | 2517.0 |
| 32.5° | 2863.3 | 2848.0 | 2718.7 | 2531.3  | 2490.7  | 2500.6  | 2495.1  | 2454.6 | 2407.5 | 2417.3 | 2564.2 |
| 35°   | 3177.8 | 3140.5 | 2957.5 | 2682.5  | 2556.5  | 2545.5  | 2532.4  | 2492.9 | 2434.9 | 2425.0 | 2603.6 |
| 37.5° | 3846.2 | 3780.5 | 3468.2 | 2977.3  | 2705.5  | 2634.3  | 2593.7  | 2554.3 | 2464.4 | 2425.0 | 2648.5 |
| 40°   | 4600.1 | 4533.3 | 4172.8 | 3470.4  | 2953.2  | 2832.6  | 2736.2  | 2626.6 | 2495.1 | 2439.2 | 2718.7 |
| 42.5° | 5386.9 | 5313.5 | 4943.1 | 4081.8  | 3307.1  | 3059.5  | 2879.7  | 2684.7 | 2545.5 | 2483.1 | 2811.8 |
| 45°   | 6265.7 | 6173.7 | 5689.4 | 4719.6  | 3821.0  | 3436.4  | 3111.0  | 2804.1 | 2633.2 | 2560.9 | 2938.9 |
| 47.5° | 7192.8 | 7073.3 | 6433.4 | 5338.7  | 4374.4  | 3958.0  | 3533.9  | 3017.8 | 2762.5 | 2677.0 | 3111.0 |
| 50°   | 8014.6 | 7896.3 | 7201.6 | 5986.3  | 4891.6  | 4454.4  | 4016.1  | 3313.7 | 2956.5 | 2841.4 | 3342.2 |
| 52.5° | 8605.3 | 8515.4 | 7900.7 | 6654.8  | 5429.7  | 4920.1  | 4453.3  | 3657.8 | 3201.9 | 3051.8 | 3615.0 |
| 55°   | 9000.9 | 8918.7 | 8396.0 | 7288.1  | 6055.4  | 5432.9  | 4884.0  | 4031.4 | 3497.8 | 3303.8 | 3916.4 |
| 57.5° | 9240.8 | 9193.7 | 8754.3 | 7853.6  | 6675.6  | 5994.0  | 5377.1  | 4442.3 | 3846.2 | 3600.8 | 4252.8 |
| 60°   | 9326.3 | 9287.9 | 8976.7 | 8392.7  | 7425.1  | 6667.9  | 5956.7  | 4905.9 | 4269.2 | 3938.3 | 4598.0 |
| 62.5° | 9098.4 | 9106.0 | 9136.7 | 9031.5  | 8215.2  | 7456.9  | 6651.5  | 5462.5 | 4738.2 | 4320.7 | 4922.3 |
| 65°   | 8025.6 | 8089.2 | 8672.1 | 9739.4  | 9261.6  | 8445.3  | 7535.8  | 6141.9 | 5275.2 | 4755.7 | 5179.8 |
| 67.5° | 6644.9 | 6736.9 | 7462.4 | 10153.6 | 10377.2 | 9728.5  | 8767.4  | 7007.6 | 5915.1 | 5198.4 | 5277.3 |
| 70°   | 5086.7 | 5185.3 | 6064.1 | 10067.1 | 11421.5 | 11131.1 | 10290.6 | 8108.9 | 6578.1 | 5505.3 | 5028.6 |
| 72.5° | 3630.4 | 3680.8 | 4373.3 | 9296.7  | 11849.9 | 12086.6 | 11412.7 | 9152.1 | 6916.7 | 5335.4 | 4101.6 |
| 75°   | 2551.0 | 2542.2 | 3001.4 | 7486.5  | 11182.6 | 11970.5 | 11019.3 | 8587.7 | 6259.2 | 4238.5 | 2529.1 |
| 77.5° | 1111.1 | 1113.3 | 1499.0 | 4546.4  | 8925.2  | 10223.8 | 9159.7  | 5379.3 | 4363.5 | 2246.4 | 1067.3 |
| 80°   | 288.2  | 297.0  | 550.1  | 1810.3  | 5373.8  | 6747.9  | 5586.4  | 2364.7 | 2016.3 | 547.9  | 203.8  |
| 82.5° | 101.9  | 108.5  | 253.1  | 568.7   | 1982.3  | 3094.5  | 2487.5  | 756.1  | 526.0  | 156.7  | 54.8   |
| 85°   | 29.6   | 35.1   | 135.9  | 174.2   | 409.8   | 874.4   | 603.8   | 146.8  | 129.3  | 81.1   | 14.2   |
| 87.5° | 0.0    | 4.4    | 27.4   | 24.1    | 24.1    | 16.4    | 30.7    | 16.4   | 20.8   | 9.9    | 4.4    |
| 90°   | 0.0    | 0.0    | 0.0    | 0.0     | 0.0     | 0.0     | 0.0     | 0.0    | 0.0    | 0.0    | 0.0    |

REPORT NUMBER: P940421

CATALOG NUMBER: GALN-SB3C-727-U-SL4-HSS

**CANDELA DISTRIBUTION (continued):**

|       | 90°    | 95°    | 105°   | 115°   | 125°   | 135°   | 145°   | 155°   | 165°   | 175°   | 180°   |
|-------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 0°    | 1926.4 | 1926.4 | 1926.4 | 1926.4 | 1926.4 | 1926.4 | 1926.4 | 1926.4 | 1926.4 | 1926.4 | 1926.4 |
| 2.5°  | 1936.3 | 1928.6 | 1912.2 | 1894.6 | 1878.2 | 1862.8 | 1858.5 | 1842.0 | 1834.4 | 1835.5 | 1834.4 |
| 5°    | 1946.1 | 1931.9 | 1900.1 | 1861.8 | 1822.3 | 1777.4 | 1740.1 | 1687.5 | 1642.6 | 1637.1 | 1633.8 |
| 7.5°  | 1972.4 | 1949.4 | 1897.9 | 1823.4 | 1724.8 | 1601.0 | 1485.9 | 1371.9 | 1307.3 | 1272.2 | 1270.0 |
| 10°   | 2013.0 | 1982.3 | 1903.4 | 1760.9 | 1551.6 | 1330.3 | 1156.1 | 1012.5 | 939.1  | 905.1  | 898.6  |
| 12.5° | 2061.2 | 2027.2 | 1912.2 | 1654.6 | 1328.1 | 1037.7 | 849.2  | 761.6  | 746.2  | 744.0  | 742.9  |
| 15°   | 2129.1 | 2091.9 | 1922.0 | 1511.1 | 1085.9 | 790.1  | 703.5  | 704.6  | 716.6  | 723.2  | 722.1  |
| 17.5° | 2204.7 | 2167.5 | 1907.8 | 1335.8 | 847.0  | 675.0  | 672.8  | 682.7  | 700.2  | 706.8  | 705.7  |
| 20°   | 2281.4 | 2246.4 | 1857.4 | 1129.8 | 684.9  | 643.2  | 652.0  | 663.0  | 680.5  | 689.3  | 689.3  |
| 22.5° | 2360.3 | 2329.7 | 1777.4 | 910.6  | 618.0  | 620.2  | 631.2  | 642.1  | 661.9  | 671.7  | 671.7  |
| 25°   | 2444.7 | 2418.4 | 1671.1 | 729.8  | 589.5  | 596.1  | 610.4  | 623.5  | 644.3  | 656.4  | 656.4  |
| 27.5° | 2530.2 | 2510.5 | 1550.5 | 609.3  | 563.2  | 570.9  | 587.3  | 604.9  | 625.7  | 639.9  | 641.0  |
| 30°   | 2623.3 | 2612.4 | 1454.1 | 564.3  | 538.0  | 544.6  | 563.2  | 583.0  | 606.0  | 623.5  | 625.7  |
| 32.5° | 2718.7 | 2716.5 | 1407.0 | 597.2  | 515.0  | 519.4  | 535.8  | 555.6  | 584.1  | 606.0  | 608.2  |
| 35°   | 2812.9 | 2817.3 | 1379.6 | 690.4  | 507.4  | 495.3  | 506.3  | 523.8  | 557.8  | 585.2  | 589.5  |
| 37.5° | 2933.4 | 2944.4 | 1378.5 | 791.2  | 526.0  | 471.2  | 478.9  | 490.9  | 520.5  | 552.3  | 557.8  |
| 40°   | 3113.2 | 3171.2 | 1448.6 | 877.7  | 558.9  | 449.3  | 451.5  | 453.7  | 469.0  | 495.3  | 504.1  |
| 42.5° | 3352.0 | 3521.9 | 1701.8 | 936.9  | 572.0  | 429.6  | 421.9  | 409.8  | 407.6  | 421.9  | 429.6  |
| 45°   | 3649.0 | 3946.0 | 2146.7 | 969.8  | 558.9  | 407.6  | 386.8  | 355.0  | 343.0  | 352.8  | 352.8  |
| 47.5° | 3998.6 | 4410.6 | 2673.7 | 977.4  | 536.9  | 380.2  | 343.0  | 301.3  | 291.5  | 294.8  | 293.7  |
| 50°   | 4339.3 | 4759.0 | 3137.3 | 913.9  | 500.8  | 345.2  | 294.8  | 259.7  | 253.1  | 254.2  | 254.2  |
| 52.5° | 4640.7 | 4878.5 | 3268.8 | 763.8  | 452.6  | 302.4  | 253.1  | 229.0  | 224.6  | 224.6  | 223.5  |
| 55°   | 4840.1 | 4749.2 | 2914.8 | 584.1  | 392.3  | 258.6  | 217.0  | 204.9  | 202.7  | 201.6  | 199.4  |
| 57.5° | 4881.8 | 4328.4 | 2201.4 | 421.9  | 306.8  | 218.1  | 192.9  | 186.3  | 181.9  | 177.5  | 175.3  |
| 60°   | 4732.7 | 3627.1 | 1401.5 | 294.8  | 230.1  | 186.3  | 170.9  | 166.6  | 157.8  | 149.0  | 145.7  |
| 62.5° | 4410.6 | 2739.5 | 775.8  | 204.9  | 185.2  | 158.9  | 151.2  | 145.7  | 129.3  | 115.1  | 110.7  |
| 65°   | 3977.7 | 1821.2 | 343.0  | 160.0  | 151.2  | 133.7  | 129.3  | 121.6  | 101.9  | 85.5   | 82.2   |
| 67.5° | 3542.7 | 1048.7 | 154.5  | 128.2  | 121.6  | 109.6  | 106.3  | 100.8  | 86.6   | 71.2   | 69.0   |
| 70°   | 3046.3 | 531.5  | 106.3  | 101.9  | 94.2   | 83.3   | 86.6   | 85.5   | 71.2   | 58.1   | 55.9   |
| 72.5° | 2268.3 | 264.1  | 80.0   | 76.7   | 67.9   | 59.2   | 71.2   | 70.1   | 55.9   | 43.8   | 41.6   |
| 75°   | 1284.3 | 130.4  | 58.1   | 53.7   | 40.5   | 43.8   | 57.0   | 53.7   | 38.4   | 28.5   | 26.3   |
| 77.5° | 509.5  | 66.8   | 38.4   | 32.9   | 24.1   | 29.6   | 41.6   | 36.2   | 19.7   | 12.1   | 11.0   |
| 80°   | 117.2  | 32.9   | 19.7   | 14.2   | 11.0   | 17.5   | 21.9   | 13.1   | 5.5    | 1.1    | 0.0    |
| 82.5° | 32.9   | 14.2   | 6.6    | 5.5    | 5.5    | 6.6    | 5.5    | 2.2    | 0.0    | 0.0    | 0.0    |
| 85°   | 11.0   | 6.6    | 2.2    | 1.1    | 1.1    | 1.1    | 1.1    | 0.0    | 0.0    | 0.0    | 0.0    |
| 87.5° | 4.4    | 2.2    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 90°   | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |

(END OF REPORT)