

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: McGRAW-EDISON

Report Number: P823407

Luminaire Tested: **TTN-D2-830-U-DL**

Issue Date: 4/16/2024

**Test Information**

Test Method: LM-79-08  
Report Number: P823407  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2312-254-11)  
Test Lab: INNOVATION CENTER  
Issue Date: 4/16/2024  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: MCGRAW-EDISON  
Catalog Number: TTN-D2-830-U-DL  
Description: TOPTIER NANO LED PARKING GARAGE LUMINAIRE  
3000K, 80 CRI LEDS AND DRIVE LANE DISTRIBUTION  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 4491 lumens  
Efficiency: N/A  
Efficacy: 105.7 lumens/watt  
Luminous Opening: Circular (Dia: 0.71' x H: 0')  
IES Classification: Type IV - Short  
BUG Rating: B1 - U0 - G2  
  
Input Watts (W): 42.5  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT



REPORT NUMBER: P823407  
 CATALOG NUMBER: TTN-D2-830-U-DL

### Iso-Footcandle Lines of Horizontal Illumination


✕ Max cd  
 - - - 1/2 Max cd



Based on 25 foot mounting height. Maximum calculated value = 1 fc  
 Type IV - Short - N/A

REPORT NUMBER: P823407  
CATALOG NUMBER: TTN-D2-830-U-DL

### Luminous Intensity Polar Plot



— Vertical Plane Through 40-Deg Lateral    - - - Horizontal Cone Through 60-Deg Vertical

REPORT NUMBER: P823407  
 CATALOG NUMBER: TTN-D2-830-U-DL


**FLUX DISTRIBUTION:**

		Downward	Upward	Total
<b>House Side</b>	Lumens	956.4	0.0	956.4
	% Fixture	21.3	0.0	21.3
<b>Street Side</b>	Lumens	3534.6	0.0	3534.6
	% Fixture	78.7	0.0	78.7
<b>Total</b>	Lumens	4491.0	0.0	4491.0
	% Fixture	100.0	0.0	100.0

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	35.7	0.8
10°-20°	113.8	2.5
20°-30°	240.5	5.4
30°-40°	439.5	9.8
40°-50°	714.2	15.9
50°-60°	992.7	22.1
60°-70°	1029.1	22.9
70°-80°	737.4	16.4
80°-90°	188.0	4.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	4491.0	100.0
0°-180°	4491.0	100.0

**Coefficient of Utilization**




REPORT NUMBER: P823407  
 CATALOG NUMBER: TTN-D2-830-U-DL

**LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:**

Zone	Lumens	% Fixture	Zone Rating/Lumen Limit		
			B	U	G
FL (0°-30°)	262.8	5.9			
FM (30°-60°)	1676.9	37.3			
FH (60°-80°)	1438.3	32.0			G1/1800
FVH (80°-90°)	156.6	3.5			G2/225
BL (0°-30°)	127.2	2.8	B1/500		
BM (30°-60°)	469.5	10.5	B1/1000		
BH (60°-80°)	328.3	7.3	B1/500		G1/500
BVH (80°-90°)	31.4	0.7			G1/100
UL (90°-100°)	0.0	0.0		U0/0	
UH (100°-180°)	0.0	0.0		U0/0	

**BUG Rating: B1-U0-G2**

Type IV Short





REPORT NUMBER: P823407

CATALOG NUMBER: TTN-D2-830-U-DL

**CANDELA DISTRIBUTION (FULL):**

	0°	5°	15°	25°	35°	40°	45°	55°	65°	75°	85°
0°	378.2	378.2	378.2	378.2	378.2	378.2	378.2	378.2	378.2	378.2	378.2
2.5°	405.5	405.5	405.5	405.5	401.6	401.6	397.7	393.8	389.9	386.0	378.2
5°	440.6	440.6	436.7	432.8	425.0	421.1	417.2	409.4	401.6	393.8	382.1
7.5°	456.2	456.2	456.2	452.3	440.6	436.7	428.9	417.2	405.5	393.8	378.2
10°	483.5	483.5	479.6	475.7	464.0	460.1	452.3	436.7	417.2	397.7	378.2
12.5°	518.6	514.7	510.8	506.9	495.2	487.4	475.7	460.1	436.7	413.3	389.9
15°	561.5	553.7	553.7	545.9	534.2	522.5	514.7	491.3	467.9	436.7	405.5
17.5°	608.3	604.4	600.5	592.7	581.0	573.2	561.5	534.2	503.0	464.0	428.9
20°	666.8	659.0	662.9	651.2	639.5	635.6	616.1	584.9	545.9	503.0	460.1
22.5°	737.0	729.2	729.2	717.5	709.7	701.9	682.4	647.3	596.6	549.8	495.2
25°	815.0	807.2	807.2	799.4	791.6	783.8	760.4	721.4	662.9	604.4	542.0
27.5°	900.8	893.0	893.0	889.1	869.6	857.9	838.4	795.5	737.0	662.9	588.8
30°	990.4	982.6	990.4	982.6	970.9	947.6	924.2	877.4	811.1	729.2	639.5
32.5°	1060.6	1060.6	1064.5	1072.3	1064.5	1045.0	1017.7	978.7	889.1	787.7	686.3
35°	1142.5	1142.5	1150.3	1162.0	1158.1	1138.6	1111.3	1068.4	974.8	854.0	737.0
37.5°	1232.2	1232.2	1240.0	1259.5	1251.7	1240.0	1220.5	1165.9	1060.6	920.3	791.6
40°	1329.7	1325.8	1333.6	1360.9	1364.8	1349.2	1325.8	1271.2	1150.3	1006.0	850.1
42.5°	1427.2	1423.3	1438.9	1466.2	1470.1	1466.2	1442.8	1380.4	1243.9	1091.8	908.6
45°	1524.7	1524.7	1548.1	1591.0	1610.4	1602.7	1583.2	1505.2	1360.9	1181.5	986.5
47.5°	1626.0	1626.0	1657.2	1711.8	1735.2	1731.3	1723.5	1629.9	1474.0	1275.1	1052.8
50°	1704.0	1704.0	1754.7	1817.1	1856.1	1871.7	1832.7	1746.9	1571.5	1357.0	1107.4
52.5°	1782.0	1782.0	1832.7	1930.2	1969.2	1992.6	1941.9	1852.2	1680.6	1431.1	1158.1
55°	1821.0	1828.8	1899.0	1992.6	2055.0	2043.3	2062.8	1941.9	1750.8	1485.7	1189.3
57.5°	1824.9	1836.6	1914.6	2012.1	2082.3	2078.4	2082.3	1973.1	1778.1	1497.4	1193.2
60°	1805.4	1824.9	1895.1	1992.6	2058.9	2090.1	2051.1	1953.6	1762.5	1485.7	1189.3
62.5°	1758.6	1797.6	1871.7	1945.8	2043.3	2055.0	2023.8	1941.9	1719.6	1474.0	1169.8
65°	1653.3	1696.2	1801.5	1887.3	1965.3	1980.9	1945.8	1875.6	1676.7	1419.4	1107.4
67.5°	1548.1	1575.4	1665.0	1797.6	1852.2	1867.8	1856.1	1774.2	1602.7	1310.2	1033.3
70°	1427.2	1462.3	1532.5	1668.9	1723.5	1719.6	1754.7	1661.1	1489.6	1216.6	955.4
72.5°	1263.4	1314.1	1384.3	1497.4	1563.7	1540.3	1594.9	1516.9	1341.4	1099.6	850.1
75°	1072.3	1115.2	1204.9	1294.6	1368.7	1341.4	1384.3	1329.7	1169.8	959.3	729.2
77.5°	857.9	908.6	990.4	1072.3	1123.0	1123.0	1142.5	1095.7	970.9	787.7	596.6
80°	635.6	682.4	756.5	815.0	861.8	865.7	885.2	861.8	748.7	612.2	456.2
82.5°	421.1	444.5	510.8	557.6	604.4	600.5	631.7	616.1	522.5	421.1	304.2
85°	179.4	195.0	249.6	288.6	331.4	315.9	358.7	354.8	280.8	202.8	136.5
87.5°	7.8	11.7	11.7	7.8	11.7	3.9	11.7	15.6	11.7	7.8	7.8
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P823407

CATALOG NUMBER: TTN-D2-830-U-DL

**CANDELA DISTRIBUTION (continued):**

	90°	95°	105°	115°	125°	135°	145°	155°	165°	175°	180°
0°	378.2	378.2	378.2	378.2	378.2	378.2	378.2	378.2	378.2	378.2	378.2
2.5°	378.2	374.3	366.5	362.6	358.7	350.9	350.9	347.0	347.0	347.0	343.1
5°	378.2	370.4	362.6	350.9	343.1	335.3	327.5	319.8	315.9	315.9	312.0
7.5°	370.4	362.6	350.9	339.2	327.5	312.0	304.2	288.6	284.7	280.8	280.8
10°	370.4	362.6	343.1	327.5	312.0	296.4	284.7	269.1	257.4	253.5	253.5
12.5°	374.3	362.6	343.1	323.6	304.2	284.7	269.1	253.5	241.8	234.0	234.0
15°	389.9	374.3	350.9	323.6	300.3	276.9	261.3	241.8	230.1	222.3	222.3
17.5°	409.4	393.8	358.7	327.5	300.3	273.0	253.5	234.0	222.3	214.5	210.6
20°	436.7	413.3	374.3	331.4	300.3	273.0	249.6	230.1	214.5	206.7	206.7
22.5°	467.9	440.6	389.9	339.2	304.2	273.0	249.6	226.2	210.6	202.8	202.8
25°	506.9	471.8	413.3	354.8	312.0	276.9	249.6	226.2	210.6	202.8	202.8
27.5°	549.8	510.8	436.7	370.4	319.8	280.8	249.6	226.2	210.6	202.8	202.8
30°	588.8	545.9	460.1	386.0	331.4	284.7	253.5	230.1	214.5	206.7	202.8
32.5°	631.7	577.1	483.5	401.6	339.2	292.5	257.4	234.0	214.5	206.7	206.7
35°	674.6	616.1	506.9	421.1	350.9	300.3	261.3	237.9	218.4	210.6	210.6
37.5°	721.4	659.0	534.2	436.7	362.6	308.1	269.1	241.8	222.3	214.5	214.5
40°	776.0	701.9	561.5	456.2	374.3	315.9	273.0	249.6	230.1	222.3	222.3
42.5°	826.7	740.9	588.8	471.8	386.0	323.6	280.8	253.5	237.9	230.1	230.1
45°	877.4	787.7	616.1	491.3	397.7	335.3	288.6	265.2	245.7	237.9	237.9
47.5°	935.9	830.6	647.3	506.9	409.4	343.1	296.4	273.0	253.5	249.6	245.7
50°	982.6	861.8	666.8	522.5	417.2	350.9	304.2	276.9	261.3	253.5	253.5
52.5°	1025.5	893.0	682.4	530.3	421.1	354.8	312.0	284.7	269.1	261.3	261.3
55°	1048.9	904.7	694.1	530.3	425.0	358.7	312.0	284.7	269.1	265.2	261.3
57.5°	1048.9	904.7	686.3	522.5	417.2	350.9	308.1	280.8	269.1	261.3	261.3
60°	1033.3	893.0	666.8	506.9	405.5	339.2	300.3	273.0	261.3	257.4	257.4
62.5°	1009.9	873.5	651.2	487.4	389.9	323.6	288.6	261.3	253.5	253.5	249.6
65°	947.6	815.0	616.1	460.1	366.5	304.2	273.0	249.6	241.8	237.9	234.0
67.5°	881.3	760.4	561.5	428.9	335.3	284.7	253.5	234.0	222.3	222.3	218.4
70°	815.0	701.9	510.8	386.0	300.3	261.3	230.1	210.6	202.8	202.8	202.8
72.5°	725.3	627.8	452.3	339.2	265.2	230.1	206.7	187.2	183.3	183.3	179.4
75°	620.0	534.2	382.1	288.6	222.3	195.0	175.5	156.0	156.0	156.0	156.0
77.5°	506.9	432.8	304.2	230.1	175.5	156.0	144.3	128.7	128.7	128.7	128.7
80°	382.1	319.8	222.3	167.7	128.7	113.1	105.3	97.5	101.4	101.4	97.5
82.5°	249.6	210.6	140.4	105.3	81.9	74.1	74.1	66.3	70.2	70.2	70.2
85°	109.2	93.6	58.5	46.8	39.0	39.0	39.0	35.1	39.0	39.0	39.0
87.5°	7.8	7.8	7.8	7.8	7.8	7.8	7.8	0.0	3.9	7.8	3.9
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

(END OF REPORT)