

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: McGRAW-EDISON

Report Number: P833680

Luminaire Tested: **TTN-D2-830-U-MQ-CG-UPL1**

Issue Date: 5/15/2024

**Test Information**

Test Method: LM-79-08  
Report Number: P833680  
REPORT IS FROM IESNA LM-79-08 TEST DATA - UPLIGHT (G3-2308-121-4) AND  
Test Lab: INNOVATION CENTER  
Issue Date: 5/15/2024  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: McGRAW-EDISON  
Catalog Number: TTN-D2-830-U-MQ-CG-UPL1  
Description: TOPTIER NANO LED PARKING GARAGE LUMINAIRE WITH UPLIGHT  
3000K, 80 CRI LEDS AND MEDIUM DISTRIBUTION WITH CLEAR GLASS  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 5098.8 lumens  
Efficiency: N/A  
Efficacy: 113.1 lumens/watt  
Luminous Opening: Vertical Cylinder (Dia: 0.71' x H: 0.1')  
IES Classification: Type V - Short  
BUG Rating: B2 - U3 - G1  
  
Input Watts (W): 45.1  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT



REPORT NUMBER: P833680  
 CATALOG NUMBER: TTN-D2-830-U-MQ-CG-UPL1

### Iso-Footcandle Lines of Horizontal Illumination


✕ Max cd  
 - - - 1/2 Max cd



Based on 25 foot mounting height. Maximum calculated value = 1.8 fc  
 Type V - Short - N/A

REPORT NUMBER: P833680  
CATALOG NUMBER: TTN-D2-830-U-MQ-CG-UPL1

### Luminous Intensity Polar Plot



REPORT NUMBER: P833680

CATALOG NUMBER: TTN-D2-830-U-MQ-CG-UPL1


**FLUX DISTRIBUTION:**

		Downward	Upward	Total
<b>House Side</b>	Lumens	2401.7	147.7	2549.4
	% Fixture	47.1	2.9	50.0
<b>Street Side</b>	Lumens	2401.7	147.7	2549.4
	% Fixture	47.1	2.9	50.0
<b>Total</b>	Lumens	4803.3	295.5	5098.8
	% Fixture	94.2	5.8	100.0

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	107.3	2.1
10°-20°	310.4	6.1
20°-30°	499.3	9.8
30°-40°	667.1	13.1
40°-50°	810.5	15.9
50°-60°	941.7	18.5
60°-70°	868.8	17.0
70°-80°	508.6	10.0
80°-90°	89.5	1.8
90°-100°	6.6	0.1
100°-110°	67.0	1.3
110°-120°	98.0	1.9
120°-130°	56.9	1.1
130°-140°	30.1	0.6
140°-150°	17.9	0.4
150°-160°	11.0	0.2
160°-170°	6.0	0.1
170°-180°	2.0	0.0
0°-90°	4803.3	94.2
0°-180°	5098.8	100.0

**Coefficient of Utilization**




REPORT NUMBER: P833680  
 CATALOG NUMBER: TTN-D2-830-U-MQ-CG-UPL1

**LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:**

Zone	Lumens	% Fixture	Zone Rating/Lumen Limit		
			B	U	G
FL (0°-30°)	458.5	9.0			
FM (30°-60°)	1209.6	23.7			
FH (60°-80°)	688.7	13.5			G1/1800
FVH (80°-90°)	44.8	0.9			G1/100
BL (0°-30°)	458.5	9.0	B1/500		
BM (30°-60°)	1209.6	23.7	B2/2500		
BH (60°-80°)	688.7	13.5	B2/1000		G1/1800
BVH (80°-90°)	44.8	0.9			G1/100
UL (90°-100°)	6.6	0.1		U1/10	
UH (100°-180°)	288.9	5.7		U3/500	

**BUG Rating: B2-U3-G1**

Type V Short





REPORT NUMBER: P833680

CATALOG NUMBER: TTN-D2-830-U-MQ-CG-UPL1

**CANDELA DISTRIBUTION (FULL):**

	0°	5°	15°	25°	35°	45°	55°	65°	75°	85°	90°
0°	1142.6	1142.6	1142.6	1142.6	1142.6	1142.6	1142.6	1142.6	1142.6	1142.6	1142.6
2.5°	1130.9	1134.8	1130.9	1130.9	1130.9	1130.9	1130.9	1130.9	1130.9	1130.9	1134.8
5°	1134.8	1134.8	1134.8	1134.8	1130.9	1130.9	1130.9	1130.9	1130.9	1134.8	1134.8
7.5°	1123.1	1123.1	1123.1	1123.1	1123.1	1119.2	1123.1	1123.1	1123.1	1123.1	1123.1
10°	1111.4	1111.4	1111.4	1111.4	1111.4	1111.4	1111.4	1111.4	1111.4	1111.4	1111.4
12.5°	1103.6	1103.6	1103.6	1103.6	1103.6	1103.6	1103.6	1103.6	1103.6	1099.7	1099.7
15°	1095.8	1095.8	1095.8	1095.8	1099.7	1099.7	1095.8	1095.8	1095.8	1095.8	1095.8
17.5°	1088.0	1088.0	1088.0	1088.0	1091.9	1091.9	1091.9	1088.0	1088.0	1088.0	1088.0
20°	1080.2	1080.2	1080.2	1080.2	1084.1	1084.1	1084.1	1084.1	1084.1	1080.2	1080.2
22.5°	1076.3	1076.3	1076.3	1076.3	1080.2	1080.2	1080.2	1080.2	1076.3	1076.3	1076.3
25°	1072.4	1076.3	1076.3	1076.3	1080.2	1084.1	1084.1	1080.2	1076.3	1072.4	1072.4
27.5°	1076.3	1076.3	1076.3	1080.2	1080.2	1084.1	1084.1	1080.2	1076.3	1076.3	1076.3
30°	1072.4	1072.4	1072.4	1076.3	1080.2	1084.1	1080.2	1080.2	1076.3	1072.4	1072.4
32.5°	1064.6	1064.6	1068.5	1072.4	1076.3	1076.3	1076.3	1072.4	1068.5	1064.6	1064.6
35°	1056.8	1056.8	1056.8	1060.7	1068.5	1068.5	1068.5	1064.6	1060.7	1056.8	1052.9
37.5°	1045.1	1049.0	1049.0	1056.8	1060.7	1064.6	1060.7	1056.8	1049.0	1045.1	1045.1
40°	1037.3	1037.3	1041.2	1049.0	1056.8	1056.8	1052.9	1049.0	1041.2	1037.3	1037.3
42.5°	1025.6	1025.6	1033.4	1041.2	1052.9	1052.9	1049.0	1041.2	1033.4	1025.6	1025.6
45°	1025.6	1025.6	1033.4	1049.0	1056.8	1064.6	1056.8	1049.0	1033.4	1025.6	1021.7
47.5°	1029.5	1029.5	1037.3	1056.8	1072.4	1080.2	1068.5	1052.9	1037.3	1029.5	1025.6
50°	1021.7	1025.6	1041.2	1060.7	1080.2	1084.1	1080.2	1056.8	1041.2	1021.7	1021.7
52.5°	1025.6	1025.6	1045.1	1076.3	1095.8	1103.6	1095.8	1076.3	1041.2	1021.7	1021.7
55°	1017.8	1013.9	1041.2	1076.3	1107.5	1123.1	1107.5	1076.3	1037.3	1013.9	1010.0
57.5°	982.7	982.7	1017.8	1052.9	1091.9	1099.7	1088.0	1052.9	1013.9	982.7	974.9
60°	935.9	939.8	974.9	1013.9	1049.0	1052.9	1045.1	1013.9	974.9	939.8	928.1
62.5°	885.2	893.0	928.1	967.1	1010.0	1017.8	1006.1	967.1	920.3	896.9	877.4
65°	811.1	822.8	861.8	904.7	951.5	947.6	947.6	900.8	865.7	826.7	807.2
67.5°	729.3	741.0	768.2	826.7	865.7	861.8	857.9	826.7	768.2	741.0	729.3
70°	639.6	647.4	674.7	733.2	768.2	772.1	760.4	729.3	674.7	655.2	635.7
72.5°	534.3	538.2	577.2	624.0	659.1	655.2	651.3	624.0	573.3	553.8	530.4
75°	421.2	425.1	460.2	503.1	530.4	526.5	522.6	503.1	460.2	436.8	417.3
77.5°	315.9	312.0	347.1	378.3	393.9	397.8	390.0	374.4	343.2	323.7	312.0
80°	206.7	202.8	234.0	257.4	269.1	269.1	265.2	253.5	230.1	214.5	206.7
82.5°	117.0	113.1	132.6	148.2	159.9	156.0	152.1	144.3	132.6	120.9	113.1
85°	42.9	42.9	54.6	62.4	70.2	70.2	66.3	62.4	50.7	46.8	42.9
87.5°	3.9	3.9	7.8	11.7	11.7	11.7	7.8	7.8	3.9	3.9	3.9
90°	2.5	2.5	3.0	3.0	3.0	3.0	3.0	3.0	3.0	2.5	2.5
92.5°	2.5	2.5	2.5	3.5	4.0	3.5	4.0	3.0	3.0	2.5	2.5
95°	3.0	3.0	3.5	4.5	5.6	6.1	6.1	3.5	3.5	3.0	3.0
97.5°	4.0	4.5	4.5	5.6	9.1	16.7	10.1	5.1	5.1	4.5	4.0
100°	6.6	7.1	7.1	12.6	26.8	35.9	25.8	13.1	9.6	7.1	7.1
102.5°	21.2	22.2	27.3	40.9	60.7	55.1	46.5	44.0	30.3	24.3	23.3
105°	54.1	53.6	57.6	68.2	84.9	83.4	76.8	69.8	60.2	55.6	55.6
107.5°	71.3	71.3	74.8	83.9	96.6	112.7	114.2	90.5	79.4	74.3	73.8
110°	80.4	80.4	83.4	91.0	107.7	130.4	129.4	111.7	98.1	91.5	90.5



REPORT NUMBER: P833680  
 CATALOG NUMBER: TTN-D2-830-U-MQ-CG-UPL1

**CANDELA DISTRIBUTION (continued):**

	0°	5°	15°	25°	35°	45°	55°	65°	75°	85°	90°
112.5°	82.4	82.9	86.9	98.6	116.8	126.9	122.3	115.3	109.2	104.1	103.1
115°	85.4	85.4	90.0	101.1	111.2	115.3	110.2	104.6	100.6	98.6	99.6
117.5°	84.4	85.9	86.9	93.0	99.6	102.6	100.1	92.5	89.5	88.5	86.9
120°	78.4	78.4	79.4	82.4	85.9	87.5	86.4	81.4	78.9	78.4	77.3
122.5°	69.8	70.3	69.8	71.3	73.8	75.3	74.3	70.3	69.3	69.3	68.2
125°	61.2	61.2	60.7	61.7	63.2	62.7	63.2	61.2	60.7	60.7	60.2
127.5°	55.1	54.6	53.6	54.1	54.6	54.6	55.1	53.1	53.6	54.1	53.6
130°	49.0	49.0	48.0	48.0	48.0	47.0	48.0	47.0	47.5	48.0	48.5
132.5°	43.5	43.5	42.0	41.5	41.5	41.5	42.0	41.5	42.5	43.5	43.5
135°	38.9	38.9	37.4	37.9	37.9	37.4	37.9	37.4	38.4	38.9	38.9
137.5°	35.4	35.4	34.4	34.4	34.4	33.9	34.4	34.4	34.9	35.9	36.4
140°	32.4	32.4	31.8	31.8	31.3	31.8	31.8	31.8	32.4	32.9	32.9
142.5°	30.8	30.3	29.8	29.3	29.8	29.8	29.8	29.3	29.8	30.8	30.8
145°	28.3	28.3	27.8	27.8	27.8	28.3	27.8	27.8	28.3	28.3	28.8
147.5°	26.8	26.8	26.3	26.8	26.8	26.8	26.8	26.3	26.8	26.8	27.3
150°	26.3	25.8	25.3	25.8	25.8	25.3	25.3	25.3	25.3	25.8	25.8
152.5°	24.8	24.8	24.3	24.8	24.3	24.3	24.3	24.3	24.3	24.8	25.3
155°	23.8	23.8	23.3	23.8	23.8	23.8	23.8	23.8	23.8	23.8	23.8
157.5°	22.7	23.3	22.7	22.7	22.7	22.7	22.7	22.7	22.7	23.3	23.3
160°	22.2	22.2	22.2	22.2	21.7	21.7	21.7	22.2	22.2	22.2	22.7
162.5°	21.7	21.7	21.7	21.7	21.2	21.2	21.2	21.2	21.7	21.7	22.2
165°	21.7	21.2	21.2	21.2	20.7	20.7	20.7	20.7	21.2	21.7	21.2
167.5°	20.7	20.7	20.7	20.7	20.7	20.2	20.2	20.7	20.7	20.7	21.2
170°	20.7	20.7	20.2	20.2	20.2	20.2	20.2	20.2	20.2	20.2	20.7
172.5°	20.7	20.7	20.7	20.7	20.2	20.2	20.2	20.2	20.2	20.7	20.7
175°	20.7	20.7	20.7	20.7	20.2	20.2	20.2	20.7	20.7	20.7	20.2
177.5°	20.7	20.7	20.7	20.7	20.2	20.7	20.7	20.7	20.7	20.7	20.7
180°	20.7	20.7	20.7	20.7	20.7	20.7	20.7	20.7	20.7	20.7	20.7

(END OF REPORT)