

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: McGRAW-EDISON

Report Number: P833697

Luminaire Tested: **TTN-D2-830-U-WQ-SG-UPL3**

Issue Date: 5/15/2024

**Test Information**

Test Method: LM-79-08  
Report Number: P833697  
REPORT IS FROM IESNA LM-79-08 TEST DATA - UPLIGHT (G3-2308-121-4) AND  
Test Lab: INNOVATION CENTER  
Issue Date: 5/15/2024  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: McGRAW-EDISON  
Catalog Number: TTN-D2-830-U-WQ-SG-UPL3  
Description: TOPTIER NANO LED PARKING GARAGE LUMINAIRE WITH UPLIGHT  
3000K, 80 CRI LEDS AND WIDE DISTRIBUTION WITH SOLITE GLASS  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 5150.7 lumens  
Efficiency: N/A  
Efficacy: 104.1 lumens/watt  
Luminous Opening: Vertical Cylinder (Dia: 0.71' x H: 0.1')  
IES Classification: Type V - Short  
BUG Rating: B2 - U4 - G1  
  
Input Watts (W): 49.5  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT



REPORT NUMBER: P833697  
 CATALOG NUMBER: TTN-D2-830-U-WQ-SG-UPL3

### Iso-Footcandle Lines of Horizontal Illumination


✕ Max cd  
 - - - 1/2 Max cd



Based on 25 foot mounting height. Maximum calculated value = 0.8 fc  
 Type V - Short - N/A

REPORT NUMBER: P833697  
CATALOG NUMBER: TTN-D2-830-U-WQ-SG-UPL3

### Luminous Intensity Polar Plot



— Vertical Plane Through 45-Deg Lateral    - - - Horizontal Cone Through 52.5-Deg Vertical

REPORT NUMBER: P833697  
 CATALOG NUMBER: TTN-D2-830-U-WQ-SG-UPL3


**FLUX DISTRIBUTION:**

		Downward	Upward	Total
<b>House Side</b>	Lumens	2205.0	370.3	2575.3
	% Fixture	42.8	7.2	50.0
<b>Street Side</b>	Lumens	2205.0	370.3	2575.3
	% Fixture	42.8	7.2	50.0
<b>Total</b>	Lumens	4410.0	740.7	5150.7
	% Fixture	85.6	14.4	100.0

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	43.3	0.8
10°-20°	142.3	2.8
20°-30°	300.3	5.8
30°-40°	548.5	10.6
40°-50°	873.2	17.0
50°-60°	1055.9	20.5
60°-70°	887.8	17.2
70°-80°	470.6	9.1
80°-90°	88.1	1.7
90°-100°	16.5	0.3
100°-110°	168.0	3.3
110°-120°	245.6	4.8
120°-130°	142.5	2.8
130°-140°	75.5	1.5
140°-150°	44.9	0.9
150°-160°	27.6	0.5
160°-170°	15.1	0.3
170°-180°	4.9	0.1
0°-90°	4410.0	85.6
0°-180°	5150.7	100.0

**Coefficient of Utilization**




REPORT NUMBER: P833697  
 CATALOG NUMBER: TTN-D2-830-U-WQ-SG-UPL3

**LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:**

Zone	Lumens	% Fixture	Zone Rating/Lumen Limit		
			B	U	G
FL (0°-30°)	242.9	4.7			
FM (30°-60°)	1238.8	24.1			
FH (60°-80°)	679.2	13.2			G1/1800
FVH (80°-90°)	44.0	0.9			G1/100
BL (0°-30°)	242.9	4.7	B1/500		
BM (30°-60°)	1238.8	24.1	B2/2500		
BH (60°-80°)	679.2	13.2	B2/1000		G1/1800
BVH (80°-90°)	44.0	0.9			G1/100
UL (90°-100°)	16.5	0.3		U2/50	
UH (100°-180°)	724.2	14.1		U4/1000	

**BUG Rating: B2-U4-G1**  
 Type V Short





REPORT NUMBER: P833697

CATALOG NUMBER: TTN-D2-830-U-WQ-SG-UPL3

**CANDELA DISTRIBUTION (FULL):**

	0°	5°	15°	25°	35°	45°	55°	65°	75°	85°	90°
0°	448.3	448.3	448.3	448.3	448.3	448.3	448.3	448.3	448.3	448.3	448.3
2.5°	448.3	448.3	448.3	448.3	448.3	448.3	448.3	448.3	448.3	448.3	448.3
5°	452.1	452.1	448.3	452.1	452.1	452.1	452.1	452.1	452.1	452.1	452.1
7.5°	452.1	452.1	452.1	456.0	456.0	456.0	456.0	452.1	452.1	452.1	452.1
10°	459.9	459.9	459.9	459.9	459.9	459.9	459.9	459.9	459.9	459.9	459.9
12.5°	471.6	471.6	471.6	471.6	471.6	471.6	471.6	471.6	471.6	471.6	471.6
15°	491.1	491.1	491.1	491.1	495.0	495.0	495.0	491.1	491.1	491.1	491.1
17.5°	514.5	514.5	518.4	518.4	522.3	522.3	522.3	518.4	514.5	518.4	514.5
20°	549.6	549.6	549.6	553.5	557.4	557.4	557.4	549.6	549.6	549.6	549.6
22.5°	588.6	588.6	588.6	592.5	596.4	596.4	596.4	588.6	588.6	588.6	588.6
25°	635.3	635.3	635.3	639.2	643.1	647.0	647.0	639.2	635.3	635.3	631.4
27.5°	682.1	682.1	689.9	693.8	697.7	697.7	697.7	689.9	686.0	686.0	686.0
30°	736.7	736.7	744.5	748.4	756.2	756.2	756.2	744.5	740.6	736.7	736.7
32.5°	787.4	791.3	799.1	806.9	814.6	814.6	818.5	803.0	795.2	791.3	791.3
35°	841.9	845.8	853.6	865.3	873.1	877.0	880.9	865.3	853.6	849.7	849.7
37.5°	904.3	908.2	919.9	931.6	947.2	955.0	958.9	935.5	916.0	908.2	908.2
40°	974.5	978.4	990.1	1005.6	1021.2	1029.0	1032.9	1009.5	990.1	982.3	978.4
42.5°	1032.9	1040.7	1052.4	1075.8	1091.4	1103.1	1103.1	1075.8	1052.4	1040.7	1040.7
45°	1087.5	1095.3	1114.8	1138.2	1161.6	1173.2	1169.4	1142.1	1114.8	1099.2	1095.3
47.5°	1130.4	1138.2	1161.6	1188.8	1220.0	1231.7	1227.8	1196.6	1161.6	1142.1	1138.2
50°	1153.8	1157.7	1184.9	1223.9	1255.1	1266.8	1259.0	1227.8	1188.8	1161.6	1157.7
52.5°	1149.9	1153.8	1184.9	1227.8	1262.9	1274.6	1262.9	1227.8	1188.8	1157.7	1153.8
55°	1126.5	1130.4	1161.6	1208.3	1243.4	1255.1	1243.4	1208.3	1165.5	1134.3	1130.4
57.5°	1083.6	1087.5	1118.7	1165.5	1204.4	1216.1	1200.5	1161.6	1118.7	1087.5	1087.5
60°	1021.2	1025.1	1056.3	1107.0	1142.1	1153.8	1134.3	1103.1	1060.2	1025.1	1021.2
62.5°	939.4	939.4	974.5	1025.1	1056.3	1071.9	1052.4	1017.3	978.4	939.4	943.3
65°	841.9	838.0	873.1	919.9	955.0	966.7	947.2	916.0	877.0	841.9	841.9
67.5°	740.6	740.6	767.9	806.9	838.0	849.7	830.2	803.0	771.8	740.6	740.6
70°	631.4	631.4	650.9	689.9	717.2	725.0	713.3	686.0	658.7	631.4	631.4
72.5°	522.3	518.4	537.9	569.1	592.5	600.3	588.6	573.0	541.8	522.3	522.3
75°	413.2	409.3	421.0	448.3	467.7	475.5	463.8	452.1	428.8	413.2	413.2
77.5°	307.9	304.0	315.7	339.1	350.8	354.7	346.9	339.1	319.6	307.9	307.9
80°	210.5	206.6	214.4	230.0	241.7	241.7	237.8	233.9	218.3	210.5	214.4
82.5°	124.7	120.8	128.6	140.3	148.1	144.2	144.2	140.3	128.6	124.7	124.7
85°	54.6	50.7	54.6	62.4	70.2	66.3	66.3	66.3	58.5	54.6	54.6
87.5°	7.8	7.8	7.8	11.7	15.6	11.7	11.7	11.7	7.8	7.8	7.8
90°	6.3	6.3	7.6	7.6	7.6	7.6	7.6	7.6	7.6	6.3	6.3
92.5°	6.3	6.3	6.3	8.9	10.1	8.9	10.1	7.6	7.6	6.3	6.3
95°	7.6	7.6	8.9	11.4	13.9	15.2	15.2	8.9	8.9	7.6	7.6
97.5°	10.1	11.4	11.4	13.9	22.8	41.8	25.3	12.7	12.7	11.4	10.1
100°	16.5	17.7	17.7	31.7	67.2	90.0	64.6	32.9	24.1	17.7	17.7
102.5°	53.2	55.8	68.4	102.6	152.1	138.1	116.6	110.2	76.0	60.8	58.3
105°	135.6	134.3	144.5	171.1	212.9	209.1	192.6	174.9	150.8	139.4	139.4
107.5°	178.7	178.7	187.5	210.4	242.0	282.6	286.4	226.8	198.9	186.3	185.0
110°	201.5	201.5	209.1	228.1	269.9	326.9	324.4	280.0	245.8	229.4	226.8



REPORT NUMBER: P833697  
 CATALOG NUMBER: TTN-D2-830-U-WQ-SG-UPL3

**CANDELA DISTRIBUTION (continued):**

	0°	5°	15°	25°	35°	45°	55°	65°	75°	85°	90°
112.5°	206.5	207.8	218.0	247.1	292.7	318.1	306.7	288.9	273.7	261.0	258.5
115°	214.2	214.2	225.6	253.4	278.8	288.9	276.2	262.3	252.2	247.1	249.6
117.5°	211.6	215.4	218.0	233.2	249.6	257.2	250.9	231.9	224.3	221.8	218.0
120°	196.4	196.4	198.9	206.5	215.4	219.2	216.7	204.0	197.7	196.4	193.9
122.5°	174.9	176.1	174.9	178.7	185.0	188.8	186.3	176.1	173.6	173.6	171.1
125°	153.3	153.3	152.1	154.6	158.4	157.1	158.4	153.3	152.1	152.1	150.8
127.5°	138.1	136.9	134.3	135.6	136.9	136.9	138.1	133.1	134.3	135.6	134.3
130°	122.9	122.9	120.4	120.4	120.4	117.8	120.4	117.8	119.1	120.4	121.6
132.5°	109.0	109.0	105.2	103.9	103.9	103.9	105.2	103.9	106.4	109.0	109.0
135°	97.6	97.6	93.8	95.0	95.0	93.8	95.0	93.8	96.3	97.6	97.6
137.5°	88.7	88.7	86.2	86.2	86.2	84.9	86.2	86.2	87.4	90.0	91.2
140°	81.1	81.1	79.8	79.8	78.6	79.8	79.8	79.8	81.1	82.4	82.4
142.5°	77.3	76.0	74.8	73.5	74.8	74.8	74.8	73.5	74.8	77.3	77.3
145°	71.0	71.0	69.7	69.7	69.7	71.0	69.7	69.7	71.0	71.0	72.2
147.5°	67.2	67.2	65.9	67.2	67.2	67.2	67.2	65.9	67.2	67.2	68.4
150°	65.9	64.6	63.4	64.6	64.6	63.4	63.4	63.4	63.4	64.6	64.6
152.5°	62.1	62.1	60.8	62.1	60.8	60.8	60.8	60.8	60.8	62.1	63.4
155°	59.6	59.6	58.3	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6
157.5°	57.0	58.3	57.0	57.0	57.0	57.0	57.0	57.0	57.0	58.3	58.3
160°	55.8	55.8	55.8	55.8	54.5	54.5	54.5	55.8	55.8	55.8	57.0
162.5°	54.5	54.5	54.5	54.5	53.2	53.2	53.2	53.2	54.5	54.5	55.8
165°	54.5	53.2	53.2	53.2	52.0	52.0	52.0	52.0	53.2	54.5	53.2
167.5°	52.0	52.0	52.0	52.0	52.0	50.7	50.7	52.0	52.0	52.0	53.2
170°	52.0	52.0	50.7	50.7	50.7	50.7	50.7	50.7	50.7	50.7	52.0
172.5°	52.0	52.0	52.0	52.0	50.7	50.7	50.7	50.7	50.7	52.0	52.0
175°	52.0	52.0	52.0	52.0	50.7	50.7	50.7	52.0	52.0	52.0	50.7
177.5°	52.0	52.0	52.0	52.0	50.7	52.0	52.0	52.0	52.0	52.0	52.0
180°	52.0	52.0	52.0	52.0	52.0	52.0	52.0	52.0	52.0	52.0	52.0

(END OF REPORT)